



ISO/IEC 29341-5-11

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

**Information technology – UPnP Device Architecture –  
Part 5-11: Digital Security Camera Device Control Protocol –  
Digital Security Camera Settings Service**



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2008 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

## **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

## **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



ISO/IEC 29341-5-11

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

**Information technology – UPnP Device Architecture –  
Part 5-11: Digital Security Camera Device Control Protocol –  
Digital Security Camera Settings Service**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

H

## CONTENTS

|   |           |
|---|-----------|
| FOREWORD .....  | 4         |
| ORIGINAL UPNP DOCUMENTS (informative) .....                     | 6         |
| <b>1. Overview and Scope .....</b>                              | <b>8</b>  |
| <b>2. Service Modeling Definitions .....</b>                    | <b>9</b>  |
| 2.1. ServiceType .....  | 9         |
| 2.2. State Variables .....                                      | 9         |
| 2.2.1. AutomaticWhiteBalance .....                              | 9         |
| 2.2.2. FixedWhiteBalance .....                                  | 9         |
| 2.2.3. AvailableRotations .....                                 | 9         |
| 2.2.4. DefaultRotation .....                                    | 10        |
| 2.2.5. Brightness .....   | 10        |
| 2.2.6. ColorSaturation .....                                    | 10        |
| 2.3. Eventing and Moderation .....                              | 11        |
| 2.4. Actions .....  | 12        |
| 2.4.1. SetAutomaticWhiteBalance .....                           | 12        |
| 2.4.2. GetAutomaticWhiteBalance .....                           | 12        |
| 2.4.3. SetFixedWhiteBalance .....                               | 13        |
| 2.4.4. GetFixedWhiteBalance .....                               | 13        |
| 2.4.5. GetAvailableRotations .....                              | 13        |
| 2.4.6. SetDefaultRotation .....                                 | 14        |
| 2.4.7. GetDefaultRotation .....                                 | 14        |
| 2.4.8. SetBrightness .....                                      | 14        |
| 2.4.9. GetBrightness .....                                      | 15        |
| 2.4.10. IncreaseBrightness .....                                | 15        |
| 2.4.11. DecreaseBrightness .....                                | 15        |
| 2.4.12. SetColorSaturation .....                                | 16        |
| 2.4.13. GetColorSaturation .....                                | 16        |
| 2.4.14. IncreaseColorSaturation .....                           | 16        |
| 2.4.15. DecreaseColorSaturation .....                           | 17        |
| 2.4.16. Non-Standard Actions Implemented by a UPnP Vendor ..... | 17        |
| 2.4.17. Common Error Codes .....                                | 17        |
| 2.5. Theory of Operation .....                                  | 18        |
| <b>3. XML Service Description .....</b>                         | <b>19</b> |
| <b>4. Test .....</b>  | <b>22</b> |

## LIST OF TABLES

|  |    |
|--|----|
| Table 1: State Variables .....   | 9  |
| Table 2: Event Moderation.....   | 11 |
| Table 3: Actions .....   | 12 |
| Table 4: Arguments for <u><a href="#">SetAutomaticWhiteBalance</a></u> ..... | 12 |
| Table 5: Arguments for <u><a href="#">GetAutomaticWhiteBalance</a></u> ..... | 13 |
| Table 6: Arguments for <u><a href="#">SetFixedWhiteBalance</a></u> .....     | 13 |
| Table 7: Arguments for <u><a href="#">GetFixedWhiteBalance</a></u> .....     | 13 |
| Table 8: Arguments for <u><a href="#">GetAvailableRotations</a></u> .....    | 13 |
| Table 9: Arguments for <u><a href="#">SetDefaultRotation</a></u> .....       | 14 |
| Table 10: Arguments for <u><a href="#">GetDefaultRotation</a></u> .....      | 14 |
| Table 11: Arguments for <u><a href="#">SetBrightness</a></u> .....           | 14 |
| Table 12: Arguments for <u><a href="#">GetBrightness</a></u> .....           | 15 |
| Table 13: Arguments for <u><a href="#">SetColorSaturation</a></u> .....      | 16 |
| Table 14: Arguments for <u><a href="#">GetColorSaturation</a></u> .....      | 16 |
| Table 15: Common Error Codes.....  | 17 |

## **INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –**

### **Part 5-11: Digital Security Camera Device Control Protocol – Digital Security Camera Settings Service**

#### **FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation  
Standards Licensing Department  
5200 NE Elam Young Parkway  
MS: JFS-98  
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US;  
10/783 524 / US

Information may be obtained from:

Microsoft Corporation  
One Microsoft Way  
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S  
High Tech campus, building 44 3A21  
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)  
High Tech campus 60  
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.  
1-3-7 Shiromi, Chuoh-ku  
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company  
1501 Page Mill Road  
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.  
416 Maetan-3 Dong, Yeongtang-Gu,  
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-5-11 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

## ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

| UPnP Document Title                             | ISO/IEC 29341 Part  |
|---|---------------------|
| UPnP Device Architecture 1.0                    | ISO/IEC 29341-1     |
| UPnP Basic:1 Device                             | ISO/IEC 29341-2     |
| UPnP AV Architecture:1                          | ISO/IEC 29341-3-1   |
| UPnP MediaRenderer:1 Device                     | ISO/IEC 29341-3-2   |
| UPnP MediaServer:1 Device                       | ISO/IEC 29341-3-3   |
| UPnP AVTransport:1 Service                      | ISO/IEC 29341-3-10  |
| UPnP ConnectionManager:1 Service                | ISO/IEC 29341-3-11  |
| UPnP ContentDirectory:1 Service                 | ISO/IEC 29341-3-12  |
| UPnP RenderingControl:1 Service                 | ISO/IEC 29341-3-13  |
| UPnP MediaRenderer:2 Device                     | ISO/IEC 29341-4-2   |
| UPnP MediaServer:2 Device                       | ISO/IEC 29341-4-3   |
| UPnP AV Datastructure Template:1                | ISO/IEC 29341-4-4   |
| UPnP AVTransport:2 Service                      | ISO/IEC 29341-4-10  |
| UPnP ConnectionManager:2 Service                | ISO/IEC 29341-4-11  |
| UPnP ContentDirectory:2 Service                 | ISO/IEC 29341-4-12  |
| UPnP RenderingControl:2 Service                 | ISO/IEC 29341-4-13  |
| UPnP ScheduledRecording:1                       | ISO/IEC 29341-4-14  |
| UPnP DigitalSecurityCamera:1 Device             | ISO/IEC 29341-5-1   |
| UPnP DigitalSecurityCameraMotionImage:1 Service | ISO/IEC 29341-5-10  |
| UPnP DigitalSecurityCameraSettings:1 Service    | ISO/IEC 29341-5-11  |
| UPnP DigitalSecurityCameraStillImage:1 Service  | ISO/IEC 29341-5-12  |
| UPnP HVAC_System:1 Device                       | ISO/IEC 29341-6-1   |
| UPnP HVAC_ZoneThermostat:1 Device               | ISO/IEC 29341-6-2   |
| UPnP ControlValve:1 Service                     | ISO/IEC 29341-6-10  |
| UPnP HVAC_FanOperatingMode:1 Service            | ISO/IEC 29341-6-11  |
| UPnP FanSpeed:1 Service                         | ISO/IEC 29341-6-12  |
| UPnP HouseStatus:1 Service                      | ISO/IEC 29341-6-13  |
| UPnP HVAC_SetpointSchedule:1 Service            | ISO/IEC 29341-6-14  |
| UPnP TemperatureSensor:1 Service                | ISO/IEC 29341-6-15  |
| UPnP TemperatureSetpoint:1 Service              | ISO/IEC 29341-6-16  |
| UPnP HVAC_UserOperatingMode:1 Service           | ISO/IEC 29341-6-17  |
| UPnP BinaryLight:1 Device                       | ISO/IEC 29341-7-1   |
| UPnP DimmableLight:1 Device                     | ISO/IEC 29341-7-2   |
| UPnP Dimming:1 Service                          | ISO/IEC 29341-7-10  |
| UPnP SwitchPower:1 Service                      | ISO/IEC 29341-7-11  |
| UPnP InternetGatewayDevice:1 Device             | ISO/IEC 29341-8-1   |
| UPnP LANDevice:1 Device                         | ISO/IEC 29341-8-2   |
| UPnP WANDevice:1 Device                         | ISO/IEC 29341-8-3   |
| UPnP WANConnectionDevice:1 Device               | ISO/IEC 29341-8-4   |
| UPnP WLANAccessPointDevice:1 Device             | ISO/IEC 29341-8-5   |
| UPnP LANHostConfigManagement:1 Service          | ISO/IEC 29341-8-10  |
| UPnP Layer3Forwarding:1 Service                 | ISO/IEC 29341-8-11  |
| UPnP LinkAuthentication:1 Service               | ISO/IEC 29341-8-12  |
| UPnP RadiusClient:1 Service                     | ISO/IEC 29341-8-13  |
| UPnP WANCableLinkConfig:1 Service               | ISO/IEC 29341-8-14  |
| UPnP WANCommonInterfaceConfig:1 Service         | ISO/IEC 29341-8-15  |
| UPnP WANDSLLinkConfig:1 Service                 | ISO/IEC 29341-8-16  |
| UPnP WANEthernetLinkConfig:1 Service            | ISO/IEC 29341-8-17  |
| UPnP WANIPConnection:1 Service                  | ISO/IEC 29341-8-18  |
| UPnP WANPOTSLinkConfig:1 Service                | ISO/IEC 29341-8-19  |
| UPnP WANPPPConnection:1 Service                 | ISO/IEC 29341-8-20  |
| UPnP WLANConfiguration:1 Service                | ISO/IEC 29341-8-21  |
| UPnP Printer:1 Device                           | ISO/IEC 29341-9-1   |
| UPnP Scanner:1.0 Device                         | ISO/IEC 29341-9-2   |
| UPnP ExternalActivity:1 Service                 | ISO/IEC 29341-9-10  |
| UPnP Feeder:1.0 Service                         | ISO/IEC 29341-9-11  |
| UPnP PrintBasic:1 Service                       | ISO/IEC 29341-9-12  |
| UPnP Scan:1 Service                             | ISO/IEC 29341-9-13  |
| UPnP QoS Architecture:1.0                       | ISO/IEC 29341-10-1  |
| UPnP QoSDevice:1 Service                        | ISO/IEC 29341-10-10 |
| UPnP QoSManager:1 Service                       | ISO/IEC 29341-10-11 |
| UPnP QoSPolicyHolder:1 Service                  | ISO/IEC 29341-10-12 |
| UPnP QoS Architecture:2                         | ISO/IEC 29341-11-1  |
| UPnP QOS v2 Schema Files                        | ISO/IEC 29341-11-2  |



| <b>UPnP Document Title</b>         | <b>ISO/IEC 29341 Part</b> |
|------------------------------------|---------------------------|
| UPnP QosDevice:2 Service           | ISO/IEC 29341-11-10       |
| UPnP QosManager:2 Service          | ISO/IEC 29341-11-11       |
| UPnP QosPolicyHolder:2 Service     | ISO/IEC 29341-11-12       |
| UPnP RemoteUIClientDevice:1 Device | ISO/IEC 29341-12-1        |
| UPnP RemoteUIServerDevice:1 Device | ISO/IEC 29341-12-2        |
| UPnP RemoteUIClient:1 Service      | ISO/IEC 29341-12-10       |
| UPnP RemoteUIServer:1 Service      | ISO/IEC 29341-12-11       |
| UPnP DeviceSecurity:1 Service      | ISO/IEC 29341-13-10       |
| UPnP SecurityConsole:1 Service     | ISO/IEC 29341-13-11       |

## 1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version *1.0*.

This service provides *control* of the basic setting of the actual image generating part of the security camera. Security Camera Settings are global to the device and will affect the Security Camera Still and Motion Image services contained within the Security Camera device.

## 2. Service Modeling Definitions

### 2.1. ServiceType

A service that is compliant with this template is identified with the following service type: **urn:schemas-upnp-org:service: DigitalSecurityCameraSettings:1**.

### 2.2. State Variables

**Table 1: State Variables**

| Variable Name  | Req. or Opt.<br><sup>1</sup> | Data Type      | Allowed Value | Default Value | Eng. Units |
|--|------------------------------|----------------|---------------|---------------|------------|
| <u><a href="#">AutomaticWhiteBalance</a></u>   | <u>O</u>                     | <u>boolean</u> | <u>1,0</u>    | <u>1</u>      |            |
| <u><a href="#">FixedWhiteBalance</a></u>   | <u>R</u>                     | <u>ui4</u>     | <u>[0..1]</u> | <u>3000</u>   | <u>K</u>   |
| <u><a href="#">AvailableRotations</a></u>  | <u>O</u>                     | <u>string</u>  |               |               |            |
| <u><a href="#">DefaultRotation</a></u>   | <u>O</u>                     | <u>string</u>  |               |               |            |
| <u><a href="#">Brightness</a></u>  | <u>R</u>                     | <u>ui1</u>     | <u>0..100</u> | <u>50</u>     | <u>%</u>   |
| <u><a href="#">ColorSaturation</a></u>   | <u>R</u>                     | <u>ui1</u>     | <u>0..100</u> | <u>50</u>     | <u>%</u>   |
| <i>Non-standard state variables implemented by an UPnP vendor go <a href="#">here</a>.</i> | X                            | <i>TBD</i>     | <i>TBD</i>    | <i>TBD</i>    | <i>TBD</i> |

<sup>1</sup> R = Required, O = Optional, X = Non-standard.

#### 2.2.1. AutomaticWhiteBalance

White Balance describes what the eye perceives as white. This differs with ambient light. For instance an object does not have the same color if it is placed in a room lit by light bulbs which gives a rather red light as it would if the object was placed outdoors in bright sunlight (rather blue). The human eye automatically compensates for this difference in perceived color. Cameras must in a similar manner compensate for ambient light to avoid objects being reproduced with incorrect colors.

If automatic is ON white balance should be handled automatically by the camera.

If no automatic white balance is available in the device fixed white balance value shall be used.

#### 2.2.2. FixedWhiteBalance

Fixed White balance is used in environments of known or constant light environments. The unit used is the temperature of the light in Kelvin.

#### 2.2.3. AvailableRotations

The rotation in degrees of the image calculated from what is considered normal upright positioning (0) of the camera.

The value of this string should be a comma delimited list of all supported rotations.

The list order should be the lowest compression level first.

Example: 0, 90, 180, 270

This is a read only property.

#### **2.2.4. DefaultRotation**

The value of this string must be one of the supported rotations specified in AvailableRotations.

#### **2.2.5. Brightness**

Brightness is the attribute of a visual sensation according to which an area appears to emit more or less light. It is a relative value and the definition of the normal value is left to the manufacturer.

The Value 50 is the device specific normal value. This single value must be supported.

The value 100 shall give maximum brightness.

The value 0 shall give maximum darkness.

If the full range 0..100 is unsupported, the legal values shall be a sequence of numbers appropriately mapped onto the 1..100 scale. For instance: 2, 34,45,50,74,87.

The Actions up and down shall make a complete step to the next supported legal value.

The response to an attempt to set an unsupported but legal value shall result in the nearest *supported* legal value.

#### **2.2.6. ColorSaturation**

Color Saturation describes the colorfulness of an area judged in proportion to its brightness.

At least the value 0 or the value 50 must be supported.

0 means Black and white and is the only value that must be supported by black and white cameras.

50 means device specific normal color, if no color control is available in a color camera this value is the only supported legal value.

The value 100 means very colorful images

The value 0 means black and white images only.

If the full range 0..100 is unsupported, the legal values shall be a sequence of numbers appropriately mapped onto the 1..100 scale. For instance: 2, 34,45,50,74,87.

The Actions up and down shall make a complete step to the next supported legal value.

The response to an attempt to set an unsupported but legal value shall result in the nearest *supported* legal value.

## 2.3. Eventing and Moderation

Table 2: Event Moderation

| Variable Name  | Evented    | Moderated Event | Max Event Rate <sup>1</sup> | Logical Combination | Min Delta per Event <sup>2</sup> |
|--|------------|-----------------|-----------------------------|---------------------|----------------------------------|
| <u>AutomaticWhiteBalance</u>   | <u>Yes</u> | <u>Yes</u>      | <u>1</u>                    |                     | <u>None</u>                      |
| <u>FixedWhiteBalance</u>   | <u>Yes</u> | <u>Yes</u>      | <u>1</u>                    |                     | <u>None</u>                      |
| <u>AvailableRotations</u>  | <u>No</u>  | <u>No</u>       | <u>N/A</u>                  |                     | <u>N/A</u>                       |
| <u>DefaultRotation</u>   | <u>Yes</u> | <u>Yes</u>      | <u>1</u>                    |                     | <u>None</u>                      |
| <u>Brightness</u>  | <u>Yes</u> | <u>Yes</u>      | <u>1</u>                    |                     | <u>None</u>                      |
| <u>ColorSaturation</u>   | <u>Yes</u> | <u>Yes</u>      | <u>1</u>                    |                     | <u>None</u>                      |
| <i>Non-standard state variables implemented by an UPnP vendor go here.</i> | <i>TBD</i> | <i>TBD</i>      | <i>TBD</i>                  | <i>TBD</i>          | <i>TBD</i>                       |

<sup>1</sup> Determined by N, where Rate = (Event)/(N secs).

<sup>2</sup> (N) \* (allowedValueRange Step).

## 2.4. Actions

Immediately following this table is detailed information about these actions, including short descriptions of the actions, the effects of the actions on state variables, and error codes defined by the actions.

**Table 3: Actions**

| Name   | Req. or Opt. <sup>1</sup> |
|--|---------------------------|
| <u><a href="#">SetAutomaticWhiteBalance</a></u>                    | <u><a href="#">O</a></u>  |
| <u><a href="#">GetAutomaticWhiteBalance</a></u>                    | <u><a href="#">O</a></u>  |
| <u><a href="#">SetFixedWhiteBalance</a></u>                        | <u><a href="#">R</a></u>  |
| <u><a href="#">GetFixedWhiteBalance</a></u>                        | <u><a href="#">R</a></u>  |
| <u><a href="#">GetAvailableRotations</a></u>                       | <u><a href="#">O</a></u>  |
| <u><a href="#">SetDefaultRotation</a></u>                          | <u><a href="#">O</a></u>  |
| <u><a href="#">GetDefaultRotation</a></u>                          | <u><a href="#">O</a></u>  |
| <u><a href="#">SetBrightness</a></u>                               | <u><a href="#">R</a></u>  |
| <u><a href="#">GetBrightness</a></u>                               | <u><a href="#">R</a></u>  |
| <u><a href="#">IncreaseBrightness</a></u>                          | <u><a href="#">R</a></u>  |
| <u><a href="#">DecreaseBrightness</a></u>                          | <u><a href="#">R</a></u>  |
| <u><a href="#">SetColorSaturation</a></u>                          | <u><a href="#">R</a></u>  |
| <u><a href="#">GetColorSaturation</a></u>                          | <u><a href="#">R</a></u>  |
| <u><a href="#">IncreaseColorSaturation</a></u>                     | <u><a href="#">R</a></u>  |
| <u><a href="#">DecreaseColorSaturation</a></u>                     | <u><a href="#">R</a></u>  |
| <i>Non-standard actions implemented by an UPnP vendor go here.</i> | X                         |

<sup>1</sup> R = Required, O = Optional, X = Non-standard.

### 2.4.1. SetAutomaticWhiteBalance

Enable or disable Automatic White Balance algorithm. When disabled the current fixed white balance value will be used.

#### 2.4.1.1. Arguments

**Table 4: Arguments for [SetAutomaticWhiteBalance](#)**

| Argument  | Direction                 | relatedStateVariable                         |
|---|---------------------------|--|
| <u><a href="#">NewAutomaticWhiteBalance</a></u> | <u><a href="#">IN</a></u> | <u><a href="#">AutomaticWhiteBalance</a></u> |

#### 2.4.1.2. Effect on State

Changes the value of AutomaticWhiteBalance to NewAutomaticWhiteBalance.

### 2.4.2. GetAutomaticWhiteBalance

Get AutomaticWhiteBalance.

### 2.4.2.1. Arguments

**Table 5: Arguments for GetAutomaticWhiteBalance**

| Argument                        | Direction  | relatedStateVariable         |
|---------------------------------|------------|------------------------------|
| <u>RetAutomaticWhiteBalance</u> | <u>OUT</u> | <u>AutomaticWhiteBalance</u> |

### 2.4.3. SetFixedWhiteBalance

Set the value of the FixedWhiteBalance to NewFixedWhiteBalance.

#### 2.4.3.1. Arguments

**Table 6: Arguments for SetFixedWhiteBalance**

| Argument                    | Direction | relatedStateVariable     |
|-----------------------------|-----------|--------------------------|
| <u>NewFixedWhiteBalance</u> | <u>IN</u> | <u>FixedWhiteBalance</u> |

#### 2.4.3.2. Effect on State

Changes the value of FixedWhiteBalance to NewFixedWhiteBalance.  
AutomaticWhiteBalance is set to false.

### 2.4.4. GetFixedWhiteBalance

Get FixedWhiteBalance.

#### 2.4.4.1. Arguments

**Table 7: Arguments for GetFixedWhiteBalance**

| Argument                    | Direction  | relatedStateVariable     |
|-----------------------------|------------|--------------------------|
| <u>RetFixedWhiteBalance</u> | <u>OUT</u> | <u>FixedWhiteBalance</u> |

### 2.4.5. GetAvailableRotations

Get the list of supported rotations.

#### 2.4.5.1. Arguments

**Table 8: Arguments for GetAvailableRotations**

| Argument                     | Direction  | relatedStateVariable      |
|------------------------------|------------|---------------------------|
| <u>RetAvailableRotations</u> | <u>OUT</u> | <u>AvailableRotations</u> |

## 2.4.6. SetDefaultRotation

Set the default rotation of the image.

### 2.4.6.1. Arguments

Table 9: Arguments for SetDefaultRotation

| Argument           | Direction | relatedStateVariable   |
|--------------------|-----------|------------------------|
| <u>NewRotation</u> | <u>IN</u> | <u>DefaultRotation</u> |

### 2.4.6.2. Effect on State

Changes the value of DefaultRotation to NewRotation.

### 2.4.6.3. Errors

| errorCode  | errorDescription                 | Description  |
|------------|----------------------------------|--|
| <u>700</u> | <u>NewRotation not supported</u> | NewRotation is not one of the supported rotations specified in AvailableRotations. |

## 2.4.7. GetDefaultRotation

Get the default rotation.

### 2.4.7.1. Arguments

Table 10: Arguments for GetDefaultRotation

| Argument           | Direction  | relatedStateVariable   |
|--------------------|------------|------------------------|
| <u>RetRotation</u> | <u>OUT</u> | <u>DefaultRotation</u> |

## 2.4.8. SetBrightness

Set the value of the target brightness of the image. If set to a legal but by the device unsupported value the nearest supported value shall be set.

### 2.4.8.1. Arguments

Table 11: Arguments for SetBrightness

| Argument             | Direction | relatedStateVariable |
|----------------------|-----------|----------------------|
| <u>NewBrightness</u> | <u>IN</u> | <u>Brightness</u>    |

### 2.4.8.2. Effect on State

Changes the value of Brightness to NewBrightness.

### 2.4.8.3. Errors

| errorCode  | errorDescription                   | Description                             |
|------------|------------------------------------|---|
| <u>701</u> | <u>NewBrightness not supported</u> | NewBrightness is not a supported value. |



## 2.4.9. GetBrightness

Get the brightness.

### 2.4.9.1. Arguments

Table 12: Arguments for GetBrightness

| Argument             | Direction  | relatedStateVariable |
|----------------------|------------|----------------------|
| <u>RetBrightness</u> | <u>OUT</u> | <u>Brightness</u>    |

## 2.4.10. IncreaseBrightness

Increase brightness of the image to the nearest higher *supported* legal value.

### 2.4.10.1. Arguments

(None.)

### 2.4.10.2. Effect on State

The value of Brightness is being increased.

### 2.4.10.3. Errors

| errorCode  | errorDescription                   | Description                             |
|------------|------------------------------------|---|
| <u>701</u> | <u>NewBrightness not supported</u> | NewBrightness is not a supported value. |

## 2.4.11. DecreaseBrightness

Decrease brightness of the image to the nearest lower *supported* legal value.

### 2.4.11.1. Arguments

(None.)

### 2.4.11.2. Effect on State

The value of Brightness is being decreased.

### 2.4.11.3. Errors

| errorCode  | errorDescription                   | Description                             |
|------------|------------------------------------|---|
| <u>701</u> | <u>NewBrightness not supported</u> | NewBrightness is not a supported value. |

## 2.4.12.SetColorSaturation

Set the value of the target Color Saturation of the image. If set to a legal but by the device unsupported value the nearest supported value shall be set.

### 2.4.12.1.Arguments

Table 13: Arguments for SetColorSaturation

| Argument                  | Direction | relatedStateVariable   |
|---------------------------|-----------|------------------------|
| <u>NewColorSaturation</u> | <u>IN</u> | <u>ColorSaturation</u> |

### 2.4.12.2.Effect on State

The value of ColorSaturation is changed to NewColorSaturation.

### 2.4.12.3.Errors

| errorCode  | errorDescription                        | Description                                  |
|------------|---|--|
| <u>702</u> | <u>NewColorSaturation not supported</u> | NewColorSaturation is not a supported value. |

## 2.4.13.GetColorSaturation

Get the Color Saturation.

### 2.4.13.1.Arguments

Table 14: Arguments for GetColorSaturation

| Argument                  | Direction  | relatedStateVariable   |
|---------------------------|------------|------------------------|
| <u>RetColorSaturation</u> | <u>OUT</u> | <u>ColorSaturation</u> |

## 2.4.14.IncreaseColorSaturation

Increase ColorSaturation of the image to the nearest higher *supported* legal value.

### 2.4.14.1.Arguments

(None.)

### 2.4.14.2.Effect on State

The value of ColorSaturation is being increased.

### 2.4.14.3.Errors

| errorCode  | errorDescription                        | Description                                  |
|------------|---|--|
| <u>702</u> | <u>NewColorSaturation not supported</u> | NewColorSaturation is not a supported value. |

### 2.4.15. DecreaseColorSaturation

Decrease brightness of the image to the nearest lower *supported* legal value.

#### 2.4.15.1. Arguments

(None.)

#### 2.4.15.2. Effect on State

The value of ColorSaturation is being decreased.

#### 2.4.15.3. Errors

| errorCode  | errorDescription                        | Description                                  |
|------------|---|--|
| <u>702</u> | <u>NewColorSaturation not supported</u> | NewColorSaturation is not a supported value. |

### 2.4.16. Non-Standard Actions Implemented by a UPnP Vendor

To facilitate certification, non-standard actions implemented by UPnP vendors should be included in this service template. The UPnP Device Architecture lists naming requirements for non-standard actions (see the section on Description).

### 2.4.17. Common Error Codes

The following table lists error codes common to actions for this service type. If an action results in multiple errors, the most specific error should be returned.

**Table 15: Common Error Codes**

| errorCode      | errorDescription                        | Description  |
|----------------|---|--|
| 401            | Invalid Action                          | See UPnP Device Architecture section on Control.                                   |
| 402            | Invalid Args                            | See UPnP Device Architecture section on Control.                                   |
| 404            | Invalid Var                             | See UPnP Device Architecture section on Control.                                   |
| 501            | Action Failed                           | See UPnP Device Architecture section on Control.                                   |
| 600-699        | TBD                                     | Common action errors. Defined by UPnP Forum Technical Committee.                   |
| <u>700</u>     | <u>NewRotation not supported</u>        | NewRotation is not one of the supported rotations specified in AvailableRotations. |
| <u>701</u>     | <u>NewBrightness not supported</u>      | NewBrightness is not a supported value.  |
| <u>702</u>     | <u>NewColorSaturation not supported</u> | NewColorSaturation is not a supported value.                                       |
| <u>800-899</u> | <u>TBD</u>                              | <i>(Specified by UPnP vendor.)</i>   |

## 2.5. Theory of Operation

An instance of Digital Security Camera Settings Services may be embedded into a Digital Security Camera Device or other devices requiring this service.

This service provides control of basic settings of the actual image generating part of for instance a security camera. Settings are global to the device and will affect images generated by the device regardless of retrieval method. For instance if a device is equipped with an instance of the *Digital Security Camera Motion Image Service* and an instance of the *Digital Security Camera Still Image Service*, images “retrieved” using either of these services will all be affected by changes in the here described *Settings Service*

The algorithm and functionality of *Automatic White Balance* is vendor specific, this service description document does not set any requirements on the actual implementation.

The algorithms and functionality behind *Brightness and Color Saturation* are vendor specific, this service description document does not set any requirements on the actual implementation given that they are able to produce “normal” responses at the value 50, lowest at 0 and highest at 100.

### 3. XML Service Description

```

<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <actionList>
    <action>
      <name>SetAutomaticWhiteBalance</name>
      <argumentList>
        <argument>
          <name>NewAutomaticWhiteBalance</name>
          <relatedStateVariable>AutomaticWhiteBalance</relatedStateVariable>
          <direction>in</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetAutomaticWhiteBalance</name>
      <argumentList>
        <argument>
          <name>RetAutomaticWhiteBalance</name>
          <relatedStateVariable>AutomaticWhiteBalance</relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>SetFixedWhiteBalance</name>
      <argumentList>
        <argument>
          <name>NewFixedWhiteBalance</name>
          <relatedStateVariable>FixedWhiteBalance</relatedStateVariable>
          <direction>in</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetFixedWhiteBalance</name>
      <argumentList>
        <argument>
          <name>RetFixedWhiteBalance</name>
          <relatedStateVariable>FixedWhiteBalance</relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetAvailableRotations</name>
      <argumentList>
        <argument>
          <name>RetAvailableRotations</name>
          <relatedStateVariable>AvailableRotations</relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
  </actionList>
</scpd>

```

```

<action>
  <name>SetDefaultRotation</name>
  <argumentList>
    <argument>
      <name>NewRotation</name>
      <relatedStateVariable>DefaultRotation</relatedStateVariable>
      <direction>in</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>GetDefaultRotation</name>
  <argumentList>
    <argument>
      <name>RetRotation</name>
      <relatedStateVariable>DefaultRotation</relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>SetBrightness</name>
  <argumentList>
    <argument>
      <name>NewBrightness</name>
      <relatedStateVariable>Brightness</relatedStateVariable>
      <direction>in</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>GetBrightness</name>
  <argumentList>
    <argument>
      <name>RetBrightness</name>
      <relatedStateVariable>Brightness</relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>IncreaseBrightness</name>
</action>
<action>
  <name>DecreaseBrightness</name>
</action>
<action>
  <name>SetColorSaturation</name>
  <argumentList>
    <argument>
      <name>NewColorSaturation</name>
      <relatedStateVariable>ColorSaturation</relatedStateVariable>
      <direction>in</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>GetColorSaturation</name>
  <argumentList>
    <argument>
      <name>RetColorSaturation</name>
      <relatedStateVariable>ColorSaturation</relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>

```

```

    </argumentList>
  </action>
  <action>
    <name>IncreaseColorSaturation</name>
  </action>
  <action>
    <name>DecreaseColorSaturation</name>
  </action>
</actionList>
<serviceStateTable>
  <stateVariable sendEvents="yes">
    <name>AutomaticWhiteBalance</name>
    <dataType>boolean</dataType>
    <defaultValue>1</defaultValue>
    <allowedValueList>
      <allowedValue>1</allowedValue>
      <allowedValue>0</allowedValue>
    </allowedValueList>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>FixedWhiteBalance</name>
    <dataType>ui4</dataType>
    <defaultValue>3000</defaultValue>
    <allowedValueRange>
      <minimum>0</minimum>
      <maximum>maximum</maximum>
      <step>1</step>
    </allowedValueRange>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>AvailableRotations</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>DefaultRotation</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>Brightness</name>
    <dataType>ui1</dataType>
    <defaultValue>50</defaultValue>
    <allowedValueRange>
      <minimum>0</minimum>
      <maximum>100</maximum>
      <step>1</step>
    </allowedValueRange>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>ColorSaturation</name>
    <dataType>ui1</dataType>
    <defaultValue>50</defaultValue>
    <allowedValueRange>
      <minimum>0</minimum>
      <maximum>100</maximum>
      <step>1</step>
    </allowedValueRange>
  </stateVariable>
</serviceStateTable>
</scpd>

```

## 4. Test

Testing of the UPnP functions Addressing, Discovery, Description, Control (Syntax) and Eventing are performed by the UPnP Test Tool v1.1 based on the following documents:

- UPnP Device Architecture v1.0
- The Service Definitions in chapter 2 of this document
- The XML Service Description in chapter 3 of this document
- The UPnP Test Tool service template test file: *DigitalSecurityCameraSettings1.xml*
- The UPnP Test Tool service template test file: *DigitalSecurityCameraSettings1.SyntaxTests.xml*

The test suite does not include tests for Control Semantics, since it is felt that such tests would not provide a higher level of interoperability.





INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

3, rue de Varembé  
PO Box 131  
CH-1211 Geneva 20  
Switzerland

Tel: + 41 22 919 02 11  
Fax: + 41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)