

System.Threading.TimerCallback Delegate

```
[ILAsm]
.class public sealed serializable TimerCallback extends System.Delegate {
method public hidebysig newslot virtual instance void Invoke(object state)
}

[C#]
public delegate void TimerCallback(object state);
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.ICloneable**

Summary

Defines the shape of methods that are called by an instance of the `System.Threading.Timer` class.

Parameters

Parameter	Description
<i>state</i>	A <code>System.Object</code> containing application-specific information relevant to the methods invoked by instances of this delegate, or <code>null</code> .

Inherits From: System.Delegate

Library: BCL

Description

A `TimerCallback` delegate invokes its methods once after the start time elapses, and continues invoking its methods once per period until the `System.Threading.Timer.Dispose` method is called. [*Note:* The start time for a `System.Threading.Timer` is passed in the *dueTime* parameter of the `Timer` constructors, and the period is passed via the *period* parameter.]

1
2
3
4
5
6

[*Note:* For an example that demonstrates creating and using a `TimerCallback` delegate, see the `System.Threading.Timer` class.]