

System.UnhandledExceptionHandler

Delegate

```
[ILAsm]
.class public sealed serializable UnhandledExceptionHandler extends
System.Delegate { .method public hidebysig newslot virtual instance void
Invoke(object sender, class System.UnhandledExceptionEventArgs e) }

[C#]
public delegate void UnhandledExceptionHandler(object sender,
UnhandledExceptionEventArgs e);
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.ICloneable**

Summary

Defines the shape of methods that handle the event that is raised by the system for uncaught exceptions.

Parameters

Parameter	Description
<i>sender</i>	The application domain that handled the <code>System.AppDomain.UnhandledException</code> event.
<i>e</i>	A <code>System.UnhandledExceptionEventArgs</code> that contains the event data.

Inherits From: System.Delegate

Library: RuntimeInfrastructure

Description

A `System.UnhandledExceptionHandler` instance can only be specified for the default application domain that is created by the system to execute an application.

1 Specifying a `System.UnhandledExceptionHandler` for a `System.AppDomain`
2 created by an application has no effect.

3
4 [*Note:* A `System.UnhandledExceptionHandler` instance is used to specify
5 methods that are invoked in response to exceptions that are not caught. To associate an
6 instance of `UnhandledExceptionHandler` with an application domain, add the
7 `UnhandledExceptionHandler` to the `System.AppDomain.UnhandledException`
8 event. The methods referenced by the `UnhandledExceptionHandler` instance are
9 invoked whenever an object, typically a `System.Exception`, is thrown and is not
10 caught.]

11
12
13
14 [*Note:* For additional information about events, see Partitions I and II of the CLI
15 Specification.]