



IEC 61156-11

Edition 1.0 2019-05

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 11: Symmetrical single pair cables with transmission characteristics
up to 600 MHz – Horizontal floor wiring – Sectional specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-6678-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Installation considerations	8
4.1 General remarks	8
4.2 Bending radius of installed cable.....	8
4.3 Climatic conditions.....	8
5 Materials and cable construction	8
5.1 General remarks	8
5.2 Cable construction	9
5.3 Conductor	9
5.4 Insulation	9
5.5 Cable element.....	9
5.6 Screening of the cable element.....	9
5.7 Cable make-up.....	9
5.8 Screening of the cable core	9
5.9 Sheath	9
5.10 Identification	10
5.11 Finished cable	10
6 Characteristics and requirements	10
6.1 General remarks	10
6.2 Electrical characteristics and tests	10
6.2.1 Conductor resistance	10
6.2.2 Resistance unbalance.....	10
6.2.3 Dielectric strength.....	11
6.2.4 Insulation resistance	11
6.2.5 Mutual capacitance.....	11
6.2.6 Capacitance unbalance	11
6.2.7 Transfer impedance	11
6.2.8 Coupling attenuation.....	11
6.2.9 Current-carrying capacity.....	12
6.3 Transmission characteristics.....	12
6.3.1 Velocity of propagation (phase velocity).....	12
6.3.2 Phase delay and differential delay (delay skew).....	12
6.3.3 Attenuation (α).....	12
6.3.4 Unbalance attenuation (<i>TCL</i> and <i>EL TCTL</i>).....	13
6.3.5 Alien (exogenous) near-end crosstalk (<i>PS ANEXT</i>)	13
6.3.6 Alien (exogenous) far-end crosstalk (<i>PS AACR-F</i>).....	14
6.3.7 Alien (exogenous) crosstalk of bundled cables	14
6.3.8 Impedance.....	14
6.3.9 Return loss (<i>RL</i>).....	14
6.4 Mechanical and dimensional characteristics and requirements.....	15
6.4.1 Dimensional requirements	15
6.4.2 Elongation at break of the conductor.....	15
6.4.3 Tensile strength of the insulation	15

6.4.4	Elongation at break of the insulation	15
6.4.5	Adhesion of the insulation to the conductor.....	15
6.4.6	Elongation at break of the sheath	15
6.4.7	Tensile strength of the sheath.....	15
6.4.8	Crush test of the cable.....	15
6.4.9	Impact test of the cable	15
6.4.10	Bending under tension	16
6.4.11	Repeated bending of the cable	16
6.4.12	Tensile performance of the cable.....	16
6.4.13	Shock-test requirements of the cable	16
6.4.14	Bump-test requirements of the cable	16
6.4.15	Vibration-test requirements of a cable	16
6.5	Environmental characteristics	16
6.5.1	Shrinkage of the insulation	16
6.5.2	Wrapping test of the insulation after thermal ageing	16
6.5.3	Bending test of insulation at low temperature.....	16
6.5.4	Elongation at break of the sheath after ageing	16
6.5.5	Tensile strength of the sheath after ageing	16
6.5.6	Sheath pressure test at high temperature	16
6.5.7	Cold bend test of the cable	17
6.5.8	Heat shock test.....	17
6.5.9	Damp heat steady state	17
6.5.10	Solar radiation	17
6.5.11	Solvents and contaminating fluids.....	17
6.5.12	Salt mist and sulphur dioxide	17
6.5.13	Water immersion	17
6.5.14	Hygroscopicity	17
6.5.15	Wicking.....	17
6.5.16	Flame propagation characteristics of a single cable	17
6.5.17	Flame propagation characteristics of bunched cables	17
6.5.18	Halogen gas evolution	17
6.5.19	Smoke generation.....	18
6.5.20	Toxic gas emission	18
6.5.21	Integrated fire test method for cables in environmental air handling spaces.....	18
7	Bundled cable requirements	18
7.1	General.....	18
7.2	Single pairs sharing one sheath	18
7.2.1	General	18
7.2.2	Near-end crosstalk (<i>NEXT</i>).....	18
7.2.3	Attenuation to crosstalk ratio far-end (<i>PS ACR-F</i>)	19
	Annex A (informative) Blank Detail Specification	20
	Bibliography.....	25
	Table 1 – Transfer impedance	11
	Table 2 – Coupling attenuation	12
	Table 3 – Attenuation equation constants	13
	Table 4 – <i>TCL</i> requirements	13

Table 5 – <i>EL TCTL</i> requirements	13
Table 6 – <i>PS ANEXT</i> requirements	14
Table 7 – <i>PS AACR-F</i> requirements	14
Table 8 – <i>RL</i> requirements	15
Table 9 – <i>NEXT</i> and <i>PS NEXT</i> requirements	18
Table 10 – <i>ACR-F</i> and <i>PS ACR-F</i> requirements	19

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD
CABLES FOR DIGITAL COMMUNICATIONS –****Part 11: Symmetrical single pair cables with
transmission characteristics up to 600 MHz –
Horizontal floor wiring – Sectional specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-11 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
46C/1118/FDIS	46C/1123/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 11: Symmetrical single pair cables with transmission characteristics up to 600 MHz – Horizontal floor wiring – Sectional specification

1 Scope

This part of IEC 61156 describes cables intended to be used for transmission of 1 Gbps over a single twisted pair for office, home and industrial application. An example of existing application is 1000BASE-T1, see ISO/IEC TR 11801-9906¹. The transmission characteristics of these cables are specified up to a frequency of 600 MHz and at a temperature of 20 °C. The cable type recognised is intended to be used for shielded channels with a nominal length of 40 m. Possible designs are U/FTP, X/UTP and X/FTP, where X stands for F, S or SF. A blank detail specification can be found in Annex A.

These cables can comprise more than one pair in the event that several systems are operated in parallel. In this case, refer to Clause 7 of this document.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example, the electric power supplies of public utility mains, they are intended to be used to support the delivery of low-voltage remote powering applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60708:2005, *Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath*

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*
IEC 61156-1:2007/AMD1:2009²

IEC 61156-5:2009, *Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification*

IEC 62153-4-3:2013, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

¹ Under consideration.

² A consolidated version of this publication exists, comprising IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009.

IEC 62153-4-5:2006, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62153-4-9:2018, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

ISO/IEC TS 29125:2017, *Information technology – Telecommunications cabling requirements for remote powering of terminal equipment*