



IEC 61669

Edition 2.1 2025-01
CONSOLIDATED VERSION

INTERNATIONAL STANDARD



**Electroacoustics – Measurement of real-ear acoustical performance
characteristics of hearing aids**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 17.140.50

ISBN 978-2-8327-0151-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|--|----|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 8 |
| 4 Test setup diagrams | 13 |
| 5 Limitations..... | 15 |
| 6 Test equipment..... | 16 |
| 6.1 Safety requirements..... | 16 |
| 6.2 Ambient conditions..... | 16 |
| 6.3 Test signal | 16 |
| 6.4 Sound field source | 17 |
| 6.5 Coupled sound source | 17 |
| 6.6 Test signal range | 17 |
| 6.7 Test signal level indication | 17 |
| 6.8 Equalization | 17 |
| 6.9 Frequency..... | 17 |
| 6.10 Harmonic distortion..... | 17 |
| 6.11 Probe microphone measurement..... | 17 |
| 6.12 Noise floor of probe microphone measurement | 17 |
| 6.13 Attenuation of probe microphone to external signals | 18 |
| 6.14 Analysis characteristics..... | 18 |
| 6.15 Output indication..... | 18 |
| 6.16 Graphical printout | 18 |
| 7 Test conditions | 19 |
| 7.1 Ambient conditions in the test space | 19 |
| 7.2 Background noise | 19 |
| 7.3 Acoustical properties | 19 |
| 7.4 Sound field characteristics | 19 |
| 7.5 Calibration | 19 |
| 7.6 Equalization | 19 |
| 7.6.1 General | 19 |
| 7.6.2 Substitution method..... | 19 |
| 7.6.3 Modified pressure method – Stored equalization..... | 20 |
| 7.6.4 Modified pressure method – Concurrent equalization..... | 20 |
| 7.7 Test signal level..... | 20 |
| 7.8 Location of the subject..... | 20 |
| 7.9 Location of the tester | 20 |
| 7.10 Location of the field reference point | 20 |
| 7.11 Location of the measurement point | 21 |
| 7.12 Instructions to the subject | 21 |
| 7.13 Location and coupling of the hearing aid..... | 21 |
| 7.14 Operating conditions for the hearing aid..... | 21 |
| 8 Measurements..... | 21 |
| 8.1 General..... | 21 |
| 8.2 Real-ear unaided response (REUR) curve..... | 21 |

| | | |
|--|--|----|
| 8.3 | Real-ear unaided gain (REUG) curve | 22 |
| 8.4 | Real-ear occluded response (REOR) curve | 22 |
| 8.5 | Real-ear occluded gain (REOG) curve | 22 |
| 8.6 | Real-ear aided response (REAR) curve | 22 |
| 8.7 | Real-ear aided gain (REAG) curve | 23 |
| 8.8 | Real-ear insertion gain (REIG) curve | 23 |
| 8.9 | Real-ear to coupler difference (RECD) curve | 23 |
| 8.10 | Real-ear to dial difference (REDD) curve | 23 |
| 9 | Measurement uncertainty for the performance requirements of Clause 6 | 24 |
| Annex A (informative) Positioning the probe microphone sound inlet at the measurement point | | |
| | | 25 |
| A.1 | General..... | 25 |
| A.2 | Visual positioning..... | 25 |
| A.3 | Acoustically-assisted positioning..... | 25 |
| A.4 | Acoustic positioning – Method 1..... | 26 |
| A.5 | Acoustic positioning – Method 2..... | 26 |
| A.6 | Geometrical positioning | 26 |
| Annex B (informative) Issues in RECD measurement and application | | |
| | | 27 |
| B.1 | General..... | 27 |
| B.2 | Influence of the coupled sound source | 27 |
| B.3 | Estimating ear canal SPL produced by a hearing aid..... | 30 |
| B.4 | Correcting an HL audiogram obtained with an insert earphone and a standard eartip..... | 32 |
| B.5 | Correcting an HL audiogram obtained with an insert earphone and a custom earmould..... | 33 |
| Annex C (informative) Relationship between tolerance interval, corresponding acceptance interval and the maximum permitted uncertainty of measurement..... | | |
| | | 35 |
| Bibliography..... | | |
| | | 36 |
| | | |
| Figure 1 – Test set-up..... | | |
| | | 14 |
| Figure 2 – Real-ear measurement arrangement | | |
| | | 15 |
| Figure B.1 – Computer-simulated ECLD for an average adult ear | | |
| | | 29 |
| Figure B.2 – Computer-simulated ECLD for an average 3-month old child’s ear | | |
| | | 29 |
| Figure B.3 – Computer-simulated error in estimating SPL in an average adult ear | | |
| | | 31 |
| Figure B.4 – Computer-simulated error in estimating SPL in an average 3-month old child’s ear | | |
| | | 32 |
| Figure B.5 – Computer-simulated HL correction for an average 3 month old child’s ear | | |
| | | 34 |
| Figure C.1 – Relationship between tolerance interval, corresponding acceptance interval and the maximum permitted uncertainty of measurement | | |
| | | 35 |
| | | |
| Table 1 – Tolerance limits, acceptance limits and U_{\max} for basic measurements | | |
| | | 24 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTROACOUSTICS –
MEASUREMENT OF REAL-EAR ACOUSTICAL
PERFORMANCE CHARACTERISTICS OF HEARING AIDS****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61669 edition 2.1 contains the second edition (2015-11) [documents 29/886/FDIS and 29/893/RVD] and its amendment 1 (2025-01) [documents 29/1179/CDV and 29/1194/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 61669 has been prepared by IEC technical committee 29: Electroacoustics.

This second edition cancels and replaces the first edition of IEC 61669:2001 and the first edition of ISO 12124:2001. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 61669:2001 and ISO 12124:2001:

- a) the addition of the International Speech Test Signal as a preferred speech-like stimulus;
- b) definitions and test methods for the real-ear to dial difference;
- c) definitions and test methods for the real-ear to coupler difference and
- d) an annex dealing with issues in the measurement and application of the real-ear to coupler difference;

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The performance characteristics of hearing aids in actual use can differ significantly from those determined in accordance with standards such as IEC 60118-0, and IEC 60118-7, due to differing acoustic influence and coupling presented by individual ears. Measuring methods that take into account the acoustic coupling and the acoustic influence of the individual wearer on the performance of hearing aids are therefore important in the fitting of these devices. Such measuring methods have come to be known as “real-ear measurements” and are sometimes performed clinically in less than ideal acoustic environments. The accuracy and repeatability of measurements made under such conditions are complex functions of the sound field, the test environment, the nature of the test signal, the hearing aid under evaluation, the method of test signal control, the location of the sound field source, the nature of the data acquisition, analysis and presentation as well as the degree of subject movement permitted.

This standard provides definitions for terms used in the measurement of real-ear performance characteristics of hearing aids, provides procedural and reporting guidelines, and identifies essential characteristics to be reported by the manufacturer of equipment used for this purpose. Acceptable tolerances for the control and measurement of sound pressure levels are indicated. Where possible, sources of error have been identified and suggestions provided for their management.

ELECTROACOUSTICS – MEASUREMENT OF REAL-EAR ACOUSTICAL PERFORMANCE CHARACTERISTICS OF HEARING AIDS

1 Scope

This International Standard gives recommendations and requirements for the measurement and estimation of the real-ear acoustical performance characteristics of air-conduction hearing aids and for the measurement of certain acoustic properties of the ear related to the application of hearing aids.

Measurements of real-ear acoustical characteristics of hearing aids which apply non-linear or analytical processing techniques are valid only for the test signals used and conditions employed.

The purpose of this standard is to ensure that measurements of real-ear acoustical performance characteristics of a given hearing aid on a given human ear can be replicated in other locations with other test equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60601-1, *Medical electrical equipment – Part 1: General requirements for basic safety and essential performance*

IEC 60601-1-2, *Medical electrical equipment – Part 1-2: General requirements for basic safety and essential performance – Collateral Standard: Electromagnetic disturbances – Requirements and tests*

IEC 60318-5, *Electroacoustics – Simulators of human head and ear – Part 5: 2 cm³ coupler for the measurement of hearing aids and earphones coupled to the ear by means of ear inserts*

IEC 60942, *Electroacoustics – Sound calibrators*

IEC 61260-1, *Electroacoustics – Octave-band and fractional-octave-band filters – Part 1: Specifications*

ISO 266, *Acoustics – Preferred frequencies*

ISO 8253-2, *Acoustics – Audiometric test methods – Part 2: Sound field audiometry with pure-tone and narrow-band test signals*

ISO/TR 25417, *Acoustics – Definitions of basic quantities and terms*

CONTENTS

| | |
|--|----|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 8 |
| 4 Test setup diagrams | 13 |
| 5 Limitations..... | 15 |
| 6 Test equipment..... | 16 |
| 6.1 Safety requirements..... | 16 |
| 6.2 Ambient conditions..... | 16 |
| 6.3 Test signal | 16 |
| 6.4 Sound field source | 17 |
| 6.5 Coupled sound source | 17 |
| 6.6 Test signal range | 17 |
| 6.7 Test signal level indication | 17 |
| 6.8 Equalization | 17 |
| 6.9 Frequency..... | 17 |
| 6.10 Harmonic distortion..... | 17 |
| 6.11 Probe microphone measurement..... | 17 |
| 6.12 Noise floor of probe microphone measurement | 17 |
| 6.13 Attenuation of probe microphone to external signals | 18 |
| 6.14 Analysis characteristics..... | 18 |
| 6.15 Output indication..... | 18 |
| 6.16 Graphical printout | 18 |
| 7 Test conditions | 19 |
| 7.1 Ambient conditions in the test space | 19 |
| 7.2 Background noise | 19 |
| 7.3 Acoustical properties | 19 |
| 7.4 Sound field characteristics | 19 |
| 7.5 Calibration | 19 |
| 7.6 Equalization | 19 |
| 7.6.1 General | 19 |
| 7.6.2 Substitution method..... | 19 |
| 7.6.3 Modified pressure method – Stored equalization..... | 20 |
| 7.6.4 Modified pressure method – Concurrent equalization..... | 20 |
| 7.7 Test signal level..... | 20 |
| 7.8 Location of the subject..... | 20 |
| 7.9 Location of the tester | 20 |
| 7.10 Location of the field reference point | 20 |
| 7.11 Location of the measurement point | 21 |
| 7.12 Instructions to the subject | 21 |
| 7.13 Location and coupling of the hearing aid | 21 |
| 7.14 Operating conditions for the hearing aid..... | 21 |
| 8 Measurements..... | 21 |
| 8.1 General..... | 21 |
| 8.2 Real-ear unaided response (REUR) curve..... | 21 |

| | | |
|--|--|----|
| 8.3 | Real-ear unaided gain (REUG) curve | 22 |
| 8.4 | Real-ear occluded response (REOR) curve | 22 |
| 8.5 | Real-ear occluded gain (REOG) curve | 22 |
| 8.6 | Real-ear aided response (REAR) curve | 22 |
| 8.7 | Real-ear aided gain (REAG) curve | 23 |
| 8.8 | Real-ear insertion gain (REIG) curve | 23 |
| 8.9 | Real-ear to coupler difference (RECD) curve | 23 |
| 8.10 | Real-ear to dial difference (REDD) curve | 23 |
| 9 | Measurement uncertainty for the performance requirements of Clause 6 | 24 |
| Annex A (informative) Positioning the probe microphone sound inlet at the measurement point | | 25 |
| A.1 | General..... | 25 |
| A.2 | Visual positioning..... | 25 |
| A.3 | Acoustically-assisted positioning..... | 25 |
| A.4 | Acoustic positioning – Method 1..... | 26 |
| A.5 | Acoustic positioning – Method 2..... | 26 |
| A.6 | Geometrical positioning | 26 |
| Annex B (informative) Issues in RECD measurement and application | | 27 |
| B.1 | General..... | 27 |
| B.2 | Influence of the coupled sound source | 27 |
| B.3 | Estimating ear canal SPL produced by a hearing aid..... | 30 |
| B.4 | Correcting an HL audiogram obtained with an insert earphone and a standard eartip..... | 32 |
| B.5 | Correcting an HL audiogram obtained with an insert earphone and a custom earmould..... | 33 |
| Annex C (informative) Relationship between tolerance interval, corresponding acceptance interval and the maximum permitted uncertainty of measurement..... | | 35 |
| Bibliography..... | | 36 |
| Figure 1 – Test set-up..... | | 14 |
| Figure 2 – Real-ear measurement arrangement | | 15 |
| Figure B.1 – Computer-simulated ECLD for an average adult ear | | 29 |
| Figure B.2 – Computer-simulated ECLD for an average 3-month old child’s ear | | 29 |
| Figure B.3 – Computer-simulated error in estimating SPL in an average adult ear | | 31 |
| Figure B.4 – Computer-simulated error in estimating SPL in an average 3-month old child’s ear | | 32 |
| Figure B.5 – Computer-simulated HL correction for an average 3 month old child’s ear | | 34 |
| Figure C.1 – Relationship between tolerance interval, corresponding acceptance interval and the maximum permitted uncertainty of measurement | | 35 |
| Table 1 – Tolerance limits, acceptance limits and U_{\max} for basic measurements | | 24 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTROACOUSTICS –
MEASUREMENT OF REAL-EAR ACOUSTICAL
PERFORMANCE CHARACTERISTICS OF HEARING AIDS****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61669 edition 2.1 contains the second edition (2015-11) [documents 29/886/FDIS and 29/893/RVD] and its amendment 1 (2025-01) [documents 29/1179/CDV and 29/1194/RVC].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 61669 has been prepared by IEC technical committee 29: Electroacoustics.

This second edition cancels and replaces the first edition of IEC 61669:2001 and the first edition of ISO 12124:2001. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 61669:2001 and ISO 12124:2001:

- a) the addition of the International Speech Test Signal as a preferred speech-like stimulus;
- b) definitions and test methods for the real-ear to dial difference;
- c) definitions and test methods for the real-ear to coupler difference and
- d) an annex dealing with issues in the measurement and application of the real-ear to coupler difference;

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

The performance characteristics of hearing aids in actual use can differ significantly from those determined in accordance with standards such as IEC 60118-0, and IEC 60118-7, due to differing acoustic influence and coupling presented by individual ears. Measuring methods that take into account the acoustic coupling and the acoustic influence of the individual wearer on the performance of hearing aids are therefore important in the fitting of these devices. Such measuring methods have come to be known as “real-ear measurements” and are sometimes performed clinically in less than ideal acoustic environments. The accuracy and repeatability of measurements made under such conditions are complex functions of the sound field, the test environment, the nature of the test signal, the hearing aid under evaluation, the method of test signal control, the location of the sound field source, the nature of the data acquisition, analysis and presentation as well as the degree of subject movement permitted.

This standard provides definitions for terms used in the measurement of real-ear performance characteristics of hearing aids, provides procedural and reporting guidelines, and identifies essential characteristics to be reported by the manufacturer of equipment used for this purpose. Acceptable tolerances for the control and measurement of sound pressure levels are indicated. Where possible, sources of error have been identified and suggestions provided for their management.

ELECTROACOUSTICS – MEASUREMENT OF REAL-EAR ACOUSTICAL PERFORMANCE CHARACTERISTICS OF HEARING AIDS

1 Scope

This International Standard gives recommendations and requirements for the measurement and estimation of the real-ear acoustical performance characteristics of air-conduction hearing aids and for the measurement of certain acoustic properties of the ear related to the application of hearing aids.

Measurements of real-ear acoustical characteristics of hearing aids which apply non-linear or analytical processing techniques are valid only for the test signals used and conditions employed.

The purpose of this standard is to ensure that measurements of real-ear acoustical performance characteristics of a given hearing aid on a given human ear can be replicated in other locations with other test equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60601-1, *Medical electrical equipment – Part 1: General requirements for basic safety and essential performance*

IEC 60601-1-2, *Medical electrical equipment – Part 1-2: General requirements for basic safety and essential performance – Collateral Standard: Electromagnetic disturbances – Requirements and tests*

IEC 60318-5, *Electroacoustics – Simulators of human head and ear – Part 5: 2 cm³ coupler for the measurement of hearing aids and earphones coupled to the ear by means of ear inserts*

IEC 60942, *Electroacoustics – Sound calibrators*

IEC 61260-1, *Electroacoustics – Octave-band and fractional-octave-band filters – Part 1: Specifications*

ISO 266, *Acoustics – Preferred frequencies*

ISO 8253-2, *Acoustics – Audiometric test methods – Part 2: Sound field audiometry with pure-tone and narrow-band test signals*

ISO/TR 25417, *Acoustics – Definitions of basic quantities and terms*