



IEC/TR 62000

Edition 2.0 2010-11

TECHNICAL REPORT



Guideline for combining different single-mode fibres types

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 33.180.10

ISBN 978-2-88912-268-4

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Abbreviations.....	6
3 System issues.....	6
4 Fibre issues.....	6
4.1 General.....	6
4.2 Cut-off wavelength.....	7
4.3 Splicing issues.....	7
4.4 Combination of fibre parameters: chromatic dispersion coefficient and slope, polarization mode dispersion (PMD).....	8
4.5 Non-linear effects.....	8
5 Launch fibres, pigtails, patch-cords and jumper cables.....	9
6 Attenuation.....	9
7 Summary.....	9
Bibliography.....	11

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GUIDELINE FOR COMBINING DIFFERENT SINGLE-MODE FIBRES TYPES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62000, which is a technical report, has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This second edition cancels and replaces the first edition (2005) and constitutes a technical revision.

The major technical changes with respect to the previous edition are considerations concerning B6 fibres.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86A/1276/DTR	86A/1283/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

GUIDELINE FOR COMBINING DIFFERENT SINGLE-MODE FIBRES TYPES

1 Scope

This technical report provides guidelines concerning single-mode fibre compatibility.

A given type of single-mode fibre, for example B4, may have different implementations by suitably optimising several of the following parameters: mode field diameter (hence effective area), chromatic dispersion coefficient, slope of the chromatic dispersion curve, cable cut-off wavelength.

This guideline indicates the items that should be taken into account when planning to connect: (1) different implementations of single-mode fibres of the same type, e.g. different implementations of type B single-mode fibres, and (2) single-mode fibres of different types, e.g. B1.1 with B4. See IEC 60793-2-50 for the attributes and definitions of single-mode fibre. The attributes and definitions of fibres covered in this technical report are given in Table 1.

Table 1 – Correspondence table of various single-mode fibres

Common name	Use (IEC 6079-2-50)	IEC Class	ITU-T Recommendation
Dispersion unshifted single-mode fibre	Optimised for use in the 1 310 nm region but can be used in the 1 550 nm region	B1.1	G.652 A, B
Cut-off shifted single-mode fibre	Optimised for low loss in the 1 550 nm region, with cut off wavelength shifted above the 1 310 nm region	B1.2	G.654
Extended band dispersion unshifted single-mode fibre	Optimised for use in the 1 310 nm region but can be used in the O, E, S, C and L-band (i.e. throughout the 1 260 nm to 1 625 nm range).	B1.3	G.652 C, D
Dispersion shifted single-mode fibre	Optimised for single channel transmission in the 1 550 nm region. Multiple channels can only be transmitted if care is taken to avoid the effects of four wave mixing by, for example, moderating the power levels or appropriate spacing or placement of the channels	B.2	G.653
Non-zero dispersion-shifted single-mode fibre	Optimised for multiple channel transmission in the 1 550 nm region with a cut off wavelength that may be shifted above the 1 310 nm region	B4	G.655
Wideband non-zero dispersion-shifted single-mode fibre	Optimised for multiple channel transmission in the wavelength range of 1 460 to 1 625 nm with the positive value of the chromatic dispersion coefficient that is greater than some non-zero value over the same wavelength range.	B5	G.656
Bend loss optimised	Bending loss insensitive single-mode fibre suitable for use in the access networks, including inside buildings at the end of these networks. B6_a fibres are suitable to be used in the O, E, S, C and L-band (i.e. throughout the 1 260 nm to 1 625 nm range) and meet the requirements of B1.3 fibres.	B6_a	G.657.A
	Bending loss insensitive single-mode fibre suitable for use in the access networks, including inside buildings at the end of these networks.	B6_b	G.657.B

Common name	Use (IEC 6079-2-50)	IEC Class	ITU-T Recommendation
	B6_b fibres are suitable for transmission at 1 310 nm, 1 550 nm, and 1 625 nm for restricted distances that are associated with in-building transport of signals.		

This guide does not consider the connection of fibres with the same implementation from different manufacturers, which is already considered by the standardisation procedure.