

Edition 1.0 2025-01

INTERNATIONAL STANDARD



Railway applications – Current collection systems – Validation of simulation of the dynamic interaction between pantograph and overhead contact line

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 45.060.01 ISBN 978-2-8327-0095-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Ε(JREWO	RD	6
1	Scop	e	8
2	Norm	native references	8
3	Term	s and definitions	9
4		pols and abbreviated terms	
5	•	eral	
J	5.1	Overview of the validation process	
	5.2	Typical application	
6		elling of the pantograph	
Ü	6.1	General requirements	
	6.2	Input data requirements	
	6.2.1	·	
	6.2.2		
	6.2.3	, , , , , , , , , , , , , , , , , , , ,	
	6.2.4	•	
	6.2.5		
	6.3	Validation of pantograph models	
7		elling of the overhead contact line	
	7.1	General requirements	
	7.2	Data requirements	
	7.3	Static check of overhead contact line model	
8		meters of simulation	
9		ut	
J	9.1	General	
	9.2	Contact force	
	9.3	Contact wire displacement	
	9.4	Pantograph displacement	
10		ation with measured values	
. `	10.1	General	
	10.1	Comparison values	
	10.2	Limits of validation	
	10.3.		
	10.3.		
	10.3.		
	10.3.	·	
11	l Refe	rence model	
	11.1	Purpose of reference model	26
	11.2	Reference model data	
	11.3	Parameters of simulation	
	11.4	Reference model results	27
Αı	nnex A (normative) Reference model specification	
	A.1	General	
	A.2	Overhead contact line data	
	A.2.1		
	A.2.2	Special data for the overhead contact line reference model – AC –	
		Simple	30

A.2.3	Special data for the reference model of overhead contact line AC – Stitched	31
A.2.4	Special data for the reference model of overhead contact line DC – Simple	
A.3 Pa	antograph data	
	esults of simulations for reference models	
	rmative) Model specifications and measurement results for validation	
,	easurement results of simple AC high speed overhead contact line	
B.1.1	Simulation data for overhead contact line model	
B.1.2	Pantograph model	
B.1.3	Measured data of dynamic interaction for validation	47
B.2 M	easurement results of a stitched AC high speed overhead contact line	48
B.2.1	General	48
B.2.2	Simulation data for overhead contact line model	48
B.2.3	Pantograph data	
B.2.4	Calculated and measured data of OCL-rest position for validation	
B.2.5	Measuring data of dynamic interaction for validation	
	easurement results of simple DC high speed overhead contact line	
B.3.1	General	_
B.3.2	Simulation data for overhead contact line model	
B.3.3	Pantograph data	
B.3.4	Measured data of dynamic interaction for validation	/ 5
	formative) Assessment process example for dynamic interaction between design or "new" pantograph design for interoperability purpose	77
	formative) National annex for Japan – Permissible changes of the	
	arameters	81
Bibliography	· · · · · · · · · · · · · · · · · · ·	82
Figure 1 – E	valuation process	16
Figure A.1 –	AC - Simple - Overhead contact line model	30
Figure A.2 –	AC – Stitched catenary overhead contact line model	31
Figure A.3 –	DC – Simple catenary overhead contact line model	32
-	Pantograph model	
_	Cantilever model elements in Table B.2, Table B.42 and Table B.49	
•	Basic dropper arrangement span type ST1	
•		
· ·	Basic dropper arrangement span type ST2	
_	Basic dropper arrangement span type ST3	
•	Basic dropper arrangement span type ST4	
•	Basic dropper arrangement span type ST5	
Figure B.7 –	Basic dropper arrangement span type ST6	55
Figure B.8 –	Basic dropper arrangement span type ST7	56
Figure B.9 –	Basic support arrangement Mast Type MT1 (pull-off)	58
	– Basic support arrangement Mast Type MT2 (push-off)	
	Basic support arrangement mast type MT3 (tube steady arm)	
=	Method of OCL assessment	
_	Method of pantograph assessment	
FIGURE 6.7 -	· IVIETHOU OF DAIHOUFADIT ASSESSITIENT	ര

Table 1 – Required accuracy of simulated static values	21
Table 2 – Required accuracy of simulated dynamic values	24
Table 3 – Combinations of OCL and pantograph reference models	26
Table A.1 – Data for reference overhead contact lines	29
Table A.2 – AC – Simple – Overhead contact line model – Geometry and elasticity of droppers	31
Table A.3 – AC – Stitched catenary overhead contact line model – Geometry and elasticity of droppers	32
Table A.4 – DC – Simple catenary overhead contact line model – Geometry and elasticity of overhead contact line	33
Table A.5 – Pantograph model parameters	34
Table A.6 – Ranges of results from reference model AC simple	35
Table A.7 – Ranges of results from reference model AC stitched	35
Table A.8 – Ranges of results from reference model DC simple	36
Table B.1 – Mechanical values of wires	37
Table B.2 – Mechanical values of clamps and other OCL-components	37
Table B.3 – Pre-sag information in open route and overlap	38
Table B.4 – Cantilever information in open route and overlap: steady arm geometry	38
Table B.5 – Span definition of tension length 1	39
Table B.6 – Span definition of tension length 2	39
Table B.7 – Span definition of tension length 3	39
Table B.8 – Support definition of tension length 1	40
Table B.9 – Support definition of tension length 2	41
Table B.10 – Support definition of tension length 3	42
Table B.11 – Span length = 44,7 m	42
Table B.12 – Span length = 45,3 m	43
Table B.13 – Span length = 45,5 m	43
Table B.14 – Span length = 45 m	43
Table B.15 – Span length = 49,5 m	43
Table B.16 – Span length = 50 m	43
Table B.17 – Span length = 49,8 m	43
Table B.18 – Span length = 49,2 m	43
Table B.19 – Span length = 49,2 m	44
Table B.20 – Span length = 49,8 m	44
Table B.21 – Span length = 50 m	44
Table B.22 – Span length = 48,5 m	44
Table B.23 – Span length = 49,5 m	44
Table B.24 – Span length = 54 m	44
Table B.25 – Span length = 50 m	45
Table B.26 – Span length = 49,8 m	45
Table B.27 – Span length = 49,2 m	45
Table B.28 – Span length = 49,2 m	45
Table B.29 – Span length = 49,8 m	45
Table B.30 – Span length = 41 m	45

Table B.31 – Span length = 38 m	46
Table B.32 – Span length = 45 m	46
Table B.33 – Span length = 40 m	46
Table B.34 – Span length = 47,5 m	46
Table B.35 – Span length = 49,5 m	46
Table B.36 – Span length = 54 m	46
Table B.37 – Span length = 49,8 m	46
Table B.38 – Span length = 49,2 m	47
Table B.39 – Pantograph model parameters	47
Table B.40 – Measurement result from line test	47
Table B.41 – Mechanical values of wires and tubes	48
Table B.42 – Mechanical values of clamps and other OCL-components	49
Table B.43 – Position of droppers and CW-height at dropper	50
Table B.44 – Data of supports	56
Table B.45 – Pantograph model parameters	60
Table B.46 – Dropper length and system elasticity	60
Table B.47 – Measurement result from line test	61
Table B.48 – Mechanical values of wires	62
Table B.49 – Mechanical values of clamps and other OCL-components	62
Table B.50 – Position of droppers and CW-height at dropper	63
Table B.51 – Data of supports	73
Table B.52 – Pantograph model parameters	75
Table B.53 – Measurement result from line test	76

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RAILWAY APPLICATIONS – CURRENT COLLECTION SYSTEMS – VALIDATION OF SIMULATION OF THE DYNAMIC INTERACTION BETWEEN PANTOGRAPH AND OVERHEAD CONTACT LINE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 63453 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
9/3145/FDIS	9/3163/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

RAILWAY APPLICATIONS – CURRENT COLLECTION SYSTEMS – VALIDATION OF SIMULATION OF THE DYNAMIC INTERACTION BETWEEN PANTOGRAPH AND OVERHEAD CONTACT LINE

1 Scope

Simulation techniques are used to assess the dynamic interaction between overhead contact lines and pantographs, as part of the prediction of current collection quality. This document specifies functional requirements for the validation of such simulation tools to ensure confidence in, and mutual acceptance of the results of the simulations.

This document deals with:

- input and output parameters of the simulation;
- comparison with line test measurements, and the characteristics of those line tests;
- validation of pantograph models;
- comparison between different simulation tools;
- limits of application of validated methods to assessments of pantographs and overhead contact lines.

This document applies to the current collection from an overhead contact line by pantographs mounted on railway vehicles. It does not apply to trolley bus systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60494-1:2013, Railway applications – Rolling stock – Pantographs – Characteristics and tests – Part 1: Pantographs for main line vehicles

IEC 60913:2024, Railway applications – Fixed installations – Electric traction overhead contact line systems

IEC 62846:2016, Railway applications – Current collection systems – Requirements for and validation of measurements of the dynamic interaction between pantograph and overhead contact line

IEC 62486:2017, Railway applications – Current collection systems – Technical criteria for the interaction between pantograph and overhead contactline (to achieve free access)