

IEC/ASTM 62885-7

Edition 1.0 2020-10

INTERNATIONAL STANDARD



Surface cleaning appliances – Part 7: Dry-cleaning robots for household or similar use – Methods for measuring the performance

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ISBN 978-2-8322-8540-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

INTRODUCTION	99 99 99 99 99 99 99 99 99 99 99 99 99
Normative references Terms and definitions General conditions for testing 4.1 General 4.2 Atmospheric conditions 4.3 Lighting conditions 4.4 Test equipment and materials 4.5 Number of samples 4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions Cleaning performance – Straight line	
Terms and definitions General conditions for testing 4.1 General	
4 General conditions for testing. 4.1 General	
4 General conditions for testing. 4.1 General	
4.1 General	11 12 12
4.2 Atmospheric conditions 4.3 Lighting conditions 4.4 Test equipment and materials 4.5 Number of samples 4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	11 12 12
4.3 Lighting conditions 4.4 Test equipment and materials 4.5 Number of samples 4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	12 12 12
4.4 Test equipment and materials 4.5 Number of samples 4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	12 12
4.5 Number of samples 4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	12
4.6 Preparation of the battery 4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	
4.7 Running-in of a new cleaning robot 4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	12
4.8 Operation of the cleaning robot 4.9 Measurement of collected dust weight 4.10 Measurement resolution and accuracy 4.11 Tolerance of dimensions 5 Cleaning performance – Straight line	
4.9 Measurement of collected dust weight	
4.10 Measurement resolution and accuracy	
4.11 Tolerance of dimensions	
5 Cleaning performance – Straight line	
0.1 00110141	
5.2 Preparation of test	
5.2.1 Pre-treatment of cleaning robot	
5.2.2 Preconditioning of test floor	
5.2.3 Pre-treatment of test carpet	
5.3 Test mode	
5.3.1 General	
5.3.2 Access to test mode	
5.3.3 Test mode action	
5.3.4 Speed verification	
5.4 Dust removal from hard floor	
5.4.1 Test bed	
5.4.2 Preparation of test	
5.4.3 Test method	
5.4.4 Determination of dust removal ability	
5.5 Dust removal from carpet	
5.5.1 Test bed	
5.5.2 Preparation of test	20
5.5.3 Test method	20
5.5.4 Determination of dust removal ability	21
5.6 Medium size debris removal from hard floor	21
5.6.1 Test bed	21
5.6.2 Preparation of test	21
5.6.3 Test method	
5.6.4 Determination of medium size debris removal abi	ility 24
5.7 Medium size debris removal from carpet	ιιι ι y ∠ Ι
5.7.1 Test bed	•
5.7.2 Preparation of test	22

	5.7.3	Test method	22
	5.7.4	Determination of medium size debris removal ability	22
	5.8 l	arge debris removal from hard floor	22
	5.8.1	Test bed	22
	5.8.2	Preparation of test	22
	5.8.3	Test method	24
	5.8.4	Determination of large debris removal ability	24
	5.9 I	arge debris removal from carpet	24
	5.9.1	Test bed	24
	5.9.2	Preparation of test	24
	5.9.3	Test method	25
	5.9.4	Determination of large debris removal ability	25
	5.10 F	Fibre removal from carpet	25
	5.10.1	Test bed	25
	5.10.2	Preparation of test	25
	5.10.3	Test method	27
	5.10.4	Determination of fibre removal ability	27
6	Mobili	y	28
	6.1	General	28
	6.2	est bed	29
	6.3 F	Preparation of test	29
	6.3.1	Test conditions	29
	6.3.2	Preconditioning of test floor	29
	6.3.3	Pre-treatment of cleaning robot	29
	6.4	est method	29
	6.4.1	General	29
	6.4.2	Minimum passable gap width	30
	6.4.3	Minimum passable height	31
	6.4.4	Maximum passable transition height	31
	6.4.5	Maximum passable threshold height	32
	6.5 I	Determination of mobility results	33
7	Auton	omous navigation/coverage test	34
	7.1	General	34
	7.2 F	Preparation of test	34
	7.2.1	Test bed	34
	7.2.2	Test conditions	34
	7.3	est method	34
	7.4 F	Performance measurement	36
8	Miscel	laneous	38
	8.1 E	Energy consumption of a cleaning robot	38
	8.1.1	General	38
	8.1.2	Test conditions	38
	8.1.3	Test method	39
	8.2	Airborne acoustical noise	41
	8.3	Straight-line cleaning speed	41
	8.3.1	General	41
	8.3.2	Preparation	41
	8.3.3	Test method	41
	8.3.4	Determination of straight-line cleaning speed	42

9 Test mat	erial and equipment	44
9.1 Str	aight-line test bed	44
9.1.1	Hard floor	44
9.1.2	Carpet	44
9.2 Mo	bility test bed	45
9.2.1	Basic test bed configuration	
9.2.2	Minimum passable gap width – additional equipment	
9.2.3	Minimum passable height – additional equipment	
9.2.4	Maximum passable transition height – additional equipment	
9.2.5	Maximum passable threshold height – additional equipment	
	verage test bed	
9.3.1	Floor configuration	
9.3.2 9.3.3	Wall and ceiling configuration	
	ons for use	
•	rmative) Calculation of coverage	
	finitions	
	culating orifice pass coverage	
	rmative) Comprehensive cleaning performance metric	
•	rmative/normative) Detailed images of fibre removal ability	
Bibliography		72
· ·	st mode action	
•	st distribution devices	
•	rge debris template	
Figure 4 – La	rge debris template hole alignment	24
Figure 5 – Str	aight-line fibre removal from carpet test bed configuration	25
Figure 6 – Ex	emplary picture of fibre distribution	26
Figure 7 – Ex	emplary picture of judgement area	27
Figure 8 – Sta	arting positions and orientations	30
Figure 9 – Mi	nimum passable gap width test	30
	uggested process to determine the minimum passable gap width	
	linimum passable height test	
	laximum passable transition height test	
_	rocess to determine the maximum passable transition height	
· ·	laximum passable threshold height test	
•		
_	tarting positions for navigation test	
•	xemplary graph of coverage test result	
_	traight-line speed measurement areas	
•	traight-line hard floor test bed configuration	
	traight-line carpet test bed configuration	
•	asic test bed configuration for mobility testing	
Figure 21 – T	est bed with an additional adjustable wall	46
Figure 22 – P	art 1 and part 2 of the wall	46
Figure 23 – T	est bed with an additional tunnel	47

Figure 25 – Test bed with additional threshold	9
Figure 26 – Drawings of cylindrical and rectangular thresholds	
0 0)
Figure 27 – Navigation/coverage test bed configuration	,
Figure 28 – Details of obstacles around table51	1
Figure 29 – Illustration of metal transition installation	3
Figure 30 – Illustration of wood transition installation	3
Figure 31 – Detail view of checkerboard and transitions	1
Figure 32 – Configuration of four walls and ceiling55	5
Figure 33 – Illustration of four-panel door59	9
Figure 34 – Illustration of window59	9
Figure 35 – Illustration of skirting board60)
Figure 36 – Illustration of pendant light60)
Figure 37 – Illustration of clock61	1
Figure 38 – Illustration of mirror61	1
Figure 39 – Illustration of picture62	2
Figure 40 – Illustration of curtains62	2
Figure A.1 – Robot coordinate frame64	1
Figure A.2 – Coverage step65	5
Figure C.1 – Detailed images for rating 167	7
Figure C.2 – Detailed images for rating 268	3
Figure C.3 – Detailed images for rating 369	9
Figure C.4 – Detailed images for rating 470)
Figure C.5 – Detailed images for rating 571	1
Table 1 – Tolerance of dimensions14	4
Table 2 – Medium size debris21	1
Table 3 – Large Debris23	3
Table 4 – Rating system with exemplary pictures28	3
Table 5 – List of described mobility tests29	9
Table 6 – Reported results for each mobility test	3
Table 7 – Overview of duration and the values that should be reported40)
Table 8 – Dimensions of furniture and obstacles51	1
Table 9 – Wall and ceiling furniture56	3

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SURFACE CLEANING APPLIANCES -

Part 7: Dry-cleaning robots for household or similar use – Methods for measuring the performance

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC/ASTM 62285-7 has been prepared by subcommittee 59F: Surface cleaning appliances, of IEC technical committee 59: Performance of household and similar electrical appliances, in co-operation with ASTM Committee F11: Vacuum cleaners, under the IEC/ASTM Dual Logo Agreement.

It is published as a dual logo standard.

This first edition of IEC/ASTM 62885-7 cancels and replaces IEC 62929:2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62929:2014:

- a) the box test has been cancelled;
- b) the set of straight-line tests have been extended to contain also tests on removal of different kinds of debris both from hard floors and carpets;
- c) the set of straight-line tests also contains a test on the removal of fibres from carpets;

- d) as a miscellaneous test, a method for the determination of energy consumption has been added:
- e) a separate clause on test material and equipment has been added.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
59F/393/FDIS	59F/401/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

- terms defined in Clause 3: bold type.

A list of all parts in the IEC 62885 series, published under the general title *Surface cleaning appliances*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

In addition to the performance measurement methods that are included in this International Standard, a few more performance items have been reviewed and considered. The list of the performance items that have been discussed over time but have not yet been included comprises corner/edge dust pick-up, docking, fall-off prevention, and dust re-emissions.

The performance items that have been left out in this edition will be continuously reviewed and will soon be included in future editions of this document.

SURFACE CLEANING APPLIANCES -

Part 7: Dry-cleaning robots for household or similar use – Methods for measuring the performance

1 Scope

This part of IEC 62885 is applicable to **dry-cleaning robots** for household use or under conditions similar to those in households.

The purpose of this document is to specify the essential performance characteristics of **dry-cleaning robots** that are of interest to users and to describe methods for measuring these characteristics.

This document is neither concerned with safety requirements nor with performance requirements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62301, Household electrical appliances – Measurement of standby power

IEC TS 62885-1, Surface cleaning appliances – Part 1: General requirements on test material and test equipment

IEC 62885-2:2016, Surface cleaning appliances – Part 2: Dry vacuum cleaners for household or similar use – Methods for measuring the performance

IEC 60704-1, Household and similar electrical appliances –Test code for the determination of airborne acoustical noise – Part 1: General requirements

IEC 60704-2-17, Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-17: Particular requirements for dry cleaning robots

ISO 554, Standard atmospheres for conditioning and/or testing – Specifications

ISO 2813, Paints and varnishes – Determination of gloss value at 20 degrees, 60 degrees and 85 degrees