



PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Industrial communication networks – Broadband fieldbus specification – Autbus

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 00.000

ISBN 978-2-8322-7749-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	11
1 Scope.....	12
2 Normative references	12
3 Terms and definitions, abbreviated terms and symbols	12
3.1 Terms and definitions.....	12
3.2 Abbreviated terms.....	14
3.3 Symbols.....	16
4 Data type.....	16
4.1 Overview.....	16
4.2 Basic data type	16
4.2.1 Unsigned type coding (UINT).....	16
4.2.2 Time type coding (TIMEV)	17
4.2.3 Date type coding (DATE2000)	17
4.2.4 Time of day type coding (TIMEOFDAY)	18
4.2.5 Time difference type coding (TIMEDIFFER).....	18
4.2.6 String type coding (STRING)	18
4.2.7 Bitmap tpye coding (BITMAP).....	19
4.3 Complex type.....	19
4.3.1 Struct type coding (STRUCT).....	19
4.3.2 Array type coding (ARRAY)	19
5 AUTOBUS overview	19
5.1 Overview.....	19
5.2 AUTOBUS protocol stack architecture	20
5.3 Device type	22
5.3.1 Overview	22
5.3.2 Control Device.....	22
5.3.3 Field Device	22
5.3.4 Management Node	22
5.3.5 Terminal Node.....	22
5.4 Network topology	22
6 System management.....	23
6.1 Overview.....	23
6.2 System management process	23
6.3 System management information table.....	24
6.3.1 PhL related management information table.....	24
6.3.2 DLL related management information table.....	31
6.3.3 AL related management information table.....	34
7 Physical layer	36
7.1 Physical Layer overview.....	36
7.2 PhL resource	37
7.2.1 Signal frame	37
7.2.2 Data subframe	39
7.2.3 OFDM symbol.....	40
7.2.4 Code Block.....	41
7.2.5 Resource element.....	41
7.2.6 Working mode	42

7.3	DLL–PhL interface	44
7.3.1	General	44
7.3.2	Service primitive	45
7.3.3	Primitive process	47
7.4	System management-PhL interface.....	47
7.4.1	General	47
7.4.2	Service primitive	47
7.4.3	Primitive process	49
7.5	DCE Independent Sublayer (DIS).....	50
7.5.1	General	50
7.5.2	Data sequence	50
7.6	DTE-DCE interface	51
7.6.1	General	51
7.6.2	Interface signal.....	51
7.6.3	Signal process.....	52
7.7	Medium Dependent Sublayer (MDS)	52
7.7.1	General	52
7.7.2	MDS specification.....	52
7.8	MDS-MAU interface	59
7.8.1	General	59
7.8.2	MDS-MAU interface	59
7.9	Medium Attachment Unit (MAU).....	62
7.9.1	Overview	62
7.9.2	Electrical specifications	62
7.9.3	Transmission Medium Interface	62
7.9.4	Medium	63
8	Data-link layer	65
8.1	General.....	65
8.1.1	DLL protocol architecture.....	65
8.1.2	DLL working mechanism.....	67
8.2	DLL services	70
8.2.1	General	70
8.2.2	Data-link service model	71
8.2.3	Data-link service description.....	72
8.2.4	Data-link management service description.....	85
8.2.5	Clock synchronization service description.....	101
8.3	DLL protocol	107
8.3.1	Working procedure	107
8.3.2	DLPDU structure	116
8.3.3	State machine	129
8.3.4	Error handling.....	134
9	Application Layer.....	136
9.1	Overview.....	136
9.1.1	Protocol architecture.....	136
9.1.2	Data type of AL.....	137
9.1.3	Data mapping modeling	140
9.1.4	Communication model	143
9.2	AL Service	144
9.2.1	Overview	144

9.2.2	Application Service Elements.....	145
9.2.3	Application service	169
9.3	Specification for AL protocol	171
9.3.1	Overview	171
9.3.2	Message format.....	171
9.3.3	State machine	176
Annex A (informative)	Example of data subframe allocation	184
A.1	Example A	184
A.2	Example B	185
A.3	Example C	186
Annex B (normative)	RS code generating polynomial	187
Annex C (informative)	Example for NodeID and MAC address mapping	188
Annex D (informative)	Example for multicast group working mechanism	189
Annex E (informative)	Example of service data mapping DTU message	190
Annex F (informative)	Example of OPC UA data model and AUTBUS data model mapping.....	191
Annex G (informative)	Example of RTA service processing	192
Annex H (informative)	AUTBUS virtualization solution example.....	193
Bibliography	196
Figure 1	– BITMAP data type	19
Figure 2	– Corresponding relationship between AUTBUS protocol stack and OSI reference model.....	20
Figure 3	– AUTBUS protocol stack architecture	21
Figure 4	– AUTBUS network topology	23
Figure 5	– AUTBUS system management process	24
Figure 6	– Resource block information structure	31
Figure 7	– AUTBUS Physical Layer model	37
Figure 8	– AUTBUS SF and OFDM symbol	38
Figure 9	– SF structure	39
Figure 10	– Carrier mode A and carrier mode B of data subframe	40
Figure 11	– OFDM symbol structure of PhL.....	40
Figure 12	– OFDM timing structure	41
Figure 13	– DLPDU and CB	41
Figure 14	– Resource element schematic diagram	42
Figure 15	– Mapping between data units across the DLL-PhL interface.....	44
Figure 16	– DLL-PhL interface service primitive process.....	47
Figure 17	– System management-PhL interface primitive process.....	50
Figure 18	– DTE-DCE interface signal process	52
Figure 19	– PhL channel process	53
Figure 20	– Scrambling sequence generation	53
Figure 21	– Convolutional encoder with a code rate of 1/2	55
Figure 22	– Bit deletion process with code rates 2/3 and 3/4.....	55
Figure 23	– Generation of m sequence	57
Figure 24	– OFDM symbol structure diagram	58

Figure 25 – MDS-MAU interface service process diagram.....	60
Figure 26 – Signal spectrum template	61
Figure 27 – Connector of the shielded twisted pair.....	64
Figure 28 – Terminal resistor	64
Figure 29 – DLL in AUTBUS protocol stack architecture	65
Figure 30 – Relationship of AUTBUS DLL to other filedbus layers and to users of AUTBUS DLS	66
Figure 31 – AUTBUS DLL protocol architecture diagram.....	66
Figure 32 – Resource mapping between DLL and PhL	69
Figure 33 – DLL resource mapping message queue scheduling diagram.....	70
Figure 34 – Primitive process of CLMDTA.....	73
Figure 35 – Primitive process of CLMDTNA	75
Figure 36 – Primitive process of CLMDTRA	77
Figure 37 – Primitive process of CLMDTRRNA	79
Figure 38 – Primitive process of CMDTA.....	81
Figure 39 – Primitive process of CMDTNA	83
Figure 40 – Data-link config management service primitive process.....	86
Figure 41 – TN active logout discovery service primitive process	90
Figure 42 – Data-link discovery management service primitive sequence diagram	90
Figure 43 – Local data-link maintenance service primitive process diagram	93
Figure 44 – Remote data-link maintenance service primitive process diagram	93
Figure 45 – Data-link establish management service primitive process	96
Figure 46 – Data-link release management service primitive sequence diagrame	98
Figure 47 – Data-link update management service primitive sequence diagram	100
Figure 48 – Delay measurement service primitive process	102
Figure 49 – Clock synchronization service primitive process	104
Figure 50 – Clock interrupt service primitive process	106
Figure 51 – Resource mapping configuration diagram.....	108
Figure 52 – Initial access configuration procedure diagram.....	109
Figure 53 – The random access configuration procedure diagram.....	110
Figure 54 – Node leave procedure diagram.....	112
Figure 55 – DLS data sending procedure diagram.....	113
Figure 56 – DLS data receiving procedure diagram.....	114
Figure 57 – Clock synchronization delay measurement procedure diagram.....	115
Figure 58 – Clock register structure diagram.....	115
Figure 59 – Clock synchronization procedure.....	116
Figure 60 – Universal DLPDU structure	116
Figure 61 – Basic configuration DLPDU structure.....	117
Figure 62 – General configuration block structure	118
Figure 63 – Address assignment DLPDU structure.....	119
Figure 64 – Multicast assignment DLPDU structure.....	120
Figure 65 – Resource allocation DLPDU structure	121
Figure 66 – Access notification DLPDU structure	122

Figure 67 – Resource application DLPDU structure.....	123
Figure 68 – Resource release DLPDU structure	124
Figure 69 – Status query DLPDU structure	125
Figure 70 – Status response DLPDU.....	125
Figure 71 – Announcement DLPDU structure.....	126
Figure 72 – Clock synchronization DLPDU structure	128
Figure 73 – Common DLPDU structure	129
Figure 74 – DLDE state machine	130
Figure 75 – DLME state machine	132
Figure 76 – DLCE state machine	133
Figure 77 – AL in AUTBUS protocol stack architecture.....	136
Figure 78 – Relationship of AUTBUS AL to other fieldbus layers and to users of AUTBUS application service	136
Figure 79 – Diagram of AUTBUS AL protocol architecture	137
Figure 80 – Data mapping modeling object structure.....	141
Figure 81 – Diagram of mapping data buffers and service data variables	142
Figure 82 – Diagram of P/S model	143
Figure 83 – P/S model of PUSH mode	143
Figure 84 – P/S model of PULL mode	144
Figure 85 – Diagram of C/S communication model.....	144
Figure 86 – RT data transmission model.....	147
Figure 87 – Diagram of nRT data request response model.....	149
Figure 88 – Diagram of nRT data AP interaction based on C/S communication model.....	149
Figure 89 – Diagram of nRT data AP interaction based on P/S communication model.....	150
Figure 90 – Time synchronization application interaction process	152
Figure 91 – Time query flow	153
Figure 92 – Resource AP interaction based on C/S communication model	155
Figure 93 – Resource ASE local service function Diagram	155
Figure 94 – NETWORKID identification field structure.....	156
Figure 95 – NETWORKID interaction process diagram.....	158
Figure 96 – Diagram of MAC mapping table service function.....	158
Figure 97 – IP mapping table service function diagram	159
Figure 98 – AUTBUS AL data message is mapped to IP payload data payload	159
Figure 99 – AUTBUS AL protocol header and IP protocol header mapping.....	160
Figure 100 – IP data message is mapped to valid data of AUTBUS AL data message.....	160
Figure 101 – Static configuration initialization process	163
Figure 102 – Join the network interaction process.....	163
Figure 103 – Passively exit the network interaction process.....	165
Figure 104 – Actively exit network interaction process	165
Figure 105 – Diagram of diagnostic object mapping	166
Figure 106 – Diagram of the logging process	167
Figure 107 – A physical bus divided into two virtual bus domain diagrams	167
Figure 108 – Diagram of virtualized AP interaction based on C/S communication model	169

Figure 109 – Virtualization ASE local implementation diagram	169
Figure 110 – AL protocol message header structure	171
Figure 111 – Message structure of multiple DTUs	173
Figure 112 – Transmission unit message format	174
Figure 113 – Time service notification message structure	174
Figure 114 – System management data message format	176
Figure 115 – Diagram of state transition of publisher state machine.....	177
Figure 116 – Diagram of state transition of subscriber state machine.....	179
Figure 117 – Diagram of state transition of client state machine.....	180
Figure 118 – Diagram of transition state of server state machine	180
Figure 119 – Diagram of transition state of ALCE state machine	181
Figure 120 – Diagram of transition state of ALDE state machine	182
Figure 121 – Diagram of state transition for ALME state machine	183
Figure A.1 – Resource allocation example A	184
Figure A.2 – Resource allocation example B	185
Figure A.3 – Resource allocation example C.....	186
Figure D.1 – Multicast working mechanism diagram.....	189
Figure E.1 – Data transmission unit message content example	190
Figure F.1 – OPC UA data model and mapping of AUTBUS data model.....	191
Figure G.1 – Example of RTA service processing	192
Figure H.1 – Diagram of AUTBUS industrial bus service deployment	193
Figure H.2 – Diagram of networking topology based on the virtualized bus	193
Figure H.3 – Virtual network topology based on logical business function RT1.....	194
Table 1 – Unsigned type data coding	16
Table 2 – UINT16 type data coding	17
Table 3 – TIMEV type data coding	17
Table 4 – DATE2000 type coding.....	17
Table 5 – TIMEOFDAY type coding.....	18
Table 6 – TIMEDIFFER type coding	18
Table 7 – STRING type data coding	18
Table 8 – Physical device configuration information table	25
Table 9 – System configuration related information table	26
Table 10 – PhL synchronization management information table	27
Table 11 – System diagnosis and maintenance related information table	28
Table 12 – Physical communication resource management information table.....	29
Table 13 – Protocol stack version management information table	31
Table 14 – Link node management information table	32
Table 15 – Link timeout management information table.....	33
Table 16 – Time management information table	34
Table 17 – Network management information table	35
Table 18 – AUTBUS TMs and corresponding parameters.....	42
Table 19 – Working mode under carrier mode A	43

Table 20 – Working mode under carrier mode B	44
Table 21 – Ph-Param service primitives and parameters	45
Table 22 – Ph-Param service primitive parameter description	45
Table 23 – Ph-Data service primitives and parameters	45
Table 24 – Ph-Data service primitive parameter description	46
Table 25 – Ph-Clock-Sync service primitives and parameters	46
Table 26 – Ph-Clock-Sync service primitive parameter description	46
Table 27 – Ph-RESET primitives and parameters	48
Table 28 – Ph-RESET service primitive parameter description	48
Table 29 – Ph-SET-VALUE primitives and parameters	48
Table 30 – Ph-SET-VALUE primitive parameter status description	48
Table 31 – Ph-GET-VALUE service primitives and parameters	48
Table 32 – Ph-EVENT service primitive and parameters	49
Table 33 – Ph-SYNC service primitives and parameters	49
Table 34 – RS code mode	54
Table 35 – Convolutional code mode	55
Table 36 – Bit interleaving parameters	56
Table 37 – OFDM configuration parameters	57
Table 38 – Modulation Coding Scheme in carrier mode A	58
Table 39 – Modulation Coding Scheme in carrier mode B	58
Table 40 – Minimum services at MDS-MAU interface	59
Table 41 – Allowable constellation diagram errors in different modulation modes	61
Table 42 – System transmission parameters	62
Table 43 – Transmission medium interface	62
Table 44 – NodeID address assignment of AUTOBUS DLL	67
Table 45 – NodeID and MAC address mapping	68
Table 46 – Members of Multicast Group Mapping Table Description	68
Table 47 – CLMDTA service primitives and parameters	74
Table 48 – CLMDTA service primitive parameter description	74
Table 49 – CLMDTNA service primitives and parameters	76
Table 50 – CLMDTNA service primitive parameter description	76
Table 51 – CLMDTRA service primitives and parameters	78
Table 52 – CLMDTRA service primitive parameter description	78
Table 53 – CLMDTRRNA service primitives and parameters	80
Table 54 – CLMDTRRNA service primitive parameter description	80
Table 55 – CMDTA service primitives and parameters	82
Table 56 – CMDTA service primitive parameter description	82
Table 57 – CMDTNA service primitives and parameters	84
Table 58 – CMDTNA service primitive parameter description	84
Table 59 – DLS status output value description	85
Table 60 – Data-link config management service	86
Table 61 – Data-link config management service primitive parameter description	86
Table 62 – CFG_PARAM_INFO structure description	87

Table 63 – TIMEOUT_CFG structure description	88
Table 64 – GROUP_IDMAP_S structure description.....	88
Table 65 – NODEID_MAC_S structure description	88
Table 66 – COMM_RES_CFG structure description	89
Table 67 – Data-link discovery service primitives and parameters.....	91
Table 68 – Data-link discovery management service primitive parameter description	91
Table 69 – NODE_MGT_INFO_S structure description	92
Table 70 – Data-link maintenance service primitives and parameters.....	94
Table 71 – Data-link maintenance service primitive parameter description	94
Table 72 – DIAG_INFO_S structure member parameter description	94
Table 73 – Data-link establish management service primitives and parameters.....	96
Table 74 – Data-link establish management service parameter description	96
Table 75 – CH_RES_INFO_S structure member description	97
Table 76 – Data-link release management service primitives and parameters	98
Table 77 – Data-link release management service primitive parameter description	99
Table 78 – Data-link update management service primitives and parameters	100
Table 79 – Data-link update management service primitive parameter description	100
Table 80 – DLMS status return value description	101
Table 81 – Delay measurement service primitives and parameters	102
Table 82 – Delay measurement service primitive parameter description.....	103
Table 83 – Clock synchronization service primitives and parameters	104
Table 84 – Clock synchronization service primitive parameter description.....	105
Table 85 – Clock interrupt service primitives and parameters.....	106
Table 86 – Clock interrupt service primitive parameter description	106
Table 87 – DLCSS status return value description	107
Table 88 – DLDE state transition description	131
Table 89 – DLME state machine state transition description	133
Table 90 – DLCE state machine state transition description	134
Table 91 – Description of time information structure TIMEINFO_S.....	138
Table 92 – Description of clock option information structure CLOCK_OPTION_INFO_S.....	138
Table 93 – Description of network configuration parameter structure NETWORK_CFG_PARA_S	139
Table 94 – Description of MAC mapping table NETWORKID_MAC_MAP_TABLE_S	139
Table 95 – Description of IP mapping table structure IP_MAP_TABLE_S.....	140
Table 96 – Service data mapping table parameter list	142
Table 97 – Communication models supported by AUTOBUS AL ASEs.....	145
Table 98 – Application service interface return value list.....	145
Table 99 – RT Data service interface parameters.....	146
Table 100 – nRT data service interface parameters	148
Table 101 – Timing service interface parameters	151
Table 102 – Resource service interface parameters.....	154
Table 103 – Addressing service interface parameters	157
Table 104 – Management service interface parameters	161

Table 105 – Virtual service interface parameters	168
Table 106 – Read service parameters.....	170
Table 107 – Write service parameters.....	170
Table 108 – Application service errcode description.....	171
Table 109 – AL service type flag encoding.....	172
Table 110 – State transition table of publisher state machine.....	177
Table 111 – State transition table of subscriber state machine.....	178
Table 112 – State transition table of client state machine.....	179
Table 113 – State transition table of server state machine	180
Table 114 – State transition table of ALCE state machine	181
Table 115 – State transition table of ALDE state machine	182
Table 116 – State transition table of ALME state machine.....	183
Table B.1 – RS code (255,247) generating polynomial.....	187
Table B.2 – RS code (255,239) generating polynomial.....	187
Table B.3 – RS code (255,223) generating polynomial.....	187
Table C.1 – Example of NodeID and MAC address mapping table saved on TN.....	188
Table H.1 – Virtual bus environment node NETWORKID list	195

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
BROADBAND FIELDBUS SPECIFICATION – AUTBUS**
FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 62356 has been processed by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
65C/973/DPAS	65C/983/RVDPAS

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

INDUSTRIAL COMMUNICATION NETWORKS – BROADBAND FIELDBUS SPECIFICATION – AUTBUS

1 Scope

This document defines the broadband fieldbus specification AUTBUS. AUTBUS implements real-time, high reliability and deterministic transmission and application for both industrial fieldbus data and ISO/IEC/IEEE 8802-3 Ethernet data by shared medium bus.

This document explains the structure and content of AUTBUS, and describes the definition and specification of Physical Layer (PhL) protocol / service, Data-link Layer (DLL) protocol / service and Application Layer (AL) protocol / service of AUTBUS.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3:1997, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC/IEEE 8802-3:2017, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Standard for Ethernet*