

Edition 2.0 2024-08

TECHNICAL REPORT



LVDC systems – Assessment of standard voltages and power quality requirements

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.020 ISBN 978-2-8322-9130-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWO)RD	7
INTRODU	JCTION	9
1 Scor	pe	10
2 Norr	native references	10
3 Tern	ns and definitions	10
	cture of LVDC systems	
4.1	General	
4.1	Architecture	
4.3	Operation modes	
4.3.	·	
4.3.2	•	
_	C voltage division	
5.1	General	
5.2	Voltage bands	
5.3	Operation ranges with respect to DC voltage and time	
5.4	States	
6 Pow	er quality phenomena relevant to LVDC networks	
6.1	General	
6.2	Relationships between voltage band and power quality in LVDC systems	
6.3	Relationship between oscillation and power quality in LVDC systems	
6.4	Supply voltage deviation	
6.5	Ripple and high frequency interference	
6.6	Voltage swell	
6.7	Voltage dip	24
6.8	Voltage supply interruption	25
6.9	Rapid voltage change (RVC)	25
6.10	Voltage surges	26
6.11	Voltage unbalance	27
7 Guio	lance for voltages and power quality in LVDC system	28
7.1	Considerations for voltages in distribution DC networks	28
7.1.	1 General	28
7.1.2	2 Factors considered to define voltage values	28
7.1.3	B DC voltages	30
7.2	EMC, compatibility and testing of equipment	31
7.3	Considerations for DC power quality	33
7.4	Measurement methods	34
7.4.		
7.4.2	,	
7.4.3	1	
7.4.4		
7.4.5	,	
7.5	DC power quality standardization framework	
	(informative) PQ waveforms collected from a certain LVDC project	
	(informative) A LVDC oscillation typical example	
Annex C	(informative) Supply radius in DC distribution systems	40
Annex D	(informative) Electric power and power quality computation in DC system	41

D.1	DC mean and RMS values of voltage or current	41
D.2	General electric power system: decomposition of a general electric load	41
D.3	Computation of electric powers and PQ indices	42
D.3	.1 Computation of electric values in time domain	42
D.3	·	
D.3	.3 Total harmonic distortion T_{hd} used in AC system	44
D.3	.4 The relation of different electric powers	45
D.4	Representation of electric powers in AC system	46
D.5	Representation of electric powers in DC system	46
D.6	Power quality indices in DC system	47
D.6		
D.6		
D.6	• • • • • • • • • • • • • • • • • • • •	
D.6	•••	
D.7	Illustration example of distortion power in DC system	
D.8	Main conclusions on electric value computation in DC system	
D.9	Need of characteristics of DC voltage	
	(informative) District LVDC system demonstration project in Tongli, China	
E.1	Project overview	
E.2	Voltage level selection principle	
E.3	System operation	
Annex F	(informative) A typical MV&LVDC distribution system in Wujiang, China	
F.1	Project overview	
F.2	Voltage selection	55
	6 (informative) An office building with general building utilities and office	50
•	ces	
G.1	Sustainable circular building	
G.2	Zone system	
G.3	Aspects regarding the DC zone classification in DC installation	
	I (informative) An example of configurations for active DC systems	
	General	
H.2	Structure	
H.3	State of grid (SOG)	
	(informative) Preferred voltage in different countries	
I.1	Preferred voltage in China	
1.2	Preferred voltage in the Netherlands	
I.3	Preferred voltage in Germany	
	(informative) CIGRE approaches for DC systems	
Annex L	(informative) Voltage level in Current OS	
L.1	Introduction to the organization	
L.2	Voltages used in Current OS	
	1 (informative) Voltage level in DC-INDUSTRY and open DC alliance	
M.1	General	
M.2	Operating range of the components	
M.3	Regulated feeders	
M.4	Uncontrolled feeders	
M 5	Typical DC loads	86

M.6 Co	nverters for energy storage or photovoltaic	87
M.7 DC	breakers	87
M.8 No	minal voltage	87
M.9 Vo	Itage bands and limits	87
M.10 Op	erating status of the DC grid	89
M.10.1	General	
M.10.2	Duration for the operating statuses	
M.10.3	Examples for the operating statuses	
M.10.4	Description of operating statuses	
Bibliography.		92
Figure 1 – Ur	nipolar, balanced and bipolar DC systems	15
Figure 2 – Vo	ltage bands in DC systems	16
Figure 3 – DO	C Voltage areas for safe interoperability	18
Figure 4 – Re	elationships between voltage band and power quality in LVDC systems	20
Figure 5 - Os	scillation example	21
_	voltage swell example	
•	oltage dip example	
_	/C event: example of a change in average voltage that results in an RVC	20
		26
Figure 9 – Ex	ample of voltage surge	27
Figure 10 – A	schematic of a bipolar system (the CIGRE B4 DC test system)	28
Figure 11 – L	VDC distribution domain and installation domain	29
Figure 12 – R	Relation between disturbance levels (schematic significance only)	31
Figure 13 – L	VAC voltage compatibility and immunity levels	32
	Voltage deviation caused by load switching	
•	Voltage ripple in steady state	
	Voltage dip caused by the start-up of motor load	
•	Equivalent topology of the substation	
	The voltage and current oscillation waveform on ±375 V bus	
•	Equivalent model of a general electric load	
•	Representation of electric powers in AC system	
•	Representation of electric powers in DC system	
_	Ripples of output DC voltage of positive of a PWM AC/DC converter	47
•	Spectral analysis of DC voltage and current measured at the input of an d	48
Figure D.6 –	DC powers caused by intermittent DC current	50
Figure D.7 –	LVAC compatibility level measured in differential mode values	51
Figure E.1 – A	Architecture of the district LVDC system in Tongli	52
Figure F.1 – I	Location map of the typical MV&LVDC system	55
•	The structure of the MV&LVDC system in China	
_	Office building with general building utilities and office work places	
_	Example of zone 0 and zone 1	
•	Example of zone 0, 1 and 2	
_	Example of zone 2 system	
	=	

Figure G.5 – Purely zone 3 system with the protection devices of distributed sources	04
Figure G.6 – Example of a zone 4 system with a single source	64
Figure G.7 – Current OS system overview and safety zones	65
Figure G.8 – DC zones label	65
Figure G.9 – Examples of DC zones labels	66
Figure H.1 – Active DC distribution system	68
Figure H.2 – DC distribution system with one load and one source	70
Figure H.3 – DC distribution system with more than one load and a source and increasing source power	71
Figure H.4 – Distribution system with more than one load and a source and dump load active	71
Figure H.5 – Distribution system with more than one load and source in overloaded mode	72
Figure J.1 – DC voltage definitions	77
Figure J.2 – DC voltage bands relative to earth	78
Figure J.3 – DC voltages to earth – examples	79
Figure K.1 – Temporary DC pole to ground voltage profiles in DC systems	80
Figure L.1 – Threshold of ventricular fibrillation	81
Figure L.2 – Voltage used in Current OS	83
Figure L.3 – Voltage bands of different levels	84
Figure M.1 – Operating ranges of the components (line-to-line voltage)	85
Figure M.2 – DC voltage of uncontrolled rectifiers (line-to-line)	86
Figure M.3 – Voltage bands and limits in DC-INDUSTRY	88
Figure M.4 – Operating status depending on voltage and duration	90
Table 1 – Voltage between lines (unipolar systems) or line and mid-point (bipolar systems) for installation domain	29
Table 2 – Voltage between lines (unipolar systems) or line and mid-point (bipolar systems) for distribution domain	30
Table 3 – Immunity test requirements for DC input and output power ports of devices meant to be used in residential, commercial and light industrial environment	32
Table 4 – Immunity test requirements for DC input and output power ports of devices meant to be used in industrial environment	33
Table 5 – Ripple on DC input power port immunity test	33
Table C.1 – 1,5 (±0,75) kV typical supply radius of overhead DC lines	40
Table C.2 – 750 (±375) V, 220 (±110) V typical section supply radius of overhead DC lines	40
Table D.1 – Different powers	50
Table F.1 – The current carrying capacity of medium voltage AC and DC cables	56
Table F.2 – The voltage level corresponding relationship between AC and DC with the same transmission capacity	56
Table F.3 – DC voltage range with modulation ratio limit	57
Table G.1 – Safety zones and labels	66
Table G.2 – Functions for different DC zone classification	67
Table H.1 – Examples in case of 350/700 V DC systems	69
Table H 2 – Allowed cable voltage drop	70

Table I.1 – Nominal voltage in LVDC distribution system	73
Table I.2 – Nominal voltage in ELVDC equipment	74
Table I.3 – Comparison between DC and AC system voltages	75
Table I.4 – Overview of the DC voltage classes (VC) and the corresponding $U_{f 2}$ and	
$U_{f 3}$ values	76
Table M.1 – Nominal voltage in DC-INDUSTRY	87

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LVDC SYSTEMS – ASSESSMENT OF STANDARD VOLTAGES AND POWER QUALITY REQUIREMENTS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 63282 has been prepared by IEC technical committee 8: System aspects of electrical energy supply. It is a Technical Report.

This second edition cancels and replaces the first edition published in 2020. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Optimized terms and definitions in Clause 3:
 Introduction of new terms and definitions and refining of existing ones.
- b) Modified the definition of voltage bands: In Clause 5, the definition of voltage limits in voltage bands is added, from U_1 to U_6 . The definition of voltage bands, from B4 to B7, is modified.

c) Distinguished the difference between oscillation and power quality phenomenon:

In Clause 3, the definition of oscillation is added based on IEV 103-05-04. In 6.3, relationship between oscillation and power quality is clarified. Annex B gives a LDC oscillation typical example which has really happened in a MV&LVDC system in China.

d) Modified the recommended voltage for distribution DC network:

The factors considered in voltage values definition is clarified. And the voltage is divided in two domains, distribution domain and installation domain. The voltage recommendation in LVDC is listed corresponding to voltage bands.

e) Modified the voltage immunity level assessment:

It is mentioned in 7.2 that the assessment of voltage immunity levels of mass LVDC power electronic devices need to be further discussed, ripple as an example is introduced.

f) Added DC power quality measurement methods:

In 7.3, DC power quality measurement methods is introduced based on AC methodologies. And some additional DC power quality indices are recommended to assess the DC system.

DC electric power and power quality measurement methods are introduced in 7.4, defining the electric value integration time and frequency ranges.

Typical electric power and power quality computation methods are modified in Annex D.

g) Added an annex on MVDC system:

A use case of a typical MV&LVDC distribution system is added in Annex F, to support developments of TS of 8A and 8B on DC microgrids.

h) Added an annex on Current OS voltage level:

The voltage level applied in Current OS is introduced in Annex L to give more information on the LVDC voltage level recommendation.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
8/1695/DTR	8/1704/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- · revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

LVDC (low voltage direct current) distribution systems have recently been recognized by a number of stakeholders as an alternative approach to provide efficient power supply to the consumers. LVDC covers a wide range of power applications from USB-C up to megawatts for aluminium melting. LVDC is seen as a solution for greener and more sustainable energy systems in developed economies as well as an alternative option for electricity access in developing countries.

In industrial applications, LVDC is utilized where processing of resources results in the production, distribution and storage of physical goods, especially in a factory or special area of a factory.

The standardization of DC voltages is a key issue, and urgent work is needed. Existing LVAC systems have different standard voltages, depending on the geography and application. LVDC distribution voltages are optimized to provide a good context for industries that import and export equipment but also for general travellers. Appropriate international LVDC voltage ranges will provide a basis for design and testing of electrical equipment and systems and ease of transition for equipment from AC to DC supply.

LVDC voltages meet the range of use cases where LVDC systems can make a difference. The list of standard voltages is as short as possible and allow for cost-effective and safe operation.

The PQ (power quality) issues in DC power systems are not identical to those in AC systems, but there are some common issues. Power quality considerations are well studied and standardized on AC power systems, but many power quality phenomena and EMC have not yet been fully identified and evaluated for DC distribution systems.

Power electronic converters/inverters add further demands. Power quality phenomena in LVDC distributed systems can be related to the structure of the entire system, and the operating condition of sources and loads. At the same time, the DC output performance of a single converter and the coordination among several converters can also result in different power quality issues and grid stability.

Requirements for power quality and EMC in LVDC distribution are established in order to provide a solid basis for the planning and operation of LVDC distribution systems. In addition, the design and configuration of the protection system is addressed with the objective of enhancing the availability of the source, the reliability, and the lifetime of the system.

Generally, the standardization of voltage level and PQ phenomena of LVDC distribution greatly stimulate the wide adoption of LVDC.

This document provides information on the following topics: standard voltages, EMC requirements, power quality, and measurement methods.

LVDC SYSTEMS – ASSESSMENT OF STANDARD VOLTAGES AND POWER QUALITY REQUIREMENTS

1 Scope

The purpose of this document is to collect information and report experience for the standardization of voltage levels and related aspects (power quality, EMC, measurement, etc.) for LVDC systems (systems with nominal voltage up to and including 1 500 V DC).

Rationale for the proposed voltage values is given. Variation of parameters for the voltage (power quality) for their boundaries are defined. Nevertheless, some of the technical items are not exhaustively explained in this document and some gaps are identified for future work.

Attention is paid to the definition of DC voltage.

Systems in which a unipolar voltage is interrupted periodically for certain purposes, e.g. pulse voltage, are not considered.

Traction systems are excluded from this document.

This document gives technical inputs to TCs in charge of the standardization of different issues and coordinated by SyC LVDC.

2 Normative references

There are no normative references in this document.