

TECHNICAL SPECIFICATION



**Application integration at electric utilities – System interfaces for distribution management –
Part 14: MultiSpeak – CIM harmonization**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.200

ISBN 978-2-8322-2698-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	12
2 Normative references.....	13
3 Terms, definitions, and abbreviations.....	14
3.1 Terms and definitions.....	14
3.2 Abbreviations.....	14
4 Reference model.....	15
4.1 General.....	15
4.2 CIM interface reference model.....	15
4.3 MultiSpeak reference model.....	15
4.4 MultiSpeak-CIM actor mapping.....	16
5 Document conventions.....	18
5.1 UML diagrams.....	18
6 Integration example.....	18
6.1 General.....	18
6.2 Message Header Mapping.....	19
7 Scope of the profile mappings.....	21
7.1 Profile mapping.....	21
8 1 st edition CIM meter reading to MultiSpeak 4.1.x profile mapping.....	22
8.1 Customer account config.....	22
8.2 Customer agreement config.....	24
8.3 Customer config.....	25
8.4 Customer meter data set.....	27
8.5 End device assets.....	27
8.6 ComFunction.....	28
8.7 ConnectDisconnectFunction.....	28
8.8 ElectricMeteringFunction.....	29
8.9 EndDeviceAsset.....	30
8.10 ReadingType.....	32
8.11 Register.....	33
8.12 End device controls.....	34
8.13 End device events.....	35
8.14 End device firmware.....	36
8.15 Meter asset config.....	38
8.16 Meter asset reading.....	40
8.17 Meter readings.....	42
8.18 Meter read schedule.....	44
8.19 Meter service requests.....	46
8.20 Meter readings.....	47
8.21 Activity records.....	47
8.22 ServiceDeliveryPoints.....	47
8.23 Meter system events.....	48
8.24 Pricing structure config.....	49
8.25 Receipt record.....	50
8.26 SDP Location config.....	53

8.27	Service category config	54
8.28	Service delivery point config	55
8.29	Service location config	57
8.30	Supplier config	59
8.31	Transaction record	63
9	IEC 61968-9:2013 to MultiSpeak v.5 (Release Candidate) profile mapping	65
9.1	General.....	65
9.2	Summary of changes between MultiSpeak Version 4.1.x and Version 5.0	65
9.3	Schema changes.....	67
9.4	Messaging changes.....	68
9.5	ExtensionsList.....	72
9.6	Mapping of IEC 61968-9:2013 to MultiSpeak v.5 (Release Candidate) Profile mapping.....	73
9.6.1	ActivityRecord.....	73
9.6.2	Status	74
9.6.3	ConfigurationEvents	74
9.6.4	CustomerAccountConfig	74
9.6.5	CustomerAgreementConfig	74
9.6.6	CustomerConfig	75
9.6.7	EndDeviceConfig	76
9.6.8	EndDeviceControls	80
9.6.9	EndDeviceEvents	81
9.6.10	PAN-related classes.....	83
	Annex A (normative) Embedded/Reused Class Mappings	87
	Annex B (informative) Example Mapping of MultiSpeak to CIM-based services.....	89
B.1	On Demand Read: MultiSpeak to CIM integration via ESB.....	89
B.2	Wiring the Integration	90
	Annex C (informative) UML of MultiSpeak Equivalent profiles	96
	Annex D (normative) MultiSpeak Equivalent CIM Profiles.....	105
	Bibliography	259
	Figure 1 – MultiSpeak interface reference model	16
	Figure 2 – Systems integration via an ESB (Gray, Simmins, McNaughton, Haynes, Saint, McMorran, Lambert, 2011)	18
	Figure 3 – CustomerAccountConfig CIM to MultiSpeak profile mapping	24
	Figure 4 – CustomerAgreementConfig CIM to MultiSpeak mapping	25
	Figure 5 – IEC 61968-9:2009 schema view of CustomerMeterDataSet profile	27
	Figure 6 – CIM EndDeviceControls to MultiSpeak equivalent profile mapping	35
	Figure 7 – Mapping of the CIM EndDeviceEvents to MultiSpeak mspEndDeviceEvents profile.....	36
	Figure 8 – EndDeviceFirmware CIM to MultiSpeak profile mapping	38
	Figure 9 – MeterAssetConfig CIM to MultiSpeak profile mapping.....	40
	Figure 10 – MeterReadSchedule CIM to MultiSpeak profile mapping	46
	Figure 11 – ServiceCategoryConfig profile mapping.....	55
	Figure 12 – ServiceLocationConfig CIM to MultiSpeak mapping	59
	Figure 13 – MultiSpeak Network class	59
	Figure 14 – Supplier Config profile mapping	63

Figure 15 – Preferred form of request-response messages	69
Figure 16 – Preferred form for "Initiation of an Action Messages"	69
Figure 17 – Preferred form of publish-subscribe messages	69
Figure 18 – CIM and MultiSpeak both support the Names class and subclasses as an alternative means of identifying objects	72
Figure 19 – MultiSpeak extensionsList class, used for adding attributes to a class	73
Figure 20 – Attributes of CIM generic status class	74
Figure 21 – Change to the EndDeviceControl profile which added the EndDeviceControlType class.....	81
Figure 22 – MultiSpeak V5 endDeviceEvent "shorthand" relationship	83
Figure 23 – UML representing MultiSpeak v.5 priceTierStructure classes	86
Figure B.1 – Blank BPEL project canvas that is the starting point for mapping web services and message payloads.....	89
Figure B.2 – Src folder with subfolders for MultiSpeak and CIM resources to be used in the project.	90
Figure B.3 – Creation of a BPEL partner link for the InitiateMeterReadingsService.....	91
Figure B.4 – BPEL palette options.....	91
Figure B.5 – Completing the creation of the BPEL Receive widget	92
Figure B.6 – Creation of the second MultiSpeak partner link to utilize the ReadingChangedNotification service.....	93
Figure B.7 – Creating the Reply widget to utilize the ReadingChangedNotification operation	93
Figure B.8 – The BPEL canvas with the Request-Reply pattern "wired up" to utilize the InitiateMeterReadingsByMeterID and the ReadingChangedNotification operation	94
Figure B.9 – Method invoke property editor	94
Figure B.10 – "Wiring up the service in OpenESB	95
Figure C.1 – ConnectDisconnect portion of the UML of the MultiSpeak equivalent of the EndDeviceAssets profile.....	96
Figure C.2 – UML diagram of MultiSpeak equivalent of CIM EndDeviceAssets profile.....	97
Figure C.3 – UML diagram of MultiSpeak equivalent to CIM MeterAssetReading profile.....	97
Figure C.4 – UML for MultiSpeak equivalent of the CIM MeterReadings profile.....	98
Figure C.5 – UML of MultiSpeak equivalent of the CIM MeterServiceRequests profile.....	98
Figure C.6 – UML of the MultiSpeak equivalent to the CIM MeterSystemEvents profile.....	99
Figure C.7 – UML for the MultiSpeak equivalent of the CIM PricingStructureConfig	99
Figure C.8 – UML of the MultiSpeak equivalent of the CIM ReceiptRecord profile.....	100
Figure C.9 – UML of the MultiSpeak equivalent of the CIM SDPLocationConfig profile.....	101
Figure C.10 – UML for MultiSpeak equivalent of the CIM ServiceDeliveryPointConfig profile.....	102
Figure C.11 – UML of MultiSpeak equivalent ServiceSupplierConfig profile	103
Figure C.12 – UML of MultiSpeak equivalent of CIM TransactionRecord.....	104
Table 1 – Document overview for IEC 61968-14	13
Table 2 – MultiSpeak-CIM actor mapping	17
Table 3 – MultiSpeak and IEC 61968-100 message header mapping.....	19
Table 4 – CustomerAccountConfig correlations.....	22
Table 5 – CustomerAccountConfig Transformations.....	22

Table 6 – CustomerAccountConfig Gaps	23
Table 7 – CustomerAgreementConfig correlations	24
Table 8 – CustomerAgreementConfig transformations	24
Table 9 – CustomerAgreementConfig gaps.....	25
Table 10 – CustomerConfig correlations	26
Table 11 – CustomerConfig transformations	26
Table 12 – CustomerConfig gaps	26
Table 13 – EndDeviceAssets – ComFunction.....	28
Table 14 – EndDeviceEvents – ComFunction gaps	28
Table 15 – EndDeviceAssets – ConnectDisconnect correlations.....	29
Table 16 – EndDeviceAssets – ConnectDisconnect transformations.....	29
Table 17 – EndDeviceAssets – ConnectDisconnect gaps	29
Table 18 – EndDeviceAssets – ElectricMeteringFunction	30
Table 19 – EndDeviceAssets – ElectricMeteringFunction – Transformations.....	30
Table 20 – EndDeviceAssets – ElectricMeteringFunction gaps.....	30
Table 21 – EndDeviceAssets – EndDeviceAsset.....	31
Table 22 – EndDeviceAssets – EndDeviceAsset gaps.....	32
Table 23 – EndDeviceAssets – ReadingType correlations.....	33
Table 24 – EndDeviceAssets – ReadingType gaps	33
Table 25 – EndDeviceAssets – Register gaps.....	33
Table 26 – EndDeviceControls correlations	34
Table 27 – EndDeviceControls transformations	34
Table 28 – EndDeviceControls gaps.....	34
Table 29 – EndDeviceEvents correlations.....	35
Table 30 – EndDeviceEvents transformations.....	35
Table 31 – EndDeviceEvents gaps	36
Table 32 – EndDeviceFirmware correlations	36
Table 33 – EndDeviceFirmware transformations	37
Table 34 – EndDeviceFirmware gaps	37
Table 35 – MeterAssetConfig correlations	38
Table 36 – MeterAssetConfig transformations.....	38
Table 37 – MeterAssetConfig gaps.....	39
Table 38 – MeterAssetReading correlations.....	41
Table 39 – MeterAssetReading transformations.....	41
Table 40 – MeterAssetReading gaps	42
Table 41 – MeterReadings correlations	43
Table 42 – MeterReadings transformations.....	43
Table 43 – MeterReadings gaps.....	44
Table 44 – MeterReadSchedule correlations.....	45
Table 45 – MeterReadSchedule transformations.....	45
Table 46 – MeterReadSchedule gaps	45
Table 47 – MeterServiceRequests correlations	47
Table 48 – MeterServiceRequests transformations	47

Table 49 – MeterServiceRequests gaps	48
Table 50 – MeterSystemEvents correlations	48
Table 51 – PricingStructureConfig correlations	49
Table 52 – PricingStructureConfig transformations	49
Table 53 – PricingStructureConfig gaps.....	50
Table 54 – ReceiptRecord correlations	51
Table 55 – ReceiptRecord transformations	51
Table 56 – ReceiptRecord gaps	52
Table 57 – SDPLocationConfig correlations.....	53
Table 58 – SDPLocationConfig transformations	53
Table 59 – SDPLocationConfig gaps	54
Table 60 – ServiceCategoryConfig correlations	54
Table 61 – ServiceCategoryConfig transformations.....	54
Table 62 – ServiceCategoryConfig gaps	54
Table 63 – ServiceDeliveryPointConfig correlations	55
Table 64 – ServiceDeliveryPointConfig transformations	56
Table 65 – ServiceDeliveryPointConfig gaps	57
Table 66 – ServiceLocationConfig correlations	58
Table 67 – ServiceLocationConfig transformations	58
Table 68 – ServiceLocationConfig gaps.....	58
Table 69 – Service supplier correlations	61
Table 70 – ServiceSupplierConfig transformations.....	61
Table 71 – ServiceSupplierConfig gaps	62
Table 72 – TransactionRecord correlations.....	64
Table 73 – TransactionRecord transformations.....	64
Table 74 – TransactionRecord gaps	65
Table 75 – Relationships between Version 4.1 and Version 5.0 present-tense verb names	70
Table 76 – Relationships between Version 4.1 and Version 5.0 past-tense verb names	71
Table 77 – CIM to MultiSpeak Activity mapping	73
Table 78 – CustomerAccountConfig mapping changes for CIM 2nd edition, MSP v.5	75
Table 79 – CustomerConfig mapping changes for CIM 2 nd edition, MSP v.5	76
Table 80 – EndDeviceConfig mapping changes for CIM 2nd edition, MSP v.5.....	77
Table 81 – Mappings for classes added to EndDeviceConfig.....	78
Table 82 – SimpleEndDeviceFunction mapping for CIM 2nd edition to MSP v.5.....	80
Table 83 – CIM Seals class mapping to MSP v.5	80
Table 84 – CIM EndDeviceControlsType class mapping to MSP v.5	81
Table 85 – CIM EndDeviceControlsType class mapping to MSP v.5 with support for PAN classes	81
Table 86 – CIM 2nd edition – MSP v.5 EndDeviceEvent mapping and gaps.....	82
Table 87 – PANDemandResponse mapping from CIM to MSP v.5	84
Table 88 – PANDisplay class mapping	85
Table 89 – PANPricing class mapping	85
Table A.1 – Address Correlations	87

Table A.2 – Phone Number Correlations.....88
Table A.3 – Service Location related transformations88
Table A.4 – Electronic Address related transformations88

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**APPLICATION INTEGRATION AT ELECTRIC UTILITIES –
SYSTEM INTERFACES FOR DISTRIBUTION MANAGEMENT –****Part 14: MultiSpeak – CIM harmonization**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 61968-14, which is a technical specification, has been prepared by IEC technical committee 57: Power systems management and associated information exchange.

This publication contains attached files in the form of xsd files. These are a copy of the text originally contained in Annex D of this publication. These files are intended to be used as a complement and do not form an integral part of the publication.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
57/1504/DTS	57/1555/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61968 series, published under the general title *Application integration at electric utilities – System interfaces for distribution management*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61968 seeks to address the need for harmonization between the two leading standards for software interoperability that serve the electric utility industry; MultiSpeak™, which is maintained by the MultiSpeak Initiative, and the common information model (CIM), which is maintained by the International Electrotechnical Commission. While the CIM is an international standard, MultiSpeak has a significant footprint especially among municipal and cooperative utilities and vendors that serve these utilities, particularly in the United States. MultiSpeak is also used in fifteen countries worldwide.

The goal of this technical specification is to harmonize the two standards so that the capability currently inherent in MultiSpeak could eventually be expressed as a profile within the CIM. To that end this particular effort will map V4.1x of MultiSpeak with IEC 61968-9:2009, *Interfaces for meter reading and control* of the CIM. This mapping will occur at the CIM profile level, so that each CIM profile will have a mapping to a corresponding element in MultiSpeak. This will serve two ends; (a) for those that need to translate from interfaces based on one standard to another, this mapping will give a roadmap for how that is accomplished, and (b) this exercise will reveal where alignment currently exists between the two standards and where gaps exist. As each standard goes through successive releases, reviews of business requirements which necessitated the respective releases and updates can be made in both CIM and MultiSpeak to narrow existing gaps.

As part of this exercise this part of IEC 61968 will also give a practical example of the interoperability between the two standards using an archetype of one interface being mapped to another through an enterprise service bus (ESB). This proof of concept will utilize OpenESB as this is open source and freely available. This archetype will cover the on demand meter read use case, where a source application will initiate a request for an on demand read and this request will be served by a destination application. The applications themselves will not be developed; only the interface mapping through an ESB from a MultiSpeak based source to a CIM based destination will be developed.

Multiple standards that cover the same information domain present a problem for the vendor community when developing products, and for the customers that would use these products. The classic challenge becomes one of determining which standards to support or how best to support one or both standards. The problem for the customer is integrating products that follow different standards to work with each other.

As part of a harmonization effort both 1st edition and 2nd edition CIM profiles have been mapped to equivalent MultiSpeak profiles. The reason this approach was used is that the CIM and MultiSpeak models are too large to be compared in their entirety. It was determined that the profile, representing a snapshot of the respective models and something that has been determined to be useful in the exchange of information between systems, would be a better place to begin making comparisons.

The harmonization effort includes mapping of the profiles and an assessment detailing where the profiles correlate, where a transformation needs to occur, e.g. concatenating several fields to map to a single field in the corresponding profile, and where gaps exist.

In addition to the mapping of the profiles, Annex A lists the suggested changes to the respective standards for consideration in future releases.

IEC 61968, taken as a whole, defines interfaces for the major elements of an interface architecture for Distribution Management Systems (DMS). Part 1: Interface Architecture and General Recommendations, identifies and establishes requirements for standard interfaces based on an Interface Reference Model (IRM). Parts 3 to 9 of IEC 61968 define interfaces relevant to each of the major business functions described by the Interface Reference Model.

As used in IEC 61968, a DMS consists of various distributed application components for the utility to manage electrical distribution networks. These capabilities include monitoring and

control of equipment for power delivery, management processes to ensure system reliability, voltage management, demand-side management, outage management, work management, automated mapping and facilities management.

IEC 61968 is limited to the definition of interfaces and is implementation independent. They provide for interoperability among different computer systems, platforms, and languages. Methods and technologies used to implement functionality conforming to these interfaces are considered outside of the scope of IEC 61968; only the interface itself is specified in this standard.

APPLICATION INTEGRATION AT ELECTRIC UTILITIES – SYSTEM INTERFACES FOR DISTRIBUTION MANAGEMENT –

Part 14: MultiSpeak – CIM harmonization

1 Scope

This part of IEC 61968, which is a technical specification, explains how to do a mapping from CIM to MultiSpeak using an XML mapping tool, and the inclusion of an example project that gives practical guidance on the interoperability and mapping of source and destination applications through an ESB using an on demand meter read as the archetype.

This technical specification will also cover the mapping of IEC 61968-9:2009 profiles to equivalent MultiSpeak v.4.1x message profiles.

Each CIM profile will have a corresponding MultiSpeak profile with a prefix of “msp”. For example, CIM EndDeviceEvents matches the MultiSpeak mspEndDeviceEvents.

The following profiles from IEC 61968-9:2009 are harmonized:

- AuxiliaryAgreementConfig
- CustomerAccountConfig
- CustomerAgreementConfig
- CustomerConfig
- CustomerMeterDataSet
- EndDeviceAssets
- EndDeviceControls
- EndDeviceEvents
- EndDeviceFirmware
- MeterAssetConfig
- MeterAssetReading
- MeterReadings
- MeterReadSchedule
- MeterServiceRequests
- MeterSystemEvents
- PricingStructureConfig
- ReceiptRecord
- SDPLocationConfig
- ServiceCategoryConfig
- ServiceDeliveryPointConfig
- ServiceLocationConfig
- SupplierConfig
- TransactionRecord

Although the profiles will have some changes as part of the IEC 61968-9:2013, the scope of the harmonization effort for the 2nd edition to MultiSpeak v.5 (release candidate), will be

limited to these same profiles. This will give the practitioner an ample set of mapping examples and allow them to make meaningful comparisons of the changes between IEC 61968-9:2009 and 2013 profiles and the respective mapping to MultiSpeak.

This part of IEC 61968 contains the clauses listed in Table 1.

Table 1 – Document overview for IEC 61968-14

Clause	Title	Purpose
1.	Scope	The scope and purpose of the document are described.
2.	References (Normative)	Documents that contain provisions which, through reference in this text, constitute provisions of this International Standard.
3.	Terms, definitions, and abbreviations	Establish the common terms used in this specification.
4.	Reference and Information Models	Description of general approach to metering system, reference model, use cases, interface reference model, meter reading and control functions and components, message type terms and static information model for both CIM and MultiSpeak.
5.	Document Conventions	Message types related to the exchange of information for documents related to maintenance and construction.
6.	Integration example	The main purpose of this standard is to provide guidance for integration. Since both MultiSpeak and CIM use web services for integration, this section addresses the needs to map the message headers as well as the profiles.
7.	Scope of the profile mappings	Enumerates the profiles that are mapped as part of this specification
8.	1st edition CIM Meter Reading to MultiSpeak 4.1.x Profile Mapping	Gives the reader specific guidance on CIM to MultiSpeak mapping.
9.	2 nd edition CIM Meter Reading to MultiSpeak 5.0.x Profile Mapping	Gives the reader specific guidance on CIM to MultiSpeak mapping.
Annex A	EMBEDDED/REUSED CLASS MAPPINGS	Rather than have mappings that appear in several profiles appear over and over, these repeated mappings are located in this annex for reference.
Annex B	Example Mapping of MultiSpeak to CIM-based services	This annex demonstrates one example of how to “wire” MultiSpeak to CIM-based web services through an enterprise service bus.
Annex C	UML of MultiSpeak Equivalent profiles	Provides examples of how to create MultiSpeak equivalents of various CIM profiles.
Annex D	MultiSpeak Equivalent CIM Profiles	This annex provides the XML for the MultiSpeak equivalent of the various CIM Profiles.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-300, *International Electrotechnical Vocabulary – Electrical and electronic measurements and measuring instruments*

IEC 61968-1, *Application integration at electric utilities – System interfaces for distribution management – Part 1: Interface architecture and general recommendations*

IEC TS 61968-2, *Application integration at electric utilities – System interfaces for distribution management – Part 2: Glossary*

IEC 61968-9:2013, *Application integration at electric utilities – System interfaces for distribution management – Part 9: Interfaces for meter reading and control*

IEC 61968-100, *Application integration at electric utilities – System interfaces for distribution management – Part 100: Implementation profiles*

IEC TR 62051, *Electricity metering – Glossary of terms*

IEC 62055-31, *Electricity metering – Payment systems – Part 31: Particular requirements – Static payment meters for active energy (classes 1 and 2)*

ISO 8601:2004, *Data Elements and Interchange Formats – Information Interchange – Representation of Dates and Times*

ISO 4217:2008, *Codes for the representation of currencies and funds.*

MultiSpeak Version 4.1.6