# INTERNATIONAL STANDARD

ISO 17365

Second edition 2013-03-01

# Supply chain applications of RFID — Transport units

Applications de chaîne d'approvisionnements de RFID — Unités de transport



### ISO 17365:2013(E)



# **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Coi	Contents		
Fore	word		v
Intr	oduction	1	vi
1	Scope		1
2	-	rmance and performance specifications	
3		ative references	
		s and definitions	
4			
5	5.1 5.2 5.3 5.4	epts Differentiation between this layer and the preceding layers Returnable packaging item Unique identification of transport units Other identification requirements	
6	Differ	entiation within this layer	8
7	7.1 7.2 7.3 7.4 7.5 7.6 7.7	Introduction System data elements Tag structure Protocol control (PC) bits Data elements Traceability Combined transport unit and RTI data Unique item serialization	
8	Bata s 8.1 8.2 8.3 8.4 8.5	Confidentiality Data integrity Data preservation Interrogator authentication Non-repudiation/audit trail	
9	Identi	ification of RFID labelled material	15
10		In readable information Human readable interpretation Human readable translation Data titles Backup	15 16
11	11.1 11.2 11.3 11.4 11.5 11.6 11.7 11.8 11.9 11.10 11.11 11.12 11.13	peration  Data protocol  Minimum performance requirements (range and rate)  Environmental parameters  Tag orientation  Packaging material  Shock loads and abrasions  Tag lifetime  Minimum system reliability  Air interface  Memory requirements for application  Sensor interface, if applicable  Real time clock option  Safety and regulatory considerations  Tag reusability	17 17 18 18 18 18 18 19 19 19 19
12	Tanlo	ocation and presentation	20

iii

# ISO 17365:2013(E)

	12.1	Material on which the tag is mounted or inserted	20
		Geometry of the package/tag environment	
13	Interrogator and reader requirements		20
		Safety and regulatory considerations	
		Data privacy	
14	Inter	operability, compatibility and non-interference with other RF systems	20
Anne	x A (no	rmative) Encoding	21
Bibli	ograph	y	31

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17365 was prepared by Technical Committee ISO/TC 122, Packaging.

This second edition cancels and replaces the first edition (ISO 17365:2009), which has been technically revised.

This International Standard has one annex, <u>Annex A</u>, which provides normative information.

# Introduction

The 'Supply Chain' is a multi-level concept that covers all aspects of taking a product from raw materials to a final product including shipping to a final place of sale, use and maintenance, and potentially disposal. Each of these levels covers many aspects of dealing with products and the business process for each level is both unique and overlapping with other levels.

This International Standard has been created in order to ensure compatibility at the physical, command and data levels with the four other International Standards under the general title Supply chain applications of RFID. Where possible, this compatibility takes the form of interchangeability. Where interchangeability is not feasible, the International Standards within this suite are interoperable and non-interfering. The International Standards within the complete series of Supply chain applications of RFID include

- ISO 17363, Supply chain applications of RFID Freight containers;
- ISO 17364, Supply chain applications of RFID Returnable transport items (RTIs) and returnable packaging items (RPIs);
- ISO 17365, Supply chain applications of RFID Transport units;
- ISO 17366, Supply chain applications of RFID Product packaging;
- ISO 17367, Supply chain applications of RFID Product tagging.

These International Standards define the technical aspects and data hierarchy of information required in each layer of the supply chain. The air-interface and communications protocol standards supported within the *Supply chain applications of RFID* International Standards are ISO/IEC 18000; commands and messages are specified by ISO/IEC 15961 and ISO/IEC 15962; semantics are defined in ISO/IEC 15418; syntax is defined in ISO/IEC 15434.

Although not pertinent to this International Standard, the following work is considered valuable:

- ISO/IEC JTC 1, *Information technology*, SC 31, *Automatic identification and data capture techniques*, in the areas of air interface, data semantic and syntax construction and conformance standards, and
- ISO/TC 104, *Freight containers*, in the area of freight container security, including electronic seals (e-seals) (i.e. ISO 18185) and container identification.

This International Standard defines the requirements for RFID tags for transport units. Transport units are defined here as either a transport package or a unit load (see ISO 17364:2013, 4.6 and 4.9).

An important concept here is the use cases of such things as *unitized loads*, pallets and returnable transport items. How a pallet is used can determine whether it is covered under ISO 17364 as a *returnable transport item* or within this International Standard as a *transport unit*. If ownership title of the pallet remains with its owner then the applicable International Standard is ISO 17364. If the ownership title of a pallet is transferred to the customer as part of a unitized load then it is considered an element of that unitized load, and this International Standard is applicable.

Specific to transport units is the grouping of (packaged) products, in order to make these more suitable for efficient and effective transport and distribution. The transport unit provides an added value for the product being sold, mostly in terms of logistics performance. RFID tagged transport units can help further optimize the supply chain.

Additionally, this edition of this International Standards introduces the concept of returnable packaging items (RPIs). RPIs are components of the transport unit that must be tracked as well as the transport unit itself as an asset of the owner/shipper. Annex A in ISO 17364:2013 provides guidance on RPIs.

# Supply chain applications of RFID — Transport units

# 1 Scope

This International Standard defines the basic features of RFID for use in the supply chain when applied to transport units. In particular it

- provides specifications for the identification of the transport unit,
- makes recommendations about additional information on the RF tag,
- specifies the semantics and data syntax to be used,
- specifies the data protocol to be used to interface with business applications and the RFID system,
- specifies the minimum performance requirements,
- specifies the air interface standards between the RF interrogator and RF tag, and
- specifies the reuse and recyclability of the RF tag.

## 2 Conformance and performance specifications

All of the devices and equipment that claim conformance with this International Standard shall also conform to the appropriate sections and parameters specified in ISO/IEC 18046 for performance, and ISO/IEC 18047-6 (for ISO/IEC 18000-63, Type C) and ISO/IEC/TR 18047-3 (for the ASK interface of ISO/IEC 18000-3, Mode 3) for conformance.

When through trading-partner agreement, other specific ISO/IEC 18000 air interfaces are employed (i.e. ISO/IEC 18000-2, Type A) the corresponding part of ISO/IEC 18047 shall be used.

#### 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 445, Pallets for materials handling — Vocabulary

ISO 830, Freight containers — Vocabulary

ISO 8601, Data elements and interchange formats — Information interchange — Representation of dates and times

ISO/IEC/IEEE 8802-15-4, Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (WPANs)

ISO/IEC 15418, Information technology — Automatic identification and data capture techniques — GS1 Application Identifiers and ASC MH10 Data Identifiers and maintenance

 $ISO/IEC\ 15434, Information\ technology --- Automatic\ identification\ and\ data\ capture\ techniques\ --- Syntax\ for\ high-capacity\ ADC\ media$ 

#### ISO 17365:2013(E)

ISO/IEC 15459-1, Information technology — Automatic identification and data capture techniques — Unique identification — Part 1: Individual transport units

ISO/IEC 15961, Information technology — Radio frequency identification (RFID) for item management — Data protocol: application interface

ISO/IEC 15962, Information technology — Radio frequency identification (RFID) for item management — Data protocol: data encoding rules and logical memory functions

ISO/IEC 15963, Information technology — Radio frequency identification for item management — Unique identification for RF tags

ISO/IEC 16022, Information technology — Automatic identification and data capture techniques — Data Matrix bar code symbology specification

ISO 17364:2013, Supply chain applications of RFID — Returnable transport items (RTIs) and Returnable packaging items (RPIs)

 $ISO/IEC\ 18000-3, Information\ technology -- Radio\ frequency\ identification\ for\ item\ management -- Part\ 3:$  Parameters for air interface communications at 13,56 MHz

ISO/IEC 18000-63, Information technology — Radio frequency identification for item management — Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

ISO/IEC 18004, Information technology — Automatic identification and data capture techniques — QR Code bar code symbology specification

ISO/IEC 18046 (all parts), *Information technology* — *Radio frequency identification device performance test methods* 

 ${\rm ISO/IEC~18047~(all~parts)},$  Information technology — Radio frequency identification device conformance test methods

ISO/IEC 19762, Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary

ISO 21067, Packaging — Vocabulary

ISO/IEC/IEEE 21451-7, Information technology — Smart transducer interface for sensors and actuators — Part 7: Transducer to radio frequency identification (RFID) systems communication protocols and Transducer Electronic Data Sheet (TEDS) formats

ISO/IEC/TR 24729-1, Information technology — Radio frequency identification for item management — Implementation guidelines — Part 1: RFID-enabled labels and packaging supporting ISO/IEC 18000-6C

ISO/IEC 29160, Information technology — Radio frequency identification for item management — RFID Emblem

ANS MH10.8.2, Data Identifiers and Application Identifiers

GS1 EPC, Tag Data Standard, Version 1.6

**GS1** General Specifications

ICNIRP Guidelines, Guidelines for limiting exposure to time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz)

IEEE C95-1, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz