

INTERNATIONAL
STANDARD

ISO/IEC
14760

First edition
1997-12-15

**Information technology — Data interchange
on 90 mm overwritable and read only
optical disk cartridges using phase
change — Capacity: 1,3 Gbytes per
cartridge**

*Technologies de l'information — Échange de données sur cartouches de
disque optique de recouvrement et de lecture seule, de 90 mm de
diamètre, utilisant un changement de phase — Capacité: 1,3 Gbytes par
cartouche*



Reference number
ISO/IEC 14760:1997(E)

Contents	Page
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical disk cartridge (ODC)	1
2.2 Generating system	1
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative reference	2
4 Definitions	2
5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Names	4
6 List of acronyms	4
7 General description of the optical disk cartridge	4
8 General requirements	5
8.1 Environments	5
8.1.1 Test environment	5
8.1.2 Operating environment	5
8.1.3 Storage environment	5
8.1.4 Transportation	5
8.2 Temperature shock	5
8.3 Safety requirements	6
8.4 Flammability	6
9 Reference Drive	6
9.1 Optical system	6
9.2 Optical beam	7
9.3 Read Channel	8
9.4 Focusing and tracking	8
9.5 Rotation of the disk	8

© ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office * Case Postale 56 * CH-1211 Genève 20 * Switzerland
Printed in Switzerland

Section 2 - Mechanical and physical characteristics	8
10 Dimensional and physical characteristics of the case	8
10.1 General description of the case	8
10.2 Reference planes of the case	8
10.3 Dimensions of the case	8
10.3.1 Overall dimensions	8
10.3.2 Location hole	9
10.3.3 Alignment hole	9
10.3.4 Reference surfaces	10
10.3.5 Detents	10
10.3.6 Functional Areas	11
10.3.7 Media sensor holes	11
10.3.8 Spindle and head windows	12
10.3.9 Insertion slots	13
10.3.10 Shutter	13
10.3.11 Gripper slots	14
10.3.12 Label area	14
10.4 Mechanical characteristics	15
10.4.1 Material	15
10.4.2 Mass	15
10.4.3 Edge distortion	15
10.4.4 Compliance	15
10.4.5 Shutter opening force	15
11 Dimensional, mechanical and physical characteristics of the disk	15
11.1 General description of the disk	15
11.2 Reference axis and plane of the disk	15
11.3 Dimensions of the disk	15
11.3.1 Hub dimensions	16
11.3.2 Clamping zone	16
11.4 Mechanical characteristics	16
11.4.1 Material	17
11.4.2 Mass	17
11.4.3 Moment of inertia	17
11.4.4 Imbalance	17
11.4.5 Axial deflection	17
11.4.6 Axial acceleration	17
11.4.7 Radial runout	17
11.4.8 Radial acceleration	17
11.4.9 Tilt	18
11.5 Optical characteristics	18
11.5.1 Index of refraction	18
11.5.2 Thickness of the substrate	18
11.5.3 Birefringence	18
11.5.4 Reflectance	18
12 Interface between cartridge and drive	18
12.1 Clamping method	18
12.2 Clamping force	19
12.3 Capture cylinder	19
12.4 Disk position in operating condition	19

Section 3 - Format of information	33
13 Geometry of physical tracks	33
13.1 Physical track shape	33
13.2 Direction of track spiral	33
13.3 Physical track pitch	33
14 Track format	33
14.1 Track number	33
14.2 Track layout	33
14.3 Clock frequencies and periods	33
14.4 Radial alignment	35
14.5 Sector number	35
15 Sector format	35
15.1 Sector layout	35
15.2 VFO ₁ and VFO ₂ fields	37
15.3 Address Mark (AM)	37
15.4 ID fields	37
15.5 PA ₁ field	38
15.6 Gap	38
15.7 VFO ₃ field	38
15.8 Sync	38
15.9 Data field	38
15.9.1 User data bytes	39
15.9.2 CRC and ECC bytes	39
15.9.3 Resync bytes	39
15.9.4 PA ₂ field	39
15.10 Buffer field	39
16 Recording code	39
17 Format of the Information Zone	41
17.1 General description of the Information Zone	41
17.2 Division of the Information Zone	41
17.2.1 Mirror Zone	43
17.2.2 Acquire Zone	43
17.2.3 Test Zones	43
17.2.4 Control Zones	44
17.2.5 Data Zone	44
17.2.6 Buffer Zone	44
18 Format of the Data Zone	44
18.1 Buffer tracks in the Data Zone	45
18.2 Defect Management Areas (DMAs)	45
18.3 Disk Definition Structure (DDS)	46
18.3.1 Fully overwritable disks	49
18.3.2 Fully embossed disks	49
18.3.3 Partially embossed disks	49
18.4 Partitioning	49
18.4.1 Fully overwritable disks	49
18.4.2 Partially embossed disks	49
18.4.3 Fully embossed disks	50

19 Defect management	57
19.1 Overwritable groups: Spare sectors	57
19.1.1 Initialization of the disk	57
19.1.2 Certification	57
19.1.3 Disks not certified	58
19.1.4 Write procedure	58
19.1.5 Primary Defect List (PDL)	58
19.1.6 Secondary Defect List (SDL)	59
19.2 Embossed groups: Parity sectors	60
Section 4 - Characteristics of embossed information	61
20 Method of testing	61
20.1 Environment	61
20.2 Use of the Reference Drive	61
20.2.1 Optics and mechanics	61
20.2.2 Read power	61
20.2.3 Read channels	61
20.2.4 Tracking	61
20.3 Definition of signals	61
21 Signals from grooves	63
21.1 Push-pull signal	63
21.2 Divided push-pull signal	63
21.3 Phase depth	64
21.4 Track location	64
21.5 On-track signal	64
22 Signals from Headers	64
22.1 VFO1 and VFO2	64
22.2 Address Mark, ID field and Postamble	65
23 Signals from embossed Recording fields	65
Section 5 - Characteristics of the recording layer	65
24 Method of testing	65
24.1 Environment	65
24.2 Reference Drive	65
24.2.1 Optics and mechanics	65
24.2.2 Read power	66
24.2.3 Read channel	66
24.2.4 Tracking	66
24.3 Overwrite conditions	66
24.3.1 Overwrite pulse	66
24.3.2 Overwrite power and pulse width	66
24.4 Definition of signals	67
25 Overwrite characteristics	67
25.1 Resolution	67
25.2 Narrow-band signal-to-noise ratio	68
25.3 Cross-talk	69

26 Erase characteristics	69
Section 6 - Characteristics of user data	70
27 Method of testing	70
27.1 Environment	70
27.2 Reference Drive	70
27.2.1 Optics and mechanics	70
27.2.2 Read power	70
27.2.3 Read amplifiers	70
27.2.4 Analog-to-binary converters	70
27.2.5 Error correction	70
27.2.6 Focusing and tracking	70
28 Minimum quality of a sector	70
28.1 Headers	70
28.1.1 ID fields	70
28.2 User-written data	71
28.3 Embossed data	71
29 Data interchange requirements	71
29.1 Tracking	71
29.2 User-written data	71
29.3 Embossed data	71
29.4 Quality of the disk	71
Annex A - Edge distortion test	72
Annex B - Compliance test	73
Annex C - CRC for ID fields	76
Annex D - Contents of the Control Zones	77
Annex E - Format of the Data field of a sector	83
Annex F - Test method for measuring the adsorbent force of the hub	89
Annex G - Air cleanliness class 100 000	91
Annex H - Position of the cartridge relative to the reference planes	92
Annex J - Relaxation by zones of the requirements for signals	93
Annex K - Track deviation measurement	94
Annex L - Derivation of the operating climatic environment	98
Annex M - Guidelines for sector replacement	103
Annex N - Definition of one-beam overwrite	104
Annex P - Transportation	105
Annex Q - Office environment	106
Annex R - Values to be implemented in existing and future standards	107
Annex S - Measurement of birefringence	108

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 14760 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Optical disk cartridges for information interchange*.

Annexes A to J form an integral part of this International Standard. Annexes K to S are for information only.

Introduction

The International Standards for optical disk cartridges issued up to now by ISO/IEC JTC 1 are based on a technology known as *magneto-optical (MO)*, this International Standard is the first based on a different technology known as *phase change (PC)*.

Information technology - Data interchange on 90 mm overwritable and read only optical disk cartridges using phase change - Capacity: 1,3 Gbytes per cartridge

Section 1 - General

1 Scope

This International Standard specifies the characteristics of 90 mm Optical Disk Cartridges (ODCs) using the phase change technology, with a capacity of 1,3 Gbytes per cartridge. It specifies three related Types of such cartridges.

Type R/W Provides for data to be written or overwritten and read many times over the recording surface of the disk using the phase change overwritable effect.

Type P-ROM Provides for a part of the recording surfaces of the disk to be embossed by stamping or other means. This part of the disk is read without recourse to the phase change overwritable effect. All parts which are not embossed provide for data to meet the requirements of Type R/W.

Type O-ROM Provides for the whole of the recording surfaces of the disk to be embossed and reproduced by stamping or other means. This type of disk is read without recourse to the phase change overwritable effect.

For each Type, this International Standard provides for 512-byte and 2 048-byte sectors. All sectors of a given cartridge have the same size.

Type R/W, Type P-ROM and Type O-ROM are also referred to as "fully overwritable", "partially embossed" and "fully embossed", respectively.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated, stored and transported;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written; including the physical disposition of the tracks and sectors, the error correction codes, and the modulation method used;
- the characteristics of the embossed information on the disk;
- the phase change overwritable characteristics of the disk, enabling processing systems to overwrite data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical disk cartridge (ODC)

A claim of conformance with this International Standard shall specify the Type implemented. An ODC shall be in conformance with this International Standard if it meets all mandatory requirements specified herein for that Type.

2.2 Generating system

A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system generating an ODC for interchange shall be in conformance with this International Standard if it meets the mandatory requirements of this International Standard for the Type(s) specified.

2.3 Receiving system

A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system receiving an ODC for interchange shall be in conformance to this International Standard if it is able to process any recording made on the cartridge in accordance with the Type(s) specified.

2.4 Compatibility statement

A claim of conformance by a generating or receiving system with this International Standard shall include a statement listing other International Standards supported, if any. This statement shall specify the number of the standard(s), the ODC type(s) supported (where appropriate) and whether support includes reading only or both reading and overwriting.

3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subjected to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 950:1991, *Safety of information technology equipment*.