

International Standard

ISO/IEC 23090-31

Information technology — Coded representation of immersive media —

Part 31: **Haptics coding**

Technologies de l'information — Représentation codée de média immersifs —

Partie 31: Codage haptique

First edition 2025-01



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Contents						
Fore	eword		v			
Intr	oductio	on	vi			
1	Scop	oe	1			
2	-	native references				
3	Terms, definitions and abbreviated terms					
3	3.1	Terms and definitions				
	3.2	Abbreviated terms				
	3.3	Mnemonics				
4	Overview and architecture					
•	4.1	4				
	4.2	Codec architecture	4			
5	Data model					
	5.1	Data structure overview				
	5.2	Haptic experience				
	5.3	Haptic avatar				
	5.4	Haptic perception				
	5.5	Haptic device				
	5.6	Haptic channel				
		5.6.2 Custom mesh avatar				
		5.6.3 Body part mask				
		5.6.4 Semantic body part and actuator mapping				
	5.7	Haptic band				
	5.8	Haptic effect				
	5.9	Haptic keyframe				
6		rchange file format				
	6.1	Overview				
	6.2	HJIF Specifications				
		6.2.1 MPEG_haptics				
		6.2.3 MPEG_haptics.perception				
		6.2.4 MPEG_haptics.sync				
		6.2.5 MPEG_haptics.reference_device				
		6.2.6 MPEG_haptics.channel				
		6.2.7 MPEG_haptics.vector				
		6.2.8 MPEG_haptics.band				
		6.2.9 MPEG_haptics.effect				
_		· · · · · ·				
7		G-I haptic stream (MIHS) format				
	7.1	Overview7.1.1 General				
		7.1.2 Initialization units				
		7.1.3 Temporal and spatial units				
		7.1.4 MIHS packets				
	7.2	Syntax and semantics				
		7.2.1 mpegiHapticStream()				
		7.2.2 mpegiHapticUnit()				
		7.2.3 mpegiHapticPacket()				
		7.2.5 readMetadataInitializationTiming()				
		7.2.6 readMetadataTiming()				
		7.2.7 readMetadataExperience()				

		7.2.8	readAvatar()			
		7.2.9	readMetadataPerception()	48		
		7.2.10	readReferenceDevice()	50		
			readMetadataChannel()			
			readMetadataBand()			
			readLibrary()			
		7.2.14	readLibraryEffect()			
		7.2.15				
			readEffect()			
			readEffectBasis()			
		7.2.18	readKeyframe()			
		7.2.19	5 6			
			readCurveKeyframe()			
			readVectorialKeyFrame()			
			readWaveletEffect()			
			readCRC()			
	7.3		ription of MIHSPacketType			
		7.3.1	InitializationTiming			
		7.3.2	Timing			
		7.3.3	MetadataHaptics			
		7.3.4	MetadataPerception			
		7.3.5	MetadataChannel			
		7.3.6	MetadataBand			
		7.3.7	LibraryEffect			
		7.3.8	Data			
		7.3.9	CRC16 and CRC32			
	7.4	7.3.10				
	7.4		cation examples			
		7.4.1	Initialization units			
		7.4.2	Temporal and spatial units			
		7.4.3 7.4.4	Silent units CRC packets			
	7.5		om access support with MIHS (informative)			
_						
8			model			
	8.1		view			
	8.2		der (informative)			
		0	Encoder architecture			
		8.2.2	OHM metadata input file			
		8.2.3	Descriptive input files			
		8.2.4	PCM input file			
		8.2.5	Transcoding descriptive content			
		8.2.6	Frequency band decomposition			
		8.2.7	Keyframe extraction for low frequencies processing			
	0.2	8.2.8	Wavelet encoding			
	8.3		der			
		8.3.1 8.3.2	Decoder ArchitectureMetadata and parametric data decoding			
		8.3.3	Wavelet Decoding			
		8.3.4	Random access decode			
	8.4		nesizer (informative)			
_		-				
	•		e) JSON schema reference			
	•		ive) OHM metadata input file format			
	•		ve) Semantic body part and actuator mapping e) Profiles and Levels			
Bibliography						
ומום	iogi api	шу		112		

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iso.org/directives<

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and https://patents.iec.ch. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

A list of all parts in the ISO/IEC 23090 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iso.org/members.html and www.iso.org/members.html and

Introduction

Haptics provide an additional layer of entertainment and sensory immersion to the user. Therefore, the user experience and enjoyment of media content, from a ISOBMFF files, broadcast channel, streaming games or mobile advertisements can be significantly enhanced by the judicious addition of haptics to the audio/video content. To that end, haptics has been proposed as a first-order media type, akin to audio and video, in ISOBMFF. Further, haptics has also been proposed as an addition to ISO/IEC 23009-1 (MPEG-DASH) to signal the presence of haptics in MP4 segments to DASH streaming clients. Lastly, the ISO/IEC 23090 (MPEG-I) use cases have been augmented with haptics

Haptics digital encoding is the storing of tactile data in a digital format. As with audio and video, digital encoding is of fundamental importance to allow digital haptic devices to function. Haptics encoding gained relevance with the increased market importance of wideband haptics in consumer peripherals such as smartphones with haptic engines and game consoles with haptic enabled controllers. The prior generation of haptics peripherals was based on less expressive haptic actuators usually based on state machine control processes.

In the field of haptics, the signal encoding usually takes one of two approaches:

- Quantized: This representation is generally made from measured data. The samples from the original phenomenon are stored at a specific acquisition frequency inside the file to represent this signal. One example of a quantized haptic signal is proposed through WAV files, originally developed for audio. WAV file formalism allows the capture of real-world data and the representation of complex wideband haptic feedback. This type of haptics encoding has the disadvantage of being difficult to modify once encoded due to the inability to access the primitives used to create the signal.
- Descriptive: This representation is used to encode haptic signals as a combination of functions to be synthesized. Examples of such vectorized formats include AHAP and IVS. These formats have the advantage of being created with a composition of primitives. They are easily modifiable at runtime by an application and by dedicated editing tools. Currently, these solutions support only vibrotactile perception, but can easily be extended for other forms of haptics such as kinaesthetic, temperature and textures. They also tend to be memory inefficient with increasing signal complexity and cannot encode non-periodic phenomena

This document describes the coded representation allowing to encode both descriptive and quantized data in a human readable JSON format (.hjif) used as an exchange format. This format can be compressed and packetized into a binary file format for distribution and streaming purposes (.hmpg).

Information technology — Coded representation of immersive media —

Part 31:

Haptics coding

1 Scope

This document specifies technology that supports the efficient transmission and rendering of haptic signals for the playback of immersive experiences in a wide variety of scenarios. The document describes in detail a robust coded representation of haptic media covering the two most popular haptic perceptions leveraged by devices today: vibrotactile and kinaesthetic. Support for other haptic modalities has also been integrated.

The coded representation allows to encode both descriptive and quantized data in a human readable JSON format used for exchange purposes, and a compressed bitstream version, optimised for memory usage and distribution purposes. This approach also allows to meet the expectations for compatibility with both descriptive and quantized formats, as required by the market, as well as interoperability between devices for 3D immersive experiences, mobile applications and other distribution purposes.

Information provided in this document related to the decoder is normative, while information related to the encoder and renderer is informative.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601-1, Date and time — Representations for information interchange — Part 1: Basic rules

ISO 8601-2, Date and time — Representations for information interchange — Part 2: Extensions

ISO/IEC 21778:2017, Information technology — The JSON data interchange syntax

IETF RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*, available at: https://www.rfc-editor.org/info/rfc3986

IETF RFC 8259, *The JavaScript Object Notation (JSON) Data Interchange Format*, available at: https://www.rfc-editor.org/info/rfc8259

IETF RFC 4648, *The Base16, Base32, and Base64 Data Encodings*, available at: https://www.rfc-editor.org/info/rfc4648