INTERNATIONAL STANDARD

ISO/IEC 30193

Third edition 2020-03

Corrected version 2020-07

Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk

Technologies de l'information — Supports enregistrés numériquement pour échange et stockage d'information — Disques BD réinscriptibles de 120 mm triple couche (100,0 Go par disque)





COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents			Page
Fore	word		ix
Intro	oductio	n	X
1	Scone	<u>a</u>	1
2	-	native references	
3	_	s and definitions	
4	Symb	ools and abbreviated terms	6
5		ormance	
	5.1	Optical disk	
	5.2 5.3	Generating system	
	5.3 5.4	Receiving systemCompatibility statement	
6	Conv 6.1	entions and notations	
	6.2	Representation of numbers	
	6.3	Integer calculus	
7		ral description of disk	
		•	
8		ral requirements	
	8.1	Environments	
		8.1.2 Operating environment	
		8.1.3 Storage environment	
		8.1.4 Transportation	
	8.2	Safety requirements	
	8.3	Flammability	16
9	Reference drive		16
	9.1	General	
	9.2	Measurement conditions	
	9.3	Optical system	
	9.4 9.5	Optical beam HF read channel	
	9.6	Radial PP read channel	
	9.7	Disk clamping	
	9.8	Rotation of disk and measurement velocity	19
	9.9	Normalized servo transfer function	19
	9.10	Measurement velocities and reference servos for axial tracking	
		9.10.1 General 9.10.2 Reference servo for axial tracking for 1x measurement velocity	
		9.10.3 reference servo for axial tracking for 2x measurement velocity	
	9.11	Measurement velocities and reference servos for radial tracking	
		9.11.1 General	
		9.11.2 Reference servo for radial tracking for 1x measurement velocity	
		9.11.3 Reference servo for radial tracking for 2x measurement velocity	25
10	Dime	nsional characteristics	26
	10.1	General	
	10.2	Disk reference planes and reference axis	
	10.3	Overall dimensions	
	10.4 10.5	First transition area	
	10.5	Clamping zone	
	10.0	Second transition area	20

	10.8	information area	
		10.8.1 General	29
	10.9	10.8.2 Subdivision of information zone on TL disk	
11		anical characteristics	
	11.1	Mass	
	11.1	Moment of inertia	
	11.2	Dynamic imbalance	
	11.3	Axial runout	
	11.4	11.4.1 General	
		11.4.2 Residual axial tracking error for 1x measurement velocity	32
	11 5	11.4.3 Residual axial tracking error for 2x measurement velocity	32
	11.5	Radial runout	
		11.5.1 General	
		11.5.2 Residual radial tracking error for 1x measurement velocity	33
	44.6	11.5.3 Residual radial tracking error for 2x measurement velocity	33
	11.6	Durability of cover layer	33
		11.6.1 Impact resistance of cover layer	
		11.6.2 Scratch resistance of cover layer	
		11.6.3 Repulsion of fingerprints by cover layer	34
12	Ontic	al characteristics in information area	34
14	12.1	General	
	12.1	Refractive index of transmission stacks (TS)	34 3 <i>1</i> 1
	12.3	Thickness of transmission stacks (TS)	
	12.3	Example of target thickness of spacer layers for TL disks	
	12.4	Reflectivity of recording layers	
	12.5	Birefringence	
		Angular deviation	
	12.7		
13	Data format		
	13.1	General	38
	13.2	Data frame	41
	13.3	Error-detection code (EDC)	41
	13.4	Scrambled data frame	42
	13.5	Data block	43
	13.6	LDC block	43
	13.7	LDC code-words	44
	13.8	LDC cluster	
		13.8.1 General	
		13.8.2 First interleaving step	
		13.8.3 Second interleaving step	
	13.9	Addressing and control data	
	10.7	13.9.1 General	
		13.9.2 Address units	
		13.9.3 User-control data	
		13.9.4 Byte/Bit assignment for user-control data	
	12 10	Access block	
		BIS block	
		BIS code-words	
		BIS cluster	
		ECC cluster	
		Recording frames	
		Physical cluster	
	13.17	17PP modulation for recordable data	
		13.17.1 General	
		13.17.2 Bit conversion rules	
		13.17.3 dc-control procedure	
		13.17.4 Frame sync	63

	13.18	Modulation and NRZI conversion	65
14	Physi	cal data allocating and linking	65
	14.1	General	
	14.2	Recording-unit block (RUB)	
		14.2.1 General	
		14.2.2 Data run-in	
		14.2.3 Data run-out	
		14.2.4 Guard_3 field	
	14.3	Locating data relative to wobble addresses	
	2 1.0	14.3.1 General	
		14.3.2 Start-position shift (SPS)	
15	Track	x format	
15	15.1	General	
	15.2	Track shape	
	15.3	Track path	
	15.4	Track pitch	
	15.1	15.4.1 Track pitch in BCA zone	
		15.4.2 Track pitch in embossed HFM areas	
		15.4.3 Track pitch in rewritable areas	
		15.4.4 Track pitch in rewritable areas	72
	15.5	Track layout of HFM grooves	
	13.3	15.5.1 General	
		15.5.2 Data format	
		O Company of the comp	
	156	15.5.4 Recording frames	
	15.6	Track layout of wobbled grooves	
		15.6.1 General	
		15.6.2 Modulation of wobbles	
	157	15.6.3 Wobble polarity	
	15.7	ADIP information	
		15.7.1 General	
		15.7.2 ADIP-unit types	82
		15.7.3 ADIP word structure	
		15.7.4 ADIP data structure	
	4	15.7.5 ADIP error correction	
	15.8	Disk information in ADIP aux frame	
		15.8.1 General	
		15.8.2 Error protection for disk information aux frames	
		15.8.3 Disk-Information data structure	91
16	Gene	ral description of information zone	140
	16.1	General	
	16.2	Format of information zone	141
17	Lavoi	ıt of rewritable area of information zone	141
18	-	zone	
10	18.1	General	
	18.2	Permanent information and control data (PIC) zone	
		18.2.1 General	
		18.2.2 Content of PIC zone	
	100	18.2.3 Emergency brake	
	18.3	Rewritable area of inner zone(s)	
		18.3.1 Protection-zone 2	
		18.3.2 Buffer	
		18.3.3 INFO 2/Reserved 8	
		18.3.4 INFO 2/Reserved 7	
		18.3.5 INFO 2/Reserved 6	
		18.3.6 INFO 2/Reserved 5	153

		18.3.7 INFO 2/PAC 2	153
		18.3.8 INFO 2/Reserved	153
		18.3.9 INFO 2/DMA 2	
		18.3.10 INFO 2/Control data 2	
		18.3.11 INFO 2/Buffer 2	
		18.3.12 OPC/Test zone	
		18.3.13 Reserved	
		18.3.15 INFO 1/Drive area (optional)	
		18.3.16 INFO 1/Reserved 3	
		18.3.17 INFO 1/Reserved 2	
		18.3.18 INFO 1/Reserved 1	
		18.3.19 INFO 1/DMA 1	
		18.3.20 INFO 1/Control Data 1	155
		18.3.21 INFO 1/PAC 1	
		18.3.22 INFO 1/Reserved	155
19	Data z	one	156
20	20.1	zone(s)	
	20.1	INFO 3/Buffer 3	
	20.2	INFO 3/DMA 3	
	20.3	INFO 3/Control data 3	
	20.5	Angular buffer	
	20.6	INFO 4/DMA 4	
	20.7	INFO 4/Control data 4	
	20.8	INFO 4/Buffer 4	
	20.9	DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone	
	20.10	Protection-zone 3	157
21	Physic	cal-access control clusters	157
	21.1	General	
	21.2	Layout of PAC zones	
	21.3	General structure of PAC clusters	
	21.4	Primary PAC cluster (mandatory)	
	21.5	Disk write-protect PAC cluster (optional)	
	21.6	IS1 and IS2 PAC clusters	
22		nanagement	
	22.1	General	
	22.2	Disk-management structure (DMS)	
		22.2.1 General	
		22.2.2 Disk-definition structure (DDS)	
		22.2.3 Defect list (DFL)	
23	Assign	nment of logical-sector numbers (LSNs)	182
24	Chara	cteristics of grooved areas	183
25	Metho	od of testing for grooved area	183
_0	25.1	General	
	25.2	Environment	
	25.3	Reference drive	
		25.3.1 General	
		25.3.2 Read power	
		25.3.3 Read channels	
		25.3.4 Tracking requirements	
	0= :	25.3.5 Scanning velocities	
	25.4	Definition of signals	184
26	Signal	s from HFM grooves	185

	26.1	Push-pull polarity	185
	26.2	Push-pull signal	
	26.3	Wobble signal	186
	26.4	Jitter of HFM signal	186
27	Signa	ıls from wobbled grooves	
	27.1	Phase depth	
	27.2	Push-pull signal	
	27.3	Wobble signal	
		27.3.1 General	
		27.3.2 Measurement of NWS	
		27.3.3 Measurement of the wobble CNR	
20	CI.		
28		acteristics of recording layer	
29		od of testing for recording layer	
	29.1	General	
	29.2	Environment	
	29.3	Reference drive	
		29.3.1 General	
		29.3.2 Read power 29.3.3 Read channels	
		29.3.4 Tracking requirements	
		29.3.5 Scanning velocities	
	29.4	Write conditions	
	27.1	29.4.1 Write-pulse waveform	
		29.4.2 Write powers	
		29.4.3 Average power	
		29.4.4 Write conditions for i-MLSE measurement	
		29.4.5 Write conditions for cross-erase measurements	
	29.5	Definition of signals	
30	Signals from recorded areas		190
	30.1	HF signals	190
	30.2	Modulated amplitude	
	30.3	Reflectivity-modulation product	
	30.4	Asymmetry	
	30.5	i-MLSE@DOW(n)	
	30.6	Cross-erase @ DOW(n) _{XE}	
	30.7	Read stability	
31		defects	
32	Chara	acteristics of user data	194
33		od of testing for user data	
	33.1	General	
	33.2	Environment	
	33.3	Reference drive	
		33.3.1 General	
		33.3.2 Read power	
		33.3.3 Read channels	
		33.3.4 Error correction	
		33.3.5 Tracking requirements 33.3.6 Scanning velocities	
	33.4	Definition of signals	
34		num quality of recorded information	
<i>J</i> 1	34.1	General	
	34.2	Random symbol error rate	
	34 3	Maximum hurst errors	196

34.4 User-written data	196
35 Burst-cutting area (BCA)	196
Annex A (normative) Thickness of transmission stacks in case of multiple layers	198
Annex B (normative) Measurement of reflectivity	201
Annex C (normative) Measurement of scratch resistance of cover layer	207
Annex D (normative) Measurement of repulsion of grime by cover layer	209
Annex E (normative) Measurement of wobble amplitude	212
Annex F (normative) Write-pulse waveform for testing	217
Annex G (normative) Optimum power control (OPC) procedure for disk	224
Annex H (normative) HF signal pre-processing for integrated-maximum likelihood sequence error estimation (i-MLSE) measurements	227
Annex I (normative) Measurement procedures	239
Annex J (informative) Measurement of birefringence	251
Annex K (informative) Measurement of thickness of cover layer and spacer layer	254
Annex L (informative) Measurement of impact resistance of cover layer	257
Annex M (informative) Groove deviation and wobble amplitude	259
Annex N (informative) Guidelines for write pulse adjustment using L-SEAT edge-shift	261
Bibliography	270

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document is in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, information *Technology*, Subcommittee SC 23, *Digitally recorded media for information interchange and storage*.

This third edition cancels and replaces the second edition (ISO/IEC 30193:2016), which has been technically revised. It also incorporates the Amendment ISO 30193:2016/DAM1.

The main changes compared to the previous edition are as follows:

- additional requirements for 4x reading velocity have been added;
- additional requirements for physical access control and reserved area of BD application have been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This corrected version of ISO 30193:2020 incorporates the following corrections:

- minor editorial corrections in symbols (italicization, bolding);
- in <u>15.8.3.2</u>, reinstatement of "These two bytes shall be set to 44 49h, representing the characters "DI"." in Bytes 0 to 1 and deletion from Byte 3.

Introduction

In March 2002, nine companies known as the Blu-ray Disc Founders, or BDF, came together to create optical-disk formats with large capacity and high-speed transfer rates that would be needed for recording and reproducing high-definition video content. This joint effort turned out to be fruitful and the first version of its Blu-ray Disc™ Rewritable Format Part 1 version 1.0 in June 2002.

Then, in October 2004, more than 100 companies joined and BDF became an open forum called the Bluray Disc Association (BDA). The BDA issued version 2.1 of the Bluray Disc™ Rewritable Format Part 1 in October 2005 and version 3.0 in June 2010. By the end of 2010, over a hundred million Bluray Disc™ had been shipped and Bluray™ devices such as players, recorders, game consoles and PC drives were in use all over the world.

The BDA also conducts verification activities for both disks and devices and has established more than 10 testing centers in Asia, Europe and the USA.

The BDA gave consumer applications the highest priority in the first few years. But it was known, of course, that international standardization would be required before many government entities and their contractors would be allowed to use Blu-ray Disc™. In January and February 2011, the chairs of ISO/IEC JTC 1/SC 23 and JIIMA (Japan Image and information Management Association) formally requested the BDA to consider international standardization. The reason for this was to enable the inclusion of writable BDs along with DVDs and CDs in an International Standard specifying the test methods for the estimation of lifetime of optical storage media for long-term data storage. In October 2011, the President of the BDA responded that his organization had decided to pursue international standardization for the basic physical formats for the recordable and rewritable Blu-ray™ Formats.

In December 2011, the BDA sent project proposals for international standardization of four formats to ISO/IEC JTC 1/SC 23 via the Japanese national body. They are 120 mm single layer (25,0 Gbytes per disk) and dual layer (50,0 Gbytes per disk) BD recordable disks, 120 mm single layer (25,0 Gbytes per disk) and dual layer (50,0 Gbytes per disk) BD rewritable disks, 120 mm triple layer (100,0 Gbytes per disk) and quadruple layer (128,0 Gbytes per disk) BD recordable disks and 120 mm triple layer (100,0 Gbytes per disk) BD rewritable disk.

This document specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 100,0 Gbytes.

A few additional specifications are required in order to write and read video-recording applications, such as BDAV format which had been specified by the BDA for use on BD rewritable disks. These specifications, which are related to the BD application, the file system or the content-protection system, are required for the disk, the generating system and the receiving system. For more information about the BD application, the content-protection system and the additional requirements for the Blu-ray $^{\text{TM}}$ Format specifications, see http://www.blu-raydisc.info.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO and IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO and IEC. information may be obtained from the patent database available at www.iso.org/patents.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Blu-ray™, Blu-ray Disc™ and the logos are trademarks of the Blu-ray Disc Association.

Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk

1 Scope

This document specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 100,0 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. User data can be written, read and overwritten many times using a reversible method. This disk is identified as a BD rewritable disk.

This document specifies the following:

- the one disk type;
- the conditions for conformance;
- the environments in which the disk is to be operated and stored;
- the mechanical and physical characteristics of the disk, so as to provide mechanical interchange between data processing systems;
- the format of the information on the disk, including the physical disposition of the tracks and sectors;
- the error-correcting codes and the coding method used;
- the characteristics of the signals recorded on the disk, enabling data processing systems to read data from the disk.

This document provides for interchange of disks between disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9352, Plastics — Determination of resistance to wear by abrasive wheels

ISO/IEC 646, Information technology — ISO 7-bit coded character set for information interchange

IEC 60068-2-2, Environmental testing — Part 2-2: Tests — Test B: Dry heat

IEC 60068-2-30, Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle)

IEC 60950-1, Information technology equipment — Safety — Part 1: General requirements