



**International
Standard**

**ISO/IEC/IEEE
8802-15-4**

**Information technology —
Telecommunications and
information exchange between
systems — Local and metropolitan
area networks — Specific
requirements —**

**Part 15-4:
Wireless medium access control
(MAC) and physical layer (PHY)
specifications for low-rate wireless
personal area networks (WPANs)**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains
— Exigences spécifiques —*

*Partie 15-4: Spécifications du contrôle d'accès du milieu sans fil
(MAC) et de la couche physique (PHY) pour les réseaux personnels
sans fil de faible débit (WPAN)*



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

IEEE Std 802.15.4™-2020
(Revision of IEEE Std 802.15.4-2015)

IEEE Standard for Low-Rate Wireless Networks

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved on 6 May 2020

IEEE SA Standards Board

Abstract: The physical layer (PHY) and medium access control (MAC) sublayer specifications for low-data-rate wireless connectivity with fixed, portable, and moving devices with no battery or very limited battery consumption requirements are defined in this standard. In addition, the standard provides modes that allow for precision ranging. PHYs are defined for devices operating in a variety of geographic regions.

Keywords: ad hoc network, IEEE 802.15.4™, low data rate, low power, LR-WPAN, mobility, PAN, personal area network, radio frequency, RF, short range, wireless, wireless network, wireless personal area network, WPAN

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 23 July 2020. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-6689-9 STD24181
Print: ISBN 978-1-5044-6690-5 STDPD24181

IEEE Prohibits discrimination, harassment, and bullying.
For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <https://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. A current IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE SA Website at <https://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <https://standards.ieee.org>.

Errata

Errata, if any, for IEEE standards can be accessed via <https://standards.ieee.org/standard/index.html>. Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore: <https://ieeexplore.ieee.org/browse/standards/collection/ieee/>. Users are encouraged to periodically check for errata.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was sent to ballot, the IEEE P802.15 Working Group had the following voting members:

Robert F. Heile, Chair

Rick Alvin, Co-Vice Chair

Patrick W. Kinney, Co-Vice Chair

James P. K. Gilb, Working Group Technical Editor

Patrick W. Kinney, Secretary

Gary Stuebing, 802.15.4md Task Group Chair

Don Sturek, 802.15.4md Task Group Vice Chair

Kunal P. Shah, 802.15.4md Technical Editor

Hendrik Ahlendorf	Christopher Hett	Michael McInnis
Koorosh Akhavan	Jay Holcomb	Apurva Mody
Bernd Baer	Oliver Holland	Ayman Naguib
David Barras	Iwao Hosako	Jaroslaw Niewczas
Tuncer Baykas	Brima Ibrahim	Paul Nikolicz
Philip Beecher	Tetsushi Ikegami	Philip Orlik
Friedbert Berens	Yeong Min Jang	Aditya Padaki
Lennert Bober	Seongah Jeong	Glenn Parsons
Monique Brown	Seong-Soo Joo	Charles Perkins
Chris Calvert	Volker Jungnickel	Albert Petrick
Radhakrishna Canchi	Paul Kettle	Joe Pollard
Jaesang Cha	Shoichi Kitazawa	Clinton Powell
Matthew Chang	Tero Kivinen	Demir Rakanovic
Soo-Young Chang	Daniel Knobloch	Ivan Reede
Clint Chaplin	Ryuji Kohno	Joerg Robert
Sangsung Choi	Fumihide Kojima	Benjamin Rolfe
Boris Danev	Ann Krieger	Ren Sakata
Luc Darmon	Thomas Kuerner	Ruben E. Salazar Cardozo
Hendricus De Ruijter	Jack Lee	Ioannis Sarris
Brandon Dewberry	Mingyu Lee	Peter Sauer
Anthony Fagan	Frank Leong	Nikola Serafimovski
Matthew Gillmore	Huan-Bang Li	Tushar Shah
Tim Godfrey	Zheda Li	Stephen Shellhammer
Jianlin Guo	Sang-Kyu Lim	Karthik Srinivasagopalan
Joachim Hammerschmidt	Thomas Lorbach	Billy Verso
Shinsuke Hara	Masood Maqbool	Johannes Wechsler
Hiroshi Harada	Vinayagam Mariappan	Brian Weis
Timothy Harrington	Alejandro Marquez	Peter Yee
Chris Hartman		Shaun Yu

Major contributions in the revision process were received from the following individuals:

Harry Bims
Hendricus De Ruijter
Chris Hett
Roger Hislop
Klaus Hueske
Shoichi Kitazawa

Tero Kivinen
Clint Powell
R. K. Rannow
George Robert
Benjamin Rolfe
Ruben E. Salazar Cardozo

Kunal P. Shah
Gary Stuebing
Don Sturek
Billy Verso
Lisa Ward
Hidetoshi Yokota

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Werner Hoelzl	Benjamin Rolfe
David Barras	Brima Ibrahim	Ruben E Salazar Cardozo
Philip E. Beecher	Raj Jain	Shigenobu Sasaki
Harry Bims	SangKwon Jeong	Naotaka Sato
Nancy Bravin	Srinivas Kandala	Peter Sauer
Vern Brethour	S. G. Karthik	James Schuessler
Demetrio Bucaneg, Jr	Stuart Kerry	Kunal Shah
William Byrd	Yongbum Kim	Tushar Shah
Paul Cardinal	Patrick Kinney	Robert Stacey
Juan Carreon	Tero Kivinen	Dorothy Stanley
Pin Chang	Jarkko Kneckt	Thomas Starai
Clint Chaplin	Daniel Knobloch	Gary Stuebing
Charles Cook	Jan Kruys	Don Sturek
Boris Danev	Yasushi Kudoh	Mark Sturza
Hendricus De Ruijter	Hyeong Ho Lee	Bo Sun
Brandon Dewberry	Mingyu Lee	Mark-Rene Uchida
Igor Dotlic	Wookbong Lee	Aditya V. Padaki
Edward Eckert	Frank Leong	Dmitri Varsanofiev
Anthony Fagan	Zheda Li	Billy Verso
Michael Fischer	Yong Liu	George Vlantis
Avraham Freedman	Thomas Lorbach	Lisa Ward
James Gilb	Michael McLaughlin	Karl Weber
Matthew Gillmore	Michael McInnis	Scott Willy
Robert Golshan	Ayman Naguib	Andreas Wolf
Randall Groves	Nick S.A. Nikjoo	Chi Xu
Rainer Hach	Tetsu Nishimura	Shang-Te Yang
Joachim Hammerschmidt	Bansi Patel	Kangjin Yoon
Timothy Harrington	Dev Paul	Yu Yuan
Robert Heile	Arumugam Paventhan	Oren Yuen
Jerome Henry	Clinton Powell	Sven Zeisberg
Marco Hernandez	Maximilian Riegel	
	Robert Robinson	

When the IEEE SA Standards Board approved this standard on 6 May 2020, it had the following membership:

Gary Hoffman, Chair
Jon Walter Rosdahl, Vice Chair
Jean-Philippe Faure, Past Chair
Konstantinos Karachalios, Secretary

Ted Burse	David J. Law	Mehmet Ulema
J. Travis Griffith	Howard Li	Lei Wang
Grace Gu	Dong Liu	Sha Wei
Guido R. Hertz	Kevin Lu	Philip B. Winston
Joseph L. Koepfinger*	Paul Nikolich	Daidi Zhong
John D. Kulick	Damir Novosel	Jingyi Zhou
	Dorothy Stanley	

*Member Emeritus

Historical participants

Many individuals have participated in the IEEE P802.15 Working Group during various stages of the standard's development. Since the initial publication, many amendments have added functionality or updated material in this standard, and now three revisions have been published. Here is a historical list of the working group participants who dedicated their valuable time, energy, and knowledge to the advancement of this standard at the time of its original publication and for its revisions. Many of these members also worked on amendments.

The following members of the IEEE P802.15 Working Group participated in the development of the original standard, IEEE Std 802.15.4-2003:

Robert F. Heile, *Chair*

James D. Allen, *Vice Chair*

Patrick W. Kinney, *Secretary*

Michael D. McInnis, *Assistant Secretary and Editor*

Ian C. Gifford, *Task Group 1 Chair*

Stephen J. Shellhammer, *Task Group 2 Chair*

John R. Barr, *Task Group 3 Chair*

Patrick W. Kinney, *Task Group 4 Chair*

Phil Jamieson, *Task Group 4 Vice Chair*

José A. Gutierrez, *Task Group 4 Editor-in-Chief*

Marco Naeve, *Task Group 4 Secretary*

Monique Bourgeois, *MAC Technical Editor*

Said Moridi, *PHY Technical Editor*

Phil Jamieson, *Layer Management Technical Editor*

Greg Breen, *Low-Band PHY Technical Editing*

Ed Callaway, *Networking Technical Editing*

Paul Gorday, *High-Band PHY Technical Editing*

Marco Naeve, *General Description Technical Editing*

David Cypher, *PICs/SDLs Technical Editing*

Robert D. Poor, *Coexistence Technical Editing*

Farron Dacus, *Regulatory Technical Editing*

Roberto Aiello

Masaaki Akahane

Richard Alfvin

Arun Arunachalam

Nael Askar

Venkat I. Bahl

Daniel Bailey

Jay Bain

James Baker

Jaiganesh Balakrishnan

Anuj Batra

Timothy Blaney

Kenneth Boehike

Stan Bottoms

Mark V. Bowles

Chuck Brabenac

Soo-Young Chang

Francois Po_Shin Chin

Aik Chindapol

Craig Conkling

Anand Dabak

Kai Dombrowski

Mary DuVal

Michael Dydyk

Jason L. Ellis

Mark W. Fidler

Jeff R. Foerster

David S. Furuno

Pierre Gandolfo

Atul Garg

James Gilb

Nada Golmie

Yasuo Harada

Allen Heberling

Barry Herold

Robert Y. Huang

Eran Igler

Katsumi Ishii

Jeyhan Karaoguz

Masami Katagiri

Joy H. Kelly

Stuart J. Kerry

Yongsuk Kim

Young Hwan Kim

Günter Kleindl

Bruce P. Kraemer

DoHoon Kwon

Jim Lansford

David Leeper

Liang Li

Yeong-Chang Maa

Steven March

Ralph Mason

Jim Meyer

Leonard E. Miller

Akira Miura

Andreas Molisch

Antonio Mondragon	Chandos Rypinski	Teik-Kheong Tan
Tony Morelli	John H. Santhoff	Larry Taylor
Chiu Ngo	Mark Schrader	Stephen E. Taylor
Kei Obara	Tom Schuster	Hans vanLeeuwen
Knut Odman	Erik Schylander	Ritesh Vishwakarma
John B. Pardee	Michael Seals	Thierry Walrant
Jongun Park	Nick Shepherd	Jing Wang
Dave Patton	Gadi Shor	Fijio Watanabe
Marcus Pendergrass	William Shvodian	Mathew Welborn
Gregg Rasor	Thomas Siep	Richard Wilson
Ivan Reede	Kazimierz Siwiak	Stephen Wood
Jim Richards	Carl Stevenson	Edward G. Woodrow
Glyn Roberts	Rene Struik	Hirohisa Yamaguchi
Richard Roberts	Shigeru Sugaya	Amos Young
William Roberts	Kazuhisaka Takamura	Song-Lin Young
Chris Rogers	Katsumi Takaoka	Nakache Yves-paul
Philippe Rouzet		Jim Zyren

Major contributions were received from the following individuals:

Tony Adamson	Ed Hogervorst	Niels Schutten
David Archer	Stephen Korfhage	Nick Shepherd
David Avery	Charles Luebke	Ari Singer
Venkat Bahl	Masahiro Maeda	Ralph D'Souza
Daniel Bailey	Ian Marsden	Carl Stevenson
Edul Batliwala	Chris Marshall	Mark Tilinghast
Pratik Bose	Paul Marshall	Hans Van Leeuwen
Boaz Carmeli	Fred Martin	Jacco van Muiswinkel
Farron Dacus	Ralph Mason	Luis Pereira
Martin Digon	Rod Miller	Richard Wilson
Ian C. Gifford	Phil Rudland	Wim Zwart

The following members of the IEEE P802.15 Working Group participated in the development of the first revision, IEEE Std 802.15.4-2006:

Robert F. Heile, Chair
James D. Allen, Vice Chair
Patrick W. Kinney, Assistant Vice Chair
James P. K. Gilb, Editor-in-Chief
Patrick W. Kinney, Secretary
Michael D. McInnis, Assistant Secretary and Editor
John R. Barr, Task Group 3b Chair
Reed Fisher, Task Group 3c Chair
Patrick W. Kinney, Task Group 4a Chair
Myung Lee, Task Group 5 Chair
Robert D. Poor, Task Group 4b Chair
Marco Naeve, Task Group 4b Vice Chair
Monique B. Brown, Task Group 4b Editor-in-Chief
Eric T. Gnoske, Task Group 4b Secretary
Philip E. Beecher, MAC Contributing Editor
Monique B. Brown, MAC Technical Editor
Edgar H. Callaway, Jr., MAC Contributing Editor
Francois Chin, PHY Contributing Editor
Robert C. Cragie, MAC/Security Contributing Editor
Paul Gorday, PHY Contributing Editor

James P. K. Gilb, *Draft D3 Editor-in-Chief*
Øyvind Janbu, *MAC/PHY/Security Contributing Editor*
Marco Naeve, *General Description/PICS Editor, MAC Contributing Editor*
Clinton C. Powell, *PHY Technical Editor*
Joseph Reddy, *Security Contributing Editor*
Zachary Smith, *MAC Contributing Editor*
René Struik, *Security Contributing Editor*
Andreas C. Wolf, *PHY Contributing Editor*

Roberto Aiello	Tian-Wei Huang	Philip Orlik
Richard Alfvin	Hideto Ikeda	Laurent Ouvry
Mikio Aoki	Tetsushi Ikegami	John Pardee
Takashi Arita	Adrian Jennings	Nirmalendu Patra
Larry Arnett	Ho-In Jeon	Dave Patton
Arthur Astrin	Tzyy Hong Jiang	Xiaoming Peng
Yasaman Bahreini	David Julian	Tony Pollock
Jay Bain	Jeyhan Karaoguz	Vidyasagar Premkumar
Alan Berkema	Michael Kelly	Yihong Qi
Bruce Bosco	Stuart Kerry	Raad Raad
Mark Bowles	Jae-Hyon Kim	Pekka Ranta
Charles Brabenac	Jaeyoung Kim	Dani Raphaeli
David Brenner	Jinkyeong Kim	Gregg Rasor
Vern Brethour	Yongsuk Kim	Charles Razzell
Ronald Brown	Kursat Kimyacioglu	Ivan Reede
Bill Carney	Matthias Kindler	Yuko Rikuta
Kuoer-Hsin Chang	Guenter Kleindl	Terry Robar
Jonathon Cheah	Ryuji Kohno	Glyn Roberts
Kwan-Wu Chin	Mike Krell	Richard Roberts
Sarm-Goo Cho	Yasushi Kudo	Benjamin A. Rolfe
Sungsoo Choi	Akiomi Kunisa	Philippe Rouzet
Yun Choi	Yuzo Kuramochi	Chandos Rypinski
Chun-Ting Chou	Jiun-You Lai	Ali Sadri
Manoj Choudhary	Ismail Lakkis	Saeid Safavi
Celestino Corral	John Lampe	Zafer Sahinoglu
Joe Decuir	Kyung Kuk Lee	Tomoki Saito
Javier Del Prado Pavon	Wooyong Lee	Syed Saleem
Kai Dombrowski	David Leeper	Kamran Sayrafian
Stefan Drude	Huan-Bang Li	Jean Schwoerer
Amal Ekbal	Haixiang Liang	Erik Schylander
Jason Ellis	Ian Macnamara	Alireza Seyedi
Shahriar Emami	Akira Maeki	Sanjeev Sharma
Paul Everest	Patricia Martigne	Siddharth Shetty
Mark W. Fidler	Abbie Mathew	John Shi
Kris Fleming	Taisuke Matsumoto	Shusaku Shimada
Amir Freund	Gustaf Max	Yuichi Shiraki
Camillo Gentile	Michael McLaughlin	Gadi Shor
Ian Gifford	Charlie Mellone	William Shvodian
Sung-Wook Goh	Klaus Meyer	Thomas Siep
Sorin Goldenberg	Samuel Mo	Michael Sim
Vivek Gupta	Andreas Molisch	Kazimierz Siwiak
Rainer Hach	Mark Moore	V. Somayazulu
Robert Hall	Ken Naganuma	Amjad Soomro
Shinsuke Hara	Yves-Paul Nakache	Carl Stevenson
Jeff Harris	Hiroyuki Nakase	Kazuaki Takahashi
Allen Heberling	Saishankar Nandagopalan	Kenichi Takizawa
Eric Heinze	Chiu Ngo	Teik-Kheong Tan
Barry Herold	Erwin Noble	Mike Tanahashi
Keisuke Higuchi	John O'Conor	Yasushi Tanaka
Jin-Meng Ho	Knut Odman	James Taylor
Patrick Houghton	Hiroyo Ogawa	Arnaud Tonnerre
Robert Huang	Yasuyuki Okuma	Ichihiko Toyoda

Jerry Upton
 Bart Van Poucke
 Chris Weber
 Matthew Welborn
 Magnus Wiklund

Gerald Wineinger
 Patrick Worfolk
 Tracy Wright
 Hirohisa Yamaguchi
 Kamya Yekeh Yazdandoost

Su-Khiong Yong
 Zhan Yu
 Serdar Yurdakul
 Mahmoud Zadeh
 Bin Zhen

Major contributions in the revision process were received from the following individuals:

Jon Adams
 Helmut P. Adamski
 Jonathan Avey
 Jon Beniston
 Bernd Grohmann
 José A. Gutierrez
 Jesper Holm
 ZhiJian Hu
 Phil A. Jamieson
 Yuen-Sam Kwok

Colin Lanzl
 Myung Lee
 Zhongding Lei
 Liang Li
 Yong Liu
 Frederick Martin
 Frank Poegel
 Matthias Scheide
 D. C. Seward

Huai-Rong Shao
 Mark Shea
 Stephen J. Shellhammer
 Mark A. Tillinghast
 Johannes Van Leeuwen
 Richard Wilson
 Ping Xiong
 Bing Xu
 ChenYang Yang
 Chunhui Zhu

The following members of the IEEE P802.15 Working Group participated in the development of the second revision, IEEE Std 802.15.4-2011:

Robert F. Heile, Chair
Rick Alvin, Co-Vice Chair
Patrick W. Kinney, Co-Vice Chair
James P. K. Gilb, Working Group Technical Editor
Patrick W. Kinney, Secretary

James P. K. Gilb, Task Group 4i Chair and Technical Editor

Emad Afifi
 Gahng-Seop Ahn
 Roberto Aiello
 Arthur Astrin
 Taehan Bae
 Michael Bahr
 John Barr
 Anuj Batra
 Tuncer Baykas
 Philip E. Beecher
 Ashutosh Bhatia
 Ghulam Bhatti
 Gary Birk
 Mathew Boytim
 Peter David Bradley
 Nancy Bravin
 David Britz
 Monique B. Brown
 Sverre Brubk
 Brian Buchanan
 John Buffington
 Kiran Bynam
 Brent Cain
 Edgar H. Callaway
 Chris Calvert

Ruben E. Salazar Cardozo
 Douglas Castor
 Jaesang Cha
 Russell Chandler
 Kuor-Hsin Chang
 Soo-Young Chang
 Clint Chaplin
 Hind Chebbo
 Chang-Soon Choi
 Sangsung Choi
 Ciaran Connell
 David Cypher
 Matthew Dahl
 David Davenport
 Mark Dawkins
 Hendricus de Ruijter
 Upkar Dhaliwal
 Gang Ding
 Paul Dixon
 Guido Dolmans
 Igor Dotlic
 Michael Dow
 Dietmar Eggert
 David Evans
 Charles Farlow

John Farserotu
 Jeffrey Fischbeck
 Mike Fischer
 George Flammer
 Ryosuke Fujiwara
 Noriyasu Fukatsu
 Kiyoshi Fukui
 John Geiger
 Gregory Gillooly
 Tim Godfrey
 Paul Gorday
 Elad Gottlib
 Robert Hall
 Shinsuke Hara
 Hiroshi Harada
 Timothy Harrington
 Rodney Hemminger
 Marco Hernandez
 Garth Hillman
 Jin-Meng Ho
 Wei Hong
 Srinath Hosur
 David Howard
 Jung-Hwan Hwang
 Taeho Hwang

Ichirou Ida	Robert Moskowitz	Steve Shearer
Tetsushi Ikegami	Hamilton Moy	Stephen Shellhammer
Akio Iso	Peter Murray	Shusaku Shimada
Yeong Min Jang	Theodore Myers	Chang Sub Shin
Adrian Jennings	Chiu Ngo	Cheol Ho Shin
Wuncheol Jeong	Paul Nikolich	Michael Sim
Steven Jillings	Hirohito Nishiyama	Jonathan Simon
Noh-Gyoung Kang	David Olson	Jaeseung Son
Tae-Gyu Kang	Okundu Omeni	Paul Stadnik
Shuzo Kato	Ryoji Ono	René Struik
Tatsuya Kato	Laurent Ouvry	Chin-Sean Sum
Jeritt Kent	James Pace	Hui-Hsia Sung
Prithpal Khakuria	Hyung-Il Park	Gu Sungi
Dae Ho Kim	Jahng Park	Kenichi Takizawa
Dong-Sun Kim	Seung-Hoon Park	Hirokazu Tanaka
Dukhyun Kim	Taejoon Park	Larry Taylor
Jaehwan Kim	Ranjeet Patro	Mark Thompson
Jeffrey King	Al Petrick	James Tomcik
Ryuji Kohno	Dalibor Pokrajac	Ichihiko Toyoda
Fumihide Kojima	Daniel Popa	David Tracey
Bruce Kraemer	Stephen Pope	Khanh Tran
Raymond Krasinski	Clinton C. Powell	Jerry Upton
Masahiro Kuroda	Richard Powell	Jana van Greunen
John Lampe	Chang-Woo Pyo	Hartman van Wyk
Zhou Lan	Mohammad Rahaman	Michel Veillette
Khanh Le	Sridhar Rajagopal	Billy Verso
Cheolhyo Lee	Jayaram Ramasastry	Bhupender Virk
Hyungsoo Lee	Marc Reed	Joachim Walewski
Myung Lee	Ivan Reede	Junyi Wang
Daniel Lewis	Richard Roberts	Quan Wang
Huan-Bang Li	Craig Rodine	Xiang Wang
Liang Li	June Chul Roh	Andy Ward
Sang-Kyu Lim	Benjamin A. Rolfe	Scott Weikel
Jeremy Link	Seung-Moon Ryu	Nicholas West
Mike Lynch	Didier Sagan	Mark Wilbur
Robert Mason	Kentaro Sakamoto	Ludwig Winkel
Tomokuni Matsumura	Will San Filippo	Eun Tae Won
Jeff McCullough	H. Sanderford	Alan Chi Wai Wong
Michael McGillan	Kamran Sayrafian	Tao Xing
Michael D. McInnis	Timothy Schmidl	Wen-Bin Yang
Michael McLaughlin	Michael Schmidt	Yang Yang
Charles Millet	Jean Schwoerer	Kazuyuki Yasukawa
Siamak Mirnezami	Cristina Seibert	Kamy Yazdandoost
Rishi Mohindra	Neal Seidl	Kaoru Yokoo
Emmanuel Monnerie	Kunal Shah	Mu Zhao
Rajendra Moorti		Bin Zhen

Major contributions in the revision process were received from the following individuals:

Philip E. Beecher
Vern Brethour
Monique B. Brown
Edgar H. Callaway
Kuor-Hsin Chang

Clint Chaplin
James P. K. Gilb
Patrick W. Kinney
Michael D. McInnis

Clinton C. Powell
Benjamin A. Rolfe
Timothy Schmidl
René Struik
Billy Verso

The following members of the IEEE P802.15 Working Group participated in the development of the second revision, IEEE Std 802.15.4-2015:

Robert F. Heile, Chair

Rick Alfin, Co-Vice Chair

Patrick W. Kinney, Co-Vice Chair

James P. K. Gilb, Working Group Technical Editor

Patrick W. Kinney, Secretary

Patrick W. Kinney, 802.15 Maintenance Committee Chair

Benjamin A. Rolfe, 802.15 Maintenance Committee Vice Chair

James P. K. Gilb, Technical Editor

Mounir Achir
Keiji Akiyama
Arthur Astrin
Philip Beecher
Frederik Beer
Chandrashekhar P. S. Bhat
Kiran Bynam
Edgar Callaway
Chris Calvert
Radhakrishna Canchi
Kapseok Chang
Soo-Young Chang
Clint Chaplin
Stephen Chasko
Paul Chilton
Sangsun Choi
Hendricus de Ruijter
Guido Dolmans
Igor Dotlic
Stefan Drude
Dietmar Eggert
Shahriar Emami
Andrew Estrada
David Evans
George Flammer
Kiyoshi Fukui
Matthew Gillmore
Tim Godfrey
Elad Gottlib
Jussi Haapola
Rainer Hach

Shinsuke Hara
Timothy Harrington
James Hartman
Marco Hernandez
Ken Hiraga
Iwao Hosako
Yeong Min Jang
Seong-Soon Joo
Akifumi Kasamatsu
Shuzo Kato
Tooyuki Kato
Jeritt Kent
Jaehwan Kim
Youngsoo Kim
Shoichi Kitazawa
Tero Kivinen
Ryuji Kohno
Fumihide Kojima
Thomas Kuerner
Byung-Jae Kwak
Jae Seung Lee
Myung Lee
Sangjae Lee
Huan-Bang Li
Liang Li
Qing Li
Michael Lynch
Itaru Maekawa
Hiroyuki Matsumura
Michael McLaughlin
Michael McInnis
Kenichi Mori

Robert Moskowitz
Jinesh P. Nair
Chiu Ngo
Paul Nikolich
John Notor
Hiroyo Ogawa
Taejoon Park
Glenn Parsons
Charles Perkins
Albert Petrick
Clinton C. Powell
Verotiana Rabariaona
Ivan Reede
Richard Roberts
Ruben E. Salazar Cardozo
Noriyuki Sato
Norihiko Sekine
Kunal Shah
Stephen Shellhammer
Shusaku Shimada
Gary Stuebing
Don Sturek
Mineo Takai
Kou Togashi
Billy Verso
Gabriel Villardi
Brian Weis
Makoto Yaita
Peter Yee
Yu Zeng
Chunhui (Allan) Zhu

Major contributions in the revision process were received from the following individuals:

Philip Beecher
Monique Brown
Edgar Callaway
Soo-Young Chang
James P. K. Gilb
Tim Godfrey
Jussi Haapola
Timothy Harrington

Jeritt Kent
Patrick W. Kinney
Tero Kivinen
Amarjeet Kumar
Michael McInnis
Robert Moskowitz
Clinton C. Powell
Verotiana Rabariaona

Benjamin A. Rolfe
Ruben E. Salazar Cardozo
Cristina Seibert
Kunal Shal
Shusakh Shimada
Chin-Sean Sum
Larry Taylor
Billy Verso

Introduction

This introduction is not part of IEEE Std 802.15.4-2020, IEEE Standard for Low-Rate Wireless Networks.

This is the fourth revision of IEEE Std 802.15.4. From the beginning, the goal of the IEEE P802.15 Working Group was to produce a standard that enabled very low-cost, low-power communications. The initial standard, IEEE Std 802.15.4-2003, defined two optional physical layers (PHYS), operating in different frequency bands with a simple and effective medium access control (MAC).

In 2006, the standard was revised and added two more PHY options. The MAC remained backward compatible, but the revision added MAC frames with an increased version number and a variety of MAC enhancements, including the following:

- Support for a shared time base with a data timestamping mechanism
- Support for beacon scheduling
- Synchronization of broadcast messages in beacon-enabled personal area networks (PANs)
- Improved MAC layer security

In 2011, the standard was revised to include the three amendments approved subsequent to the 2006 revision. This effort added four more PHY options along with the MAC capability to support ranging. Additionally, the organization of the standard was changed so that each PHY would have a separate clause, and the MAC clause was split into functional description, interface specification, and security specification.

The 2015 revision of the standard was created to roll in the amendments approved subsequent to the 2011 revision: six PHY amendments and one MAC amendment, with corrigenda and clarifications. The features added by the amendments include the following:

- Enhanced frame formats maintaining backward compatibility
- Information Elements (IEs)
- Channel agility
- Extended superframe options
- Low-energy mechanisms
- An enhanced acknowledgment frame that can carry data and can be secured
- Prioritized channel access
- A variety of new PHY modulation, coding, and band options to support a wide variety of application needs including radio frequency identification (RFID), smart utility networks (SUNs), television white space (TVWS) operation, low-energy critical infrastructure monitoring (LECIM), and rail communications and control (RCC)

Much of the corrigenda and clarifications were collected from requests from individuals after the revision in 2011. Major corrigenda items included changes to the security text to correct errors and clarify the text, removal of the encrypt only mode, addition of security policy checks for the IEs, corrections regarding personal area network identifier (PAN ID) compression behavior to eliminate ambiguous specification, and changes to the IEs subclauses to include more information necessary for users of this standard.

The Project Authorization Request (PAR) for IEEE Std 802.15.4-2015 was first proposed in July 2013 and was approved in October 2013 by IEEE's New Standards Committee (NesCom). After three working group ballots and two IEEE SA Committee ballots, the final standard was approved in December 2015, just over two years from start to finish.

The current revision of the standard was revised to include six approved amendments subsequent to the 2015 revision. This effort added two more PHY amendments and one MAC amendment, with corrigenda and clarifications. The features added by the amendments include the following:

- A variety of new PHY modulation, coding, and band options to support a wide variety of application needs including smart utility networks (SUNs), china medical band (CMB), ternary amplitude shift keying (TASK) and rate switch Gaussian frequency shift keying (RS-GFSK)

Much of the corrigenda and clarifications were collected from requests from individuals after the revision in 2015. Major corrigenda items included changes to the transmission order of the address field.

Contents

1.	Overview.....	33
1.1	Scope.....	33
1.2	Purpose.....	33
2.	Normative references.....	34
3.	Definitions, acronyms, and abbreviations.....	35
3.1	Definitions	35
3.2	Acronyms and abbreviations	36
4.	Format conventions.....	40
4.1	General.....	40
4.2	Fields.....	40
4.3	Numbers.....	41
4.4	Strings	41
4.5	Transmission order	41
4.5.1	General.....	41
4.5.2	Vendor OUI transmission order.....	42
4.6	Reserved fields and values.....	42
5.	General description	43
5.1	Introduction.....	43
5.2	Special application spaces	43
5.2.1	General.....	43
5.2.2	Smart utility network (SUN).....	43
5.2.3	Rail communications and control (RCC).....	43
5.2.4	Television white space (TVWS).....	44
5.2.5	Radio frequency identification (RFID).....	44
5.2.6	Low-energy, critical infrastructure monitoring (LECIM)	44
5.2.7	Medical body area network (MBAN) services	44
5.2.8	China medical band (CMB).....	44
5.3	Components of the IEEE 802.15.4 WPAN.....	45
5.4	Multi-PHY management (MPM) of the SUN WPAN.....	45
5.5	Network topologies	45
5.5.1	General.....	45
5.5.2	Star network formation	46
5.5.3	Peer-to-peer network formation.....	46
5.6	Architecture	47
5.6.1	General.....	47
5.6.2	PHY	48
5.6.3	MAC sublayer.....	49
5.7	Functional overview	49
5.7.1	Superframe structure.....	49
5.7.2	Data transfer model.....	51
5.7.3	Frame structure	52
5.7.4	Information element (IEs).....	52
5.7.5	Access methods.....	52
5.7.6	Power consumption considerations	53

5.7.7	Security	54
5.7.8	Enabling spectrum resource measurement capability.....	55
5.8	Concept of primitives.....	56
6.	MAC functional description	57
6.1	Device types and conventions.....	57
6.2	Channel access.....	57
6.2.1	Superframe structure.....	57
6.2.2	Incoming and outgoing superframe timing.....	59
6.2.3	Enhanced Beacon frame timing for MPM procedure	60
6.2.4	IFS.....	61
6.2.5	Random access methods	62
6.2.6	TSCH slotframe structure	69
6.2.7	LE functional description.....	71
6.2.8	Superframe use for TMCTP operation	71
6.2.9	Rail communications and control network (RCCN) superframe structure.....	72
6.2.10	Channel hopping	73
6.3	Starting and maintaining PANs	75
6.3.1	Scanning through channels	75
6.3.2	PAN ID conflict resolution	81
6.3.3	Starting and realigning a PAN	82
6.3.4	Beacon generation.....	84
6.3.5	Device discovery.....	86
6.3.6	TSCH PAN formation	86
6.4	Association and disassociation	88
6.4.1	Association.....	88
6.4.2	Disassociation	91
6.4.3	Fast association	92
6.5	Synchronization	93
6.5.1	General.....	93
6.5.2	Synchronization with beacons	93
6.5.3	Synchronization without beacons	95
6.5.4	Synchronization in TSCH PAN	95
6.5.5	Orphaned device realignment	98
6.6	Transaction handling.....	98
6.7	Transmission, reception, and acknowledgment	100
6.7.1	Transmission	100
6.7.2	Reception and rejection	101
6.7.3	Extracting pending data from a coordinator	103
6.7.4	Use of acknowledgments and retransmissions	104
6.7.5	Transmission timing restrictions.....	107
6.7.6	Guard time	108
6.7.7	Promiscuous mode.....	109
6.7.8	Transmission scenarios	109
6.7.9	Device announcement.....	111
6.8	GTS allocation and management	111
6.8.1	GTS general requirements	111
6.8.2	CAP maintenance	112
6.8.3	GTS allocation	112
6.8.4	GTS usage.....	113
6.8.5	GTS deallocation	114
6.8.6	GTS reallocation	115
6.8.7	GTS expiration.....	117

6.9	Ranging.....	117
6.9.1	Ranging requirements.....	117
6.9.2	Set-up activities before a ranging exchange	118
6.9.3	Finish-up activities after a ranging exchange	118
6.9.4	Managing DPS	118
6.9.5	The ranging exchange	120
6.10	PHY parameter change notification procedure.....	120
6.10.1	Signaling using Beacon frames.....	120
6.10.2	Signaling using multipurpose frames	121
6.11	Deterministic and synchronous multichannel extension (DSME).....	122
6.11.1	DSME command requirements.....	122
6.11.2	DSME multi-superframe structure.....	122
6.11.3	Channel diversity	124
6.11.4	CAP reduction.....	126
6.11.5	DSME GTS allocation and management.....	127
6.11.6	Beacon scheduling	133
6.11.7	Time synchronization	134
6.11.8	Deferred beacon.....	135
6.11.9	Passive channel scan.....	135
6.12	LE transmission, reception, and acknowledgment	136
6.12.1	LE transmission, reception, and acknowledgment with positive handshakes	136
6.12.2	Coordinated sampled listening (CSL).....	136
6.12.3	RIT	140
6.12.4	Implicit RIT (I-RIT).....	143
6.13	Starting and maintaining TMCTPs	143
6.14	MPM procedure for inter-PHY coexistence	147
6.15	TVWS access procedures	149
6.15.1	General.....	149
6.15.2	Channel timing management (CTM).....	150
6.16	Spectrum Resource Measurement (SRM)	151
6.16.1	General.....	151
6.16.2	SRM Performance Metrics	151
6.16.3	SRM functionality.....	157
6.17	Using Link Margin IE.....	160
7.	MAC frame formats	161
7.1	Device extended address.....	161
7.2	General MAC frame format.....	161
7.2.1	General.....	161
7.2.2	Frame Control field.....	162
7.2.3	Sequence Number field.....	165
7.2.4	Destination PAN ID field	166
7.2.5	Destination Address field.....	166
7.2.6	Source PAN ID field.....	166
7.2.7	Source Address field.....	166
7.2.8	Auxiliary Security Header field.....	166
7.2.9	IE field	166
7.2.10	Frame Payload field	167
7.2.11	FCS field	167
7.3	Format of individual frame types.....	169
7.3.1	Beacon frame format	169
7.3.2	Data frame format.....	173
7.3.3	Ack frame format.....	174

7.3.4	MAC command frame format.....	175
7.3.5	Multipurpose frame format.....	176
7.3.6	Extended frame format	179
7.4	IEs	179
7.4.1	IE list termination	179
7.4.2	Header IEs.....	180
7.4.3	Payload IEs	197
7.4.4	Nested IE.....	198
7.5	MAC commands	237
7.5.1	Command ID field	237
7.5.2	Association Request command	239
7.5.3	Association Response command	240
7.5.4	Disassociation Notification command	241
7.5.5	Data Request command	242
7.5.6	PAN ID Conflict Notification command.....	243
7.5.7	Orphan Notification command	243
7.5.8	Beacon Request command.....	243
7.5.9	Enhanced Beacon Request command	243
7.5.10	Coordinator Realignment command.....	244
7.5.11	GTS request command.....	245
7.5.12	DSME Association Request command.....	246
7.5.13	DSME Association Response command	247
7.5.14	DSME GTS Request command	249
7.5.15	DSME GTS Response command.....	251
7.5.16	DSME GTS Notify command.....	253
7.5.17	DSME Information Request command.....	254
7.5.18	DSME Information Response command	254
7.5.19	DSME Beacon Allocation Notification command	255
7.5.20	DSME Beacon Collision Notification command.....	256
7.5.21	DSME Link Report command	256
7.5.22	RIT Data Request command.....	257
7.5.23	DBS Request command	258
7.5.24	DBS Response command.....	259
7.5.25	RIT Data Response command	260
7.5.26	SRM Request command	260
7.5.27	SRM Response command.....	262
7.5.28	SRM Report command	262
7.5.29	SRM Information command	263
7.5.30	Vendor Specific command.....	264
8.	MAC services	265
8.1	Overview.....	265
8.2	MAC management service.....	265
8.2.1	Primitives supported by the MLME-SAP interface.....	265
8.2.2	Common requirements for MLME primitives.....	267
8.2.3	Association primitives	268
8.2.4	Disassociation primitives.....	275
8.2.5	Communications notification primitives	278
8.2.6	Primitives for reading and writing PIB attributes	285
8.2.7	GTS management primitives	288
8.2.8	Primitives for orphan notification.....	291
8.2.9	Primitives for resetting the MAC sublayer.....	293
8.2.10	Primitives for specifying the receiver enable time	294

8.2.11	Primitives for channel scanning.....	296
8.2.12	Primitives for updating the superframe configuration.....	301
8.2.13	Primitives for synchronizing with a coordinator	305
8.2.14	Primitives for requesting data from a coordinator	308
8.2.15	Primitives for specifying dynamic preamble	310
8.2.16	Primitives for channel sounding	311
8.2.17	Primitives for ranging calibration.....	313
8.2.18	Primitives for Beacon Generation.....	314
8.2.19	Primitives for TSCH	318
8.2.20	Primitives for DSME GTS management	325
8.2.21	Primitives for reporting the link status	332
8.2.22	Operating parameter change primitives	334
8.2.23	TMCTP DBS allocation primitives	338
8.2.24	Primitives for device announcement.....	342
8.2.25	RIT data commands	344
8.2.26	Primitives for SRM.....	350
8.3	MAC data service	365
8.3.1	General.....	365
8.3.2	MCPS-DATA.request.....	365
8.3.3	MCPS-DATA.confirm.....	370
8.3.4	MCPS-DATA.indication	373
8.3.5	MCPS-PURGE.request.....	376
8.3.6	MCPS-PURGE.confirm.....	376
8.4	MAC constants and PIB attributes.....	377
8.4.1	General.....	377
8.4.2	MAC constants	377
8.4.3	MAC PIB attributes	378
9.	Security	400
9.1	Overview.....	400
9.2	Functional description.....	400
9.2.1	General.....	400
9.2.2	Outgoing frame security procedure	400
9.2.3	KeyDescriptor lookup procedure.....	402
9.2.4	Incoming frame security procedure, Security Enabled field is set to one	402
9.2.5	Incoming frame security procedure, Security Enabled field is set to zero	404
9.2.6	DeviceDescriptor lookup procedure	405
9.2.7	SecurityLevelDescriptor lookup procedure	406
9.2.8	Incoming IE security level checking procedure	406
9.2.9	Incoming IE key usage policy checking procedure	407
9.2.10	Incoming security level checking procedure	407
9.2.11	Incoming key usage policy checking procedure.....	407
9.3	Security operations	408
9.3.1	General.....	408
9.3.2	Integer and octet representation.....	408
9.3.3	AEAD nonce	408
9.3.4	AEAD prerequisites	410
9.3.5	AEAD transformation data representation	410
9.3.6	AEAD inverse transformation data representation	411
9.4	Auxiliary security header.....	412
9.4.1	General.....	412
9.4.2	Security Control field.....	412
9.4.3	Frame Counter field	414

9.4.4	Key Identifier field.....	415
9.5	Security-related MAC PIB attributes.....	415
10.	General PHY requirements	421
10.1	General.....	421
10.1.1	Requirements and definitions	421
10.1.2	Operating frequency range.....	422
10.1.3	Channel assignments.....	429
10.1.4	Minimum LIFS and SIFS periods.....	454
10.1.5	RF power measurement	454
10.1.6	Transmit power	454
10.1.7	Out-of-band spurious emission.....	454
10.1.8	Receiver sensitivity definitions.....	454
10.1.9	Common signaling mode (CSM) for SUN PHY	454
10.2	General radio specifications.....	455
10.2.1	General.....	455
10.2.2	TX-to-RX turnaround time	455
10.2.3	RX-to-TX turnaround time	455
10.2.4	Error-vector magnitude (EVM) definition.....	456
10.2.5	Receiver maximum input level of desired signal.....	456
10.2.6	Receiver ED	457
10.2.7	Link quality indicator (LQI)	457
10.2.8	Clear channel assessment (CCA).....	457
11.	PHY services	459
11.1	Overview.....	459
11.2	PHY constants.....	459
11.3	PHY PIB attributes	459
12.	O-QPSK PHY	467
12.1	PPDU format.....	467
12.1.1	General.....	467
12.1.2	SHR field format.....	467
12.1.3	PHR field format.....	467
12.2	Modulation and spreading	468
12.2.1	General.....	468
12.2.2	Data rate.....	468
12.2.3	Reference modulator diagram.....	468
12.2.4	Bit-to-symbol mapping	468
12.2.5	Symbol-to-chip mapping	469
12.2.6	O-QPSK modulation.....	470
12.2.7	Pulse shape.....	470
12.2.8	Chip transmission order	471
12.3	O-QPSK PHY RF requirements	471
12.3.1	Operating frequency range.....	471
12.3.2	Transmit power spectral density (PSD) mask.....	472
12.3.3	Symbol rate	472
12.3.4	Receiver sensitivity	472
12.3.5	Receiver interference rejection	472
12.3.6	TX-to-RX turnaround time	473
12.3.7	RX-to-TX turnaround time	473

12.3.8	EVM.....	473
12.3.9	Transmit center frequency tolerance.....	473
12.3.10	Transmit power	473
12.3.11	Receiver maximum input level of desired signal.....	473
12.3.12	Receiver ED	473
12.3.13	LQI.....	473
13.	Binary phase-shift keying (BPSK) PHY	474
13.1	PPDU format.....	474
13.2	Modulation and spreading	474
13.2.1	General.....	474
13.2.2	BPSK PHY data rates	474
13.2.3	Reference modulator.....	474
13.2.4	Differential encoding.....	474
13.2.5	Bit-to-chip mapping.....	475
13.2.6	BPSK modulation	475
13.3	BPSK PHY RF requirements.....	475
13.3.1	Operating frequency range.....	475
13.3.2	915 MHz band transmit PSD mask.....	475
13.3.3	Symbol rate	476
13.3.4	Receiver sensitivity.....	476
13.3.5	Receiver interference rejection	476
13.3.6	TX-to-RX turnaround time	476
13.3.7	RX-to-TX turnaround time	477
13.3.8	EVM.....	477
13.3.9	Transmit center frequency tolerance.....	477
13.3.10	Transmit power	477
13.3.11	Receiver maximum input level of desired signal.....	477
13.3.12	Receiver ED	477
13.3.13	LQI.....	477
14.	Chirp spread spectrum (CSS) PHY	478
14.1	CSS PPDU format	478
14.1.1	General.....	478
14.1.2	Preamble field	478
14.1.3	SFD field.....	478
14.1.4	PHR field	479
14.1.5	PHY Payload field	479
14.2	Modulation and spreading	479
14.2.1	General.....	479
14.2.2	Data rates	479
14.2.3	Reference modulator.....	479
14.2.4	De-multiplexer (DEMUX).....	479
14.2.5	Serial-to-parallel mapping	479
14.2.6	Data-symbol-to-bi-orthogonal-codeword mapping	480
14.2.7	Parallel-to-serial converter and QPSK symbol mapping.....	484
14.2.8	DQPSK coding	484
14.2.9	DQPSK-to-DQCSK modulation.....	485
14.2.10	CSK generator.....	485
14.2.11	Bit interleaver	485
14.3	Waveform and subchirp sequences.....	486
14.3.1	General.....	486

14.3.2	Graphical presentation of chirp symbols (subchirp sequences).....	486
14.3.3	Active usage of time gaps.....	486
14.3.4	Mathematical representation of the continuous time CSS base-band signal	487
14.3.5	Raised cosine window for chirp pulse shaping.....	489
14.3.6	Subchirp transmission order	489
14.3.7	Example of CSK signal generation.....	490
14.4	CSS RF requirements.....	491
14.4.1	General.....	491
14.4.2	Transmit power spectral density (PSD) mask and signal tolerance.....	491
14.4.3	Symbol rate	491
14.4.4	Receiver sensitivity.....	491
14.4.5	Receiver interference rejection	491
14.4.6	TX-to-RX turnaround time	492
14.4.7	RX-to-TX turnaround time	492
14.4.8	Transmit center frequency tolerance.....	493
14.4.9	Transmit power	493
14.4.10	Receiver maximum input level of desired signal.....	493
14.4.11	Receiver ED	493
14.4.12	LQI.....	493
15.	HRP UWB PHY	494
15.1	General.....	494
15.2	HRP UWB PPDU format	495
15.2.1	General.....	495
15.2.2	PPDU encoding process.....	495
15.2.3	Symbol structure	496
15.2.4	PSDU timing parameters	498
15.2.5	Preamble timing parameters	500
15.2.6	SHR field	502
15.2.7	PHR field	505
15.2.8	PHY Payload field	506
15.3	Modulation	507
15.3.1	Modulation mathematical framework.....	507
15.3.2	Spreading	507
15.3.3	FEC	509
15.4	RF requirements.....	511
15.4.1	Operating frequency bands	511
15.4.2	Channel assignments.....	513
15.4.3	Regulatory compliance	513
15.4.4	Baseband impulse response	513
15.4.5	Transmit PSD mask	514
15.4.6	Chip rate clock and chip carrier alignment	514
15.4.7	TX-to-RX turnaround time	515
15.4.8	RX-to-TX turnaround time	515
15.4.9	Transmit center frequency tolerance.....	515
15.4.10	Receiver maximum input level of desired signal.....	515
15.4.11	Receiver ED	515
15.4.12	LQI	515
15.4.13	CCA	516
15.5	HRP UWB PHY optional pulse shapes	516
15.5.1	Overview	516
15.5.2	HRP UWB PHY optional chirp on UWB (CoU) pulses	516
15.5.3	HRP UWB PHY optional continuous spectrum (CS) pulses	517

15.5.4	HRP UWB PHY linear combination of pulses (LCP).....	519
15.6	Extended preamble for optional CCA mode 6.....	519
15.7	Ranging.....	520
15.7.1	Overview.....	520
15.7.2	Ranging counter.....	520
15.7.3	Crystal characterization	520
15.7.4	Ranging FoM	521
16.	GFSK PHY	523
16.1	PPDU formats	523
16.2	Modulation.....	523
16.2.1	GFSK PHY data rates	523
16.2.2	Reference modulator diagram.....	523
16.2.3	Data whitening.....	523
16.2.4	GFSK modulation	524
16.3	GFSK PHY RF requirements	524
16.3.1	Operating frequency range.....	524
16.3.2	Transmit PSD mask	524
16.3.3	Symbol rate	525
16.3.4	Receiver sensitivity.....	525
16.3.5	Receiver interference rejection	525
16.3.6	TX-to-RX turnaround time	525
16.3.7	RX-to-TX turnaround time	525
16.3.8	Transmit center frequency tolerance.....	525
16.3.9	Transmit power	525
16.3.10	Receiver maximum input level of desired signal.....	525
16.3.11	Receiver ED	526
16.3.12	LQI.....	526
17.	MSK PHY	527
17.1	PPDU formats	527
17.1.1	Overview.....	527
17.1.2	Frame Length LSB field	527
17.1.3	Extended PHR field	527
17.1.4	Frame Length MSB field	527
17.2	Data rate	528
17.3	Multi-PHY functionality.....	528
17.4	SFD for the MSK PHY	528
17.5	MSK modulation.....	529
17.5.1	Reference modulator diagram.....	529
17.5.2	Data whitening	529
17.5.3	Bit-to-symbol mapping	529
17.5.4	Signal modulation	529
17.6	MSK PHY requirements	530
17.6.1	Operating frequency range.....	530
17.6.2	Transmit PSD mask	530
17.6.3	Symbol rate	530
17.6.4	Transmit center frequency tolerance.....	531
17.6.5	Transmit power	531
17.6.6	Receiver maximum input level of desired signal.....	531
17.6.7	Modulation frequency deviation tolerance	531
17.6.8	Zero crossing tolerance	531

18.	LRP UWB PHY specification	532
18.1	Overview.....	532
18.2	LRP UWB PHY symbol structure	532
18.2.1	Overview.....	532
18.2.2	Base mode LRP UWB PHY symbol structure	533
18.2.3	Extended mode LRP UWB PHY symbol structure	533
18.2.4	Long-range mode LRP UWB PHY symbol structure	535
18.3	LRP UWB SHR	535
18.3.1	General.....	535
18.3.2	LRP UWB SHR preamble	536
18.3.3	LRP UWB SHR SFD.....	536
18.4	LRP UWB PHR	536
18.4.1	General.....	536
18.4.2	Encoding Type field.....	537
18.4.3	Header Extension field.....	537
18.4.4	SECDED field.....	538
18.4.5	Frame Length field.....	538
18.4.6	LEIP Length field	538
18.4.7	LEIP Position field.....	538
18.5	LRP UWB PSDU.....	539
18.6	LRP UWB location enhancing information postamble	539
18.7	LRP UWB transmitter specification	539
18.7.1	Pulse shape.....	539
18.7.2	Pulse timing	539
18.7.3	Transmit PSD mask	540
18.8	LRP UWB receiver specification	540
19.	SUN FSK PHY	541
19.1	Introduction.....	541
19.2	PPDU format for SUN FSK.....	542
19.2.1	General.....	542
19.2.2	SHR field format.....	542
19.2.3	General.....	542
19.2.4	PHR field format.....	543
19.2.5	Mode Switch PHR	543
19.2.6	PHY Payload field	545
19.3	Modulation and coding for SUN FSK	546
19.3.1	General.....	546
19.3.2	Reference modulator.....	549
19.3.3	Bit-to-symbol mapping	550
19.3.4	Modulation quality.....	551
19.3.5	FEC	552
19.3.6	Code-symbol interleaving.....	555
19.4	Data whitening for SUN FSK	556
19.5	Mode switch mechanism for SUN FSK	556
19.6	SUN FSK PHY RF requirements	559
19.6.1	Operating frequency range.....	559
19.6.2	Regulatory compliance	559
19.6.3	Radio frequency tolerance	559
19.6.4	Channel switch time.....	560
19.6.5	Transmitter symbol rate	560
19.6.6	Transmit spectral mask	560

19.6.7	Receiver sensitivity.....	561
19.6.8	Receiver interference rejection.....	561
19.6.9	TX-to-RX turnaround time	561
19.6.10	RX-to-TX turnaround time	561
19.6.11	Transmit power	562
19.6.12	Receiver maximum input level of desired signal.....	562
19.6.13	Receiver ED	562
19.6.14	LQI.....	562
20.	SUN OFDM PHY	563
20.1	Introduction.....	563
20.2	PPDU format for SUN OFDM	563
20.2.1	General.....	563
20.2.2	Short Training field (STF)	563
20.2.3	Long Training field (LTf)	567
20.2.4	PHR.....	570
20.2.5	PSDU field.....	572
20.3	Data rates for SUN OFDM	572
20.4	Modulation and coding for SUN OFDM.....	573
20.4.1	Reference modulator diagram.....	573
20.4.2	Bit-to-symbol mapping	573
20.4.3	PIB attribute values for phySymbolsPerOctet.....	574
20.4.4	FEC	574
20.4.5	Interleaver	575
20.4.6	Frequency spreading	577
20.4.7	Pilot tones/null tones.....	578
20.4.8	Cyclic prefix (CP).....	581
20.4.9	PPDU Tail field	581
20.4.10	Pad field	581
20.4.11	Scrambler and scrambler seeds.....	582
20.5	SUN OFDM PHY RF requirements	583
20.5.1	Operating frequency range.....	583
20.5.2	Transmit power spectral density (PSD) mask.....	583
20.5.3	Receiver sensitivity.....	583
20.5.4	Adjacent channel rejection.....	584
20.5.5	Alternate channel rejection	584
20.5.6	TX-to-RX turnaround time	585
20.5.7	RX-to-TX turnaround time	585
20.5.8	EVM definition	585
20.5.9	Transmit center frequency and symbol tolerance	586
20.5.10	Transmit power	586
20.5.11	Receiver maximum input level of desired signal.....	586
20.5.12	Receiver ED	586
20.5.13	LQI.....	586
21.	SUN O-QPSK PHY	587
21.1	Introduction.....	587
21.2	PPDU format for SUN O-QPSK	587
21.2.1	General.....	587
21.2.2	SHR field format.....	587
21.2.3	PHR field format.....	588
21.2.4	PHY Payload field	589

21.3 Modulation and coding for SUN O-QPSK	589
21.3.1 Reference modulator.....	589
21.3.2 SHR coding and spreading	590
21.3.3 PHR coding and spreading	591
21.3.4 PSDU coding and spreading for DSSS.....	592
21.3.5 PSDU coding and spreading for MDSSS	596
21.3.6 FEC	598
21.3.7 Code-bit interleaving	600
21.3.8 Bit differential encoding (BDE)	601
21.3.9 DSSS bit-to-chip mapping.....	602
21.3.10 MDSSS bit-to-chip mapping	606
21.3.11 Chip whitening.....	609
21.3.12 Pilot insertion.....	611
21.3.13 Modulation parameters for O-QPSK	613
21.4 Support of legacy devices of the 780 MHz, 915 MHz, and 2450 MHz O-QPSK PHYs	614
21.5 SUN O-QPSK PHY RF requirements	614
21.5.1 Operating frequency range.....	614
21.5.2 Transmit power spectral density (PSD) mask.....	615
21.5.3 Receiver sensitivity.....	615
21.5.4 Adjacent channel rejection.....	617
21.5.5 TX-to-RX turnaround time	619
21.5.6 RX-to-TX turnaround time	619
21.5.7 EVM definition	619
21.5.8 Transmit center frequency and symbol tolerance	619
21.5.9 Transmit power	619
21.5.10 Receiver maximum input level of desired signal.....	619
21.5.11 Receiver ED	619
21.5.12 LQI.....	619
21.5.13 CCA	619
22. LECIM DSSS PHYs	621
22.1 PPDU format for DSSS	621
22.2 Modulation and spreading	621
22.2.1 General.....	621
22.2.2 Data rate.....	621
22.2.3 Reference modulator diagram.....	622
22.2.4 Convolutional FEC encoding.....	622
22.2.5 Interleaver	623
22.2.6 Differential encoding	624
22.2.7 Bit-to-symbol and symbol-to-chip encoding	625
22.2.8 BPSK/O-QPSK modulation.....	627
22.3 PSDU fragmentation.....	629
22.3.1 General.....	629
22.3.2 Configuration	630
22.3.3 Fragmentation	630
22.3.4 Fragment packet.....	630
22.3.5 Calculating FICS field using MIC	631
22.3.6 Fragment acknowledgment and retransmission.....	631
22.3.7 Frak	632
22.3.8 Reassembly	634
22.4 DSSS PHY RF requirements	634
22.4.1 Radio frequency tolerance	634
22.4.2 Channel switch time.....	634

22.4.3	Transmit spectral mask	634
22.4.4	Receiver sensitivity.....	634
22.4.5	Receiver interference rejection	634
22.4.6	TX-to-RX turnaround time	635
22.4.7	RX-to-TX turnaround time	635
22.4.8	Transmit power	635
23.	LECIM FSK PHY specification	636
23.1	General.....	636
23.2	PPDU format for LECIM FSK PHY	636
23.2.1	General.....	636
23.2.2	SHR field format.....	636
23.2.3	PHR field format.....	637
23.2.4	PHY Payload field	637
23.3	Modulation and coding for LECIM FSK PHY	637
23.3.1	General.....	637
23.3.2	Reference modulator.....	638
23.3.3	Bit-to-symbol mapping.....	638
23.3.4	Modulation quality.....	638
23.3.5	FEC	639
23.3.6	Code-bit interleaving	640
23.3.7	Spreading	641
23.4	Data whitening for LECIM FSK PHY	642
23.5	LECIM FSK PHY RF requirements.....	643
23.5.1	Operating frequency range.....	643
23.5.2	Radio frequency tolerance	643
23.5.3	Channel switch time.....	643
23.5.4	Transmit spectral mask	643
23.5.5	Receiver sensitivity.....	643
23.5.6	TX-to-RX turnaround time	644
23.5.7	RX-to-TX turnaround time	644
23.5.8	Transmit power	644
24.	TVWS-FSK PHY	645
24.1	PPDU format for TVWS-FSK	645
24.1.1	General.....	645
24.1.2	SHR field format.....	645
24.1.3	PHR field format.....	646
24.1.4	PHY Payload field	646
24.2	Modulation and coding for TVWS-FSK	646
24.2.1	General.....	646
24.2.2	Reference modulator.....	646
24.2.3	FEC and interleaving	647
24.2.4	Data whitening	648
24.2.5	Spreading	648
24.2.6	Bit-to-symbol mapping	648
24.2.7	Modulation quality.....	648
24.2.8	Values for phySymbolsPerOctet.....	648
24.3	TVWS-FSK RF requirements.....	649
24.3.1	Operating frequency range.....	649
24.3.2	Clock frequency and timing accuracy	649
24.3.3	Channel switch time.....	649

24.3.4	Receiver sensitivity.....	649
24.3.5	TX-to-RX turnaround time	649
24.3.6	RX-to-TX turnaround time	649
24.3.7	Receiver maximum input level of desired signal.....	649
24.3.8	Receiver ED	649
24.3.9	LQI.....	649
25.	TVWS-OFDM PHY	650
25.1	General.....	650
25.2	PPDU format for TVWS-OFDM.....	650
25.2.1	General.....	650
25.2.2	STF.....	650
25.2.3	LTF	652
25.2.4	PHR field format.....	654
25.2.5	PSDU field.....	654
25.3	System parameters for TVWS-OFDM	654
25.4	Modulation and coding for TVWS-OFDM	655
25.4.1	Reference modulator.....	655
25.4.2	Bit-to-symbol mapping	655
25.4.3	FEC	656
25.4.4	Interleaver	657
25.4.5	Pilot tones/null tones.....	659
25.4.6	CP.....	660
25.4.7	PPDU Tail field	660
25.4.8	Pad field	660
25.4.9	Scrambler and scrambler seeds.....	660
25.5	TVWS-OFDM RF requirements	660
25.5.1	Operating frequency range.....	660
25.5.2	Pulse shaping	661
25.5.3	Transmit power spectral density (PSD) mask.....	661
25.5.4	Receiver sensitivity.....	661
25.5.5	TX-to-RX turnaround time	661
25.5.6	RX-to-TX turnaround time	661
25.5.7	EVM definition	661
25.5.8	Transmit center frequency and symbol tolerance	662
26.	TVWS-NB-OFDM PHY	663
26.1	PPDU format for TVWS-NB-OFDM.....	663
26.1.1	General.....	663
26.1.2	Short Training field (STF)	663
26.1.3	Long training field (LTF)	667
26.1.4	PHR.....	671
26.1.5	PHY Payload field	672
26.2	System parameters for TVWS-NB-OFDM	672
26.3	Modulation and coding parameters for TVWS-NB-OFDM.....	673
26.3.1	General.....	673
26.3.2	Reference modulator.....	673
26.3.3	Scrambler and scrambler seed	673
26.3.4	Outer encoding.....	673
26.3.5	Inner encoding	674
26.3.6	Pad bit insertion	677
26.3.7	Spreader	677

26.3.8	Bit interleaving	678
26.3.9	Subcarrier mapping.....	678
26.3.10	Frequency interleaving	680
26.3.11	Pilot tones	681
26.3.12	Cyclic prefix	681
26.3.13	Pulse shaping	681
26.3.14	PIB attribute values for phySymbolsPerOctet.....	682
26.4	Channel aggregation for TVWS-NB-OFDM	682
26.5	TVWS-NB-OFDM RF requirements.....	682
26.5.1	Operating frequency range.....	682
26.5.2	Receiver sensitivity.....	682
26.5.3	TX-to-RX turnaround time	683
26.5.4	RX-to-TX turnaround time	683
26.5.5	EVM definition	683
26.5.6	Transmit center frequency and symbol tolerance	684
27.	RCC LMR PHY	685
27.1	RCC PHY overview.....	685
27.2	PPDU format.....	685
27.2.1	General.....	685
27.2.2	SHR.....	685
27.2.3	PHR.....	686
27.2.4	PHY payload.....	686
27.2.5	Tail bits	686
27.3	FEC	686
27.4	Interleaver	687
27.5	Data whitening	687
27.6	Modulation.....	688
27.6.1	GMSK.....	688
27.6.2	4-FSK.....	688
27.6.3	QPSK	689
27.6.4	p/4 DQPSK	689
27.6.5	DSSS DPSK.....	690
27.7	Reference modulator	692
27.8	LMR PHY RF requirements	692
27.8.1	Transmitter symbol rate tolerance	692
27.8.2	Channel switching time	692
27.8.3	Error vector magnitude	692
27.8.4	Receiver sensitivity.....	692
27.8.5	Receiver interference rejection	692
27.8.6	Receiver maximum input level of desired signal.....	693
27.8.7	TX-to-RX turnaround time	693
27.8.8	RX-to-TX turnaround time	693
27.8.9	Receiver ED	693
27.8.10	LQI.....	693
28.	RCC DSSS BPSK PHY	694
28.1	Overview.....	694
28.2	RCC DSSS BPSK PHY specification	694
29.	CMB PHY	695

29.1	CMB O-QPSK PHY specification.....	695
29.1.1	PPDU format for the CMB O-QPSK PHY	695
29.1.2	Modulation and coding for CMB O-QPSK PHY	696
29.1.3	CMB O-QPSK PHY RF requirements	697
29.2	CMB GFSK PHY specification.....	699
29.2.1	PPDU format for CMB GFSK PHY	699
29.2.2	Modulation and coding for CMB GFSK PHY	700
29.2.3	Data whitening for CMB GFSK PHY	702
29.2.4	CMB GFSK PHY RF requirements.....	702
30.	TASK PHY	705
30.1	General.....	705
30.2	PPDU	705
30.2.1	General.....	705
30.2.2	PPDU format.....	705
30.2.3	Generation of PPDU signal.....	708
30.3	MCS mode, MCS, data rates, and related parameters	709
30.3.1	MCS mode	709
30.3.2	Data rates in the 2450 MHz band	709
30.3.3	Data rates in the 780 MHz, 863 MHz, and 915 MHz bands.....	710
30.3.4	Data rates in the 433 MHz and 470 MHz bands.....	710
30.4	FEC, ternary sequence spreading, and pseudo-random chip inversion	711
30.4.1	General.....	711
30.4.2	FEC codes	712
30.4.3	Ternary sequence spreading: Data-symbol-to-chip conversion.....	717
30.4.4	Pseudo-random chip inversion.....	719
30.5	Modulation	721
30.6	Pulse shaping	722
30.7	Representation of the modulated waveforms.....	722
30.8	RF requirements.....	722
30.8.1	Transmit PSD mask	722
30.8.2	Receiver sensitivity.....	723
30.8.3	Interference rejection capability	723
30.8.4	TX-to-RX turnaround time	724
30.8.5	RX-to-TX turnaround time	724
30.8.6	EVM.....	724
30.8.7	Transmit power	724
30.8.8	Transmit center frequency tolerance.....	724
30.8.9	Receiver maximum input level of desired signal.....	724
30.8.10	Receiver ED	724
30.8.11	SNR measurement	724
30.8.12	CCA	724
31.	RS-GFSK PHY	725
31.1	PPDU format.....	725
31.1.1	General.....	725
31.1.2	Preamble field	725
31.1.3	SFD	725
31.1.4	Long PHR	725
31.1.5	Short PHR	726
31.2	Modulation and coding	727
31.2.1	General.....	727

31.2.2	Reference modulator diagram.....	728
31.2.3	Differential encoding	728
31.2.4	Bit-to-symbol mapping	729
31.2.5	Modulation quality.....	729
31.2.6	Frequency deviation tolerance	729
31.2.7	Zero crossing tolerance	730
31.2.8	FEC	730
31.2.9	Code-symbol interleaving.....	730
31.2.10	Data whitening for RS-GFSK.....	730
31.3	Rate switch RS-GFSK	731
31.4	RF requirements.....	731
31.4.1	RF tolerance	731
31.4.2	Channel switch time	731
31.4.3	Receiver sensitivity.....	731
31.4.4	Receiver interference rejection	732
31.4.5	TX-to-RX turnaround time	732
31.4.6	RX-to-TX turnaround time	732
31.4.7	Receiver maximum input level of desired signal.....	732
31.4.8	Receiver ED	732
31.4.9	LQI.....	732
31.4.10	CCA	732
	Annex A (informative) Bibliography	733
	Annex B (normative) CCM* mode of operation	735
	Annex C (informative) Test vectors for cryptographic building blocks.....	741
	Annex D (informative) Protocol implementation conformance statement (PICS) proforma.....	753
	Annex E (normative) Time-slot relaying based link extension (TRLE)	772
	Annex F (informative) Geographic regional frequency band details	797

IEEE Standard for Low-Rate Wireless Networks

1. Overview

1.1 Scope

This standard defines the physical layer (PHY) and medium access control (MAC) sublayer specifications for low-data-rate wireless connectivity with fixed, portable, and moving devices with no battery or very limited battery consumption requirements. In addition, the standard provides modes that allow for precision ranging. PHYs are defined for devices operating in a variety of geographic regions.

1.2 Purpose

The standard provides for ultra low complexity, ultra low cost, ultra low power consumption, and low data rate wireless connectivity among inexpensive devices, especially targeting the communications requirements of what is now commonly referred to as the Internet of Things. In addition, some of the alternate PHYs provide precision ranging capability that is accurate to one meter. Multiple PHYs are defined to support a variety of frequency bands.

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

ANSI X3.66-1979, Advanced Data Communication Control Procedures.¹

Code of Federal Regulations, Title 47: Telecommunication, Part 90—Private Land Mobile Radio Services, Subpart S—Regulations Governing Licensing and Use of Frequencies in the 806–824, 851–869, 896–901, and 935–940 MHz Bands (47 CFR, Part 90, Subpart S).²

Code of Federal Regulations, Title 47: Telecommunication, Part 90—Private Land Mobile Radio Services, Subpart Y—Regulations Governing Licensing and Use of Frequencies in the 4940–4990 MHz Band (47 CFR, Part 90, Subpart Y).

FIPS Pub 197, Advanced Encryption Standard (AES).³

IEEE Std 802[®]-2014, IEEE Standards for Local and Metropolitan Area Networks: Overview and Architecture.^{4, 5}

IETF RFC 6225, Dynamic Host Configuration Protocol Options for Coordinate-Based Location Configuration Information, Internet Engineering Task Force.⁶

¹ANSI publications are available from the American National Standards Institute (<http://www.ansi.org/>)

²CFR publications are available from the U.S. Government Printing Office (<http://www.gpo.gov/>).

³FIPS publications are available from the National Technical Information Service (NTIS) (<http://www.ntis.org/>).

⁴IEEE publications are available from The Institute of Electrical and Electronics Engineers (<http://standards.ieee.org/>).

⁵The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.

⁶IETF RFCs are available from the Internet Engineering Task Force (<http://www.ietf.org/>).