
**Information technology — UPnP
Device Architecture —**

**Part 24-2:
Internet gateway device control
protocol — Level 2 — Wide area
network connection device**

*Technologies de l'information — Architecture de dispositif UPnP —
Partie 24-2: Protocole de contrôle de dispositif de passerelle
Internet — Niveau 2 — Dispositif de connexion de réseau étendu*





COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

CONTENTS

Foreword	iv
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions, symbols and abbreviated terms.....	3
4 Device model.....	3
4.1 Device type	3
4.2 Device architecture	3
4.2.1 Device requirements	3
4.2.2 Relationships between services	5
5 XML Device Description.....	6
6 Test	7
Annex A (informative) Theory of Operation	8
Figure 1 — <i>WANConnectionDevice</i> devices and services hierarchy.....	4
Figure A.1 — Configuration and Connection Management.....	9
Table 1 — Device Requirements	4
Table A.1 — Valid Combinations of <i>LinkType</i> and <i>PossibleConnectionTypes</i>	9

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <http://www.iso.org/directives>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of Standard, the meaning of the ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword – Supplementary information](#)

ISO/IEC 29341-24-2 was prepared by UPnP Forum and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of ISO/IEC 29341 series, under the general title *Information technology — UPnP Device Architecture*, can be found on the [ISO web site](#).

Introduction

ISO and IEC draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights. The holders of -these patent rights have assured ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US;
7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

ISO/IEC 29341-24-2:2017(E)

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Huawei Technologies Co., Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Huawei Technologies Co., Ltd.
Administration Building, Bantian Longgang District
Shenzhen – China 518129

Qualcomm Incorporated has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Qualcomm Incorporated
5775 Morehouse Drive
San Diego, CA – USA 92121

Telecom Italia S.p.A. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Telecom Italia S.p.A.
Via Reiss Romoli, 274
Turin - Italy 10148

Cisco Systems informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA – USA 95134

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Original UPnP Document

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation and later by UPnP Forum. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1:2008
UPnP Device Architecture Version 1.0	ISO/IEC 29341-1:2011
UPnP Device Architecture 1.1	ISO/IEC 29341-1-1:2011
UPnP Device Architecture 2.0	ISO/IEC 29341-1-2
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2008
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2011
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaRenderer:2 Device	ISO/IEC 29341-3-2:2011
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2008
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2011
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2008
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2011
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2008
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2011
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP ScheduledRecording:2	ISO/IEC 29341-4-14:2011
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2008
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2011
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2

ISO/IEC 29341-24-2:2017(E)

UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11
UPnP ContentDirectory:3 Service	ISO/IEC 29341-14-12:2011
UPnP MediaServer:3 Device	ISO/IEC 29341-14-3:2011
UPnP ContentSync:1	ISO/IEC 29341-15-10:2011
UPnP Low Power Architecture:1	ISO/IEC 29341-16-1:2011
UPnP LowPowerProxy:1 Service	ISO/IEC 29341-16-10:2011

UPnP LowPowerDevice:1 Service	ISO/IEC 29341-16-11:2011
UPnP QoS Architecture:3	ISO/IEC 29341-17-1:2011
UPnP QoSDevice:3 Service	ISO/IEC 29341-17-10:2011
UPnP QoSManager:3 Service	ISO/IEC 29341-17-11:2011
UPnP QoSPolicyHolder:3 Service	ISO/IEC 29341-17-12:2011
UPnP QoSDevice:3 Addendum	ISO/IEC 29341-17-13:2011
UPnP RemoteAccessArchitecture:1	ISO/IEC 29341-18-1:2011
UPnP InboundConnectionConfig:1 Service	ISO/IEC 29341-18-10:2011
UPnP RADAConfig:1 Service	ISO/IEC 29341-18-11:2011
UPnP RADASync:1 Service	ISO/IEC 29341-18-12:2011
UPnP RATAConfig:1 Service	ISO/IEC 29341-18-13:2011
UPnP RAClient:1 Device	ISO/IEC 29341-18-2:2011
UPnP RAServer:1 Device	ISO/IEC 29341-18-3:2011
UPnP RADiscoveryAgent:1 Device	ISO/IEC 29341-18-4:2011
UPnP SolarProtectionBlind:1 Device	ISO/IEC 29341-19-1:2011
UPnP TwoWayMotionMotor:1 Service	ISO/IEC 29341-19-10:2011
UPnP AV Architecture:2	ISO/IEC 29341-20-1
UPnP AVTransport:3 Service	ISO/IEC 29341-20-10
UPnP ConnectionManager:3 Service	ISO/IEC 29341-20-11
UPnP ContentDirectory:4 Device	ISO/IEC 29341-20-12
UPnP RenderingControl:3 Service	ISO/IEC 29341-20-13
UPnP ScheduledRecording:2 Service	ISO/IEC 29341-20-14
UPnP MediaRenderer:3 Service	ISO/IEC 29341-20-2
UPnP MediaServer:4 Device	ISO/IEC 29341-20-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-20-4
UPnP InternetGatewayDevice:2 Device	ISO/IEC 29341-24-1
UPnP WANIPConnection:2 Service	ISO/IEC 29341-24-10
UPnP WANIPv6FirewallControl:1 Service	ISO/IEC 29341-24-11
UPnP WANConnectionDevice:2 Service	ISO/IEC 29341-24-2
UPnP WANDevice:2 Device	ISO/IEC 29341-24-3
UPnP Telephony Architecture:2	ISO/IEC 29341-26-1
UPnP CallManagement:2 Service	ISO/IEC 29341-26-10
UPnP MediaManagement:2 Service	ISO/IEC 29341-26-11
UPnP Messaging:2 Service	ISO/IEC 29341-26-12
UPnP PhoneManagement:2 Service	ISO/IEC 29341-26-13
UPnP AddressBook:1 Service	ISO/IEC 29341-26-14
UPnP Calendar:1 Service	ISO/IEC 29341-26-15
UPnP Presense:1 Service	ISO/IEC 29341-26-16
UPnP TelephonyClient:2 Device	ISO/IEC 29341-26-2
UPnP TelephonyServer:2 Device	ISO/IEC 29341-26-3
UPnP Friendly Info Update:1 Service	ISO/IEC 29341-27-1
UPnP MultiScreen MultiScreen Architecture:1	ISO/IEC 29341-28-1
UPnP MultiScreen Application Management:1 Service	ISO/IEC 29341-28-10
UPnP MultiScreen Screen:1 Device	ISO/IEC 29341-28-2
UPnP MultiScreen Application Management:2 Service	ISO/IEC 29341-29-10
UPnP MultiScreen Screen:2 Device	ISO/IEC 29341-29-2
UPnP IoT Management and Control Architecture Overview:1	ISO/IEC 29341-30-1

ISO/IEC 29341-24-2:2017(E)

UPnP DataStore:1 Service	ISO/IEC 29341-30-10
UPnP IoT Management and Control Data Model:1 Service	ISO/IEC 29341-30-11
UPnP IoT Management and Control Transport Generic:1 Service	ISO/IEC 29341-30-12
UPnP IoT Management and Control:1 Device	ISO/IEC 29341-30-2
UPnP Energy Management:1 Service	ISO/IEC 29341-31-1

1 Scope

This document specifies the characteristics of the UPnP networked device named WANConnectionDevice, version 2. This device definition is compliant with *UPnP Device Architecture 1.0* [14] and *UPnP Device Architecture 1.1* [15].

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- [1] InternetGatewayDevice:2, version 1.00, UPnP Forum, December 10, 2010.
Available at <http://upnp.org/specs/gw/UPnP-gw-InternetGatewayDevice-v2-Device.pdf>.
- [2] WANDevice:2, version 1.0, UPnP Forum, September 10, 2010.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANDevice-v2-Device.pdf>.
- [3] WANIPConnection:2, version 1.00, UPnP Forum, September 10, 2010.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANIPConnection-v2-Service.pdf>.
- [4] WANIPv6FirewallControl:1, version 1.0, UPnP Forum, December 10, 2010. Available at: <http://upnp.org/specs/gw/UPnP-gw-WANIPv6FirewallControl-v1-Service.pdf>.
- [5] LANDevice:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-LANDevice-v1-Device.pdf>.
- [6] LANHostConfigManagement:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-LANHostConfigManagement-v1-Service.pdf>.
- [7] Layer3Forwarding:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-Layer3Forwarding-v1-Service.pdf>.
- [8] WANCableLinkConfig:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANCableLinkConfig-v1-Service.pdf>.
- [9] WANCommonInterfaceConfig:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANCommonInterfaceConfig-v1-Service.pdf>.
- [10] WANDSLLinkConfig:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANCableLinkConfig-v1-Service.pdf>.
- [11] WANEthernetLinkConfig:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANEthernetLinkConfig-v1-Service.pdf>.
- [12] WANPOTSLinkConfig:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANPOTSLinkConfig-v1-Service.pdf>.
- [13] WANPPPConection:1, version 1.0, UPnP Forum, November 19, 2001.
Available at: <http://upnp.org/specs/gw/UPnP-gw-WANPPPConection-v1-Service.pdf>.
- [14] *UPnP Device Architecture 1.0*, UPnP Forum.
Available at: <http://upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf>.
- [15] *UPnP Device Architecture 1.1*, UPnP Forum.
Available at: <http://upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.1.pdf>.
- [16] *Data elements and interchange formats – Information interchange -- Representation of dates and times*, International Standards Organization, December 21, 2000.
Available at: [ISO 8601:2000](#).

ISO/IEC 29341-24-2:2017(E)

[17] IETF RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*, T. Berners-Lee, R. Fielding, L. Masinter, January 2005.
Available at: <http://tools.ietf.org/html/rfc3986>.

[18] IETF RFC 3339, *Date and Time on the Internet: Timestamps*, G. Klyne, Clearswift Corporation, C. Newman, Sun Microsystems, July 2002.
Available at: <http://tools.ietf.org/html/rfc3339>.

[19] *Extensible Markup Language (XML) 1.0 (Third Edition)*, François Yergeau, Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, eds., W3C Recommendation, February 4, 2004.
Available at: <http://www.w3.org/TR/2004/REC-xml-20040204>.

[20] *XML Schema Part 2: Data Types, Second Edition*, Paul V. Biron, Ashok Malhotra, W3C Recommendation, 28 October 2004.
Available at: <http://www.w3.org/TR/2004/REC-xmlschema-2-20041028>.

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in [14], [15], [1] and the following apply.

3.1 Abbreviated terms

3.1.1

IGD

Internet Gateway Device

3.1.2

VC

Virtual Circuit

3.1.3

WAN*LinkConfig

any or all of the services WANPOTSLinkConfig [12], WANDSLLinkConfig [10], WANCableLinkConfig [8], WANEthernetLinkConfig [11]

[SOURCE: [1]]

3.1.4

WAN**Connection

either or both of the services WANPPPConnection [13], WANIPConnection [3]

[SOURCE: [1]]

4 Device model

4.1 Device type

A service that complies with this specification shall identify itself with the URN:

urn:schemas-upnp-org:device:WANConnectionDevice:2

All uses of the name WANConnectionDevice in this document specifically refer to version WANConnectionDevice: DeviceVersion of this device type.

4.2 Device architecture

4.2.1 Device requirements

Each WANConnectionDevice models a link on a physical WAN interface. A WANDevice, [2], shall contain one or more instances of WANConnectionDevice corresponding to one or more active links on a modem. WANCommonInterfaceConfig is a service in WANDevice that models attributes and actions that are common across all links and all connection instances on a link.

WANConnectionDevice is a container for a link and connection services specific to a link on a WAN interface. Most types of WAN interfaces can be modeled by a single instance of WANConnectionDevice. However, in the case of DSL, each VC can have unique link attributes and can be provisioned for connection services that are different from other VCs. In this case, each VC will be modeled by an instance of WANConnectionDevice. Also, in the case of a POTS modem based InternetGatewayDevice (IGD), each separate ISP instance can be modeled as an instance of WANConnectionDevice.

The describes the services contained in WANConnectionDevice in more detail.




Figure 1 — **WANConnectionDevice** devices and services hierarchy

Instances of shall implement minimum version numbers of all required embedded devices and services specified in Table 1.

Table 1 — Device Requirements

DeviceType	Root	R/A	ServiceType	R/A ^a	Service ID (prefixed by urn:upnp-org:serviceId:)
			WANPOTSLinkConfig:1	A for POTS modems	WANPOTSLinkC1
			WANDSLLinkConfig:1	A for DSL modems	WANDSLLinkC1
			WANCableLinkConfig:1	A for Cable modems	WANCableLinkC1
			WANEthernetLinkConfig:1	A for Ethernet attached modems	WANEthLinkC1
			WANPPPConnection:1	R for modems that support PPP based connections	Multiple instances possible within a WANConnectionDevice. ServiceIDs for multiple instances will be WANPPPConn1, WANPPPConn2, WANPPPConn3 and so on.
			WANIPConnection:2	R for modems that support IPv4 based connections	Only 1 instance per WANConnectionDevice is envisioned at this time, although the design could support multiple instances in future. ServiceIDs for multiple instances will be WANIPConn1, WANIPConn2, WANIPConn3 and so on.
			WANIPv6FirewallControl:1	A for IPv6 enabled IGDs	Only 1 instance per WANIPv6FirewallControl is envisioned at this time, although the design could support multiple instances in future. ServiceIDs for multiple instances will be WANIPv6Firewall1,

DeviceType	Root	R/A	ServiceType	R/A ^a	Service ID (prefixed by urn:upnp-org:serviceId:)
					<u>WANIPv6Firewall2.</u> <u>WANIPv6Firewall3 and so on.</u>
			<i>Non-standard services embedded by an UPnP vendor go here.</i>	<i>X</i>	<i>TBD</i>
<i>Non-standard devices embedded by an UPnP vendor go here.</i>	<i>TBD</i>	<i>X</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>
^a The term modem in this column refers to the WAN interface (or <u>WANDevice</u>).					

4.2.2 Relationships between services

The DefaultConnectionService state variable in the Layer3Forwarding service refers to the UDN of a WANConnectionDevice instance – this is an external dependency. There may also be dependencies between a specific instance of WAN*LinkConfig and WAN**Connection service or WANIPv6FirewallControl service in a WANConnectionDevice.

5 XML Device Description

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <deviceType>urn:schemas-upnp-org:device:WANConnectionDevice:2</deviceType>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelNumber>model number</modelNumber>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <iconList>
      <icon>
        <mimetype>image/format</mimetype>
        <width>horizontal pixels</width>
        <height>vertical pixels</height>
        <depth>color depth</depth>
        <url>URL to icon</url>
      </icon>
      <!-- XML to declare other icons, if any, go here -->
    </iconList>
    <serviceList>
      <service>
        <serviceType>
          urn:schemas-upnp-org:service:WANDSLLinkConfig1:1
        </serviceType>
        <serviceId>urn:upnp-org:serviceId:WANDSLLinkC1</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      <service>
        <serviceType>
          urn:schemas-upnp-org:service:WANIPConnection2:2
        </serviceType>
        <serviceId>urn:upnp-org:serviceId:WANIPConn1</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      <!--
        Declarations for other services added by UPnP vendor (if any) go here
      -->
    </serviceList>
    <deviceList>
      <!--
        Description of embedded devices added by UPnP vendor (if any) go here
      -->
    </deviceList>
    <presentationURL>URL for presentation</presentationURL>
  </device>
</root>
```

¹ NOTICE for implementers: This template is representative of one link type; DSL in this case. Depending on the type of modem, substitute or add device specific service names.

² NOTICE for implementers: This template is representative of one connection type; IP in this case. Depending on the type of connection, substitute or add service names.

6 Test

No semantic tests are defined for this device.

Annex A (informative)

Theory of Operation

Connections to the Internet are initiated either from the WAN interface of an IGD or are relayed or bridged through the WAN interface. DSL can be provisioned to support multiple Virtual Circuits (VCs) simultaneously. Each VC can in turn be provisioned to support one or more PPP connections or an IP connection. To handle these scenarios, each [WANDevice](#) includes one or more instances of [WANConnectionDevice](#). A [WANConnectionDevice](#) encapsulates a logical or physical link on a WAN interface over which connections are modeled. Furthermore, connections on a WAN interface can be of type PPP or IP. These are modeled by corresponding [WAN**Connection](#) service instances for IPv4 connections or [WANIPv6FirewallControl](#) service instances for IPv6 connections. Properties specific to a link are modeled in a [WAN*LinkConfig](#) service.

The definition of the [WAN*LinkConfig](#)³, [WAN**Connection](#)⁴ and [WANIPv6FirewallControl](#) services are based on the following broad objectives:

- To enable distinguishing between Internet access scenarios that are typically independent of the modem types used and configuration scenarios that are specific to modem types. This enables easier modeling of various connectivity scenarios independent of the underlying modem type or its configuration.
- To support most of the commonly deployed connection types (either originating at the WAN interface of the gateway or relayed/bridged through the gateway).
- To support manual (may need Out-Of-Band security and access control mechanisms) or automatic configuration of parameters on a modem.
- To ensure extensibility for new connection types in future.

Configuration and connectivity scenarios are independent of each other. However, there is an implied relationship in that control points will first need to complete configuration actions (unless this process is completed automatically) before initiating any connectivity related actions. It is also important to note that auto and manual configuration of a modem are mutually exclusive operations in most cases. Furthermore, in most deployment scenarios, auto configuration is given higher priority over manual configuration.

The process of configuration and subsequent management of WAN connections is via 3 variables:

- [LinkType](#): This variable, if defined in a [WAN*LinkConfig](#) service, indicates the protocol configured on a specific link. This variable can be set manually, or through an automatic mechanism (for example, AutoConfig⁵ specified by Broadband Forum).
- [PossibleConnectionTypes](#): specifies only those connection types that are permissible in a particular implementation for a specific modem link configuration (as indicated by the value of [LinkType](#)). This variable is defined in [WAN*Connection](#) service.
- [ConnectionType](#): indicates a specific connection type selected from those permissible on a link, as indicated by [PossibleConnectionTypes](#). This variable is defined in [WAN*Connection](#) service.

Figure A.1 illustrates the process of configuration and connection management, using a DSL modem as an example. Notice that the configuring agent and subsequent user(s) of connections need not be the same network entities. The 4 conceptual steps are:

³ Refer to the individual [WAN*LinkConfig](#) specifications for descriptions of those services and variables such as [LinkType](#).

⁴ Refer to the individual [WAN*Connection](#) specifications for descriptions of those services and variables such as [PossibleConnectionTypes](#) and [ConnectionType](#).

⁵ Refer to the Broadband Forum website (<http://www.broadband-forum.org>) for more details.

- **Step 1:** A configuring entity sets up the LinkType to an appropriate value.
- **Step 2:** The value of LinkType is combined with the capabilities of the modem to come up with a list of possible connection types appropriate for the particular configuration.
- **Step 3:** The variable PossibleConnectionTypes is updated with the list created in Step 2.
- **Step 4:** A control point may subsequently initiate a connection by setting ConnectionType to a value from the allowable list specified in PossibleConnectionTypes. In this step, a control point evaluates its own capabilities vis-à-vis the capabilities exposed in PossibleConnectionTypes and selects one that is appropriate for its use. In some deployment scenarios, the value of ConnectionType may be strictly read-only from a control point perspective.




Figure A.1 — Configuration and Connection Management

Table A.1 lists valid combinations of LinkType and PossibleConnectionTypes as well as connection service type for different types of WAN interfaces.

Table A.1 — Valid Combinations of LinkType and PossibleConnectionTypes

Modem Type	<u>LinkType</u> ^a	Available Modem Capabilities	<u>PossibleConnectionTypes</u> ^a	Connection Service Type
DSL	<u>Unconfigured</u>	Not Applicable	<u>Unconfigured</u>	Not Applicable
	<u>EoA</u>	Bridge	<u>IP_Bridged</u>	<u>WANIPConnection</u>
		Router	<u>IP_Routed</u>	<u>WANIPConnection</u>
	<u>IPoA</u>	Router	<u>IP_Routed</u>	<u>WANIPConnection</u>
	<u>CIP</u>	Router + CIP	<u>IP_Routed</u>	<u>WANIPConnection</u>
	<u>PPPoA</u>	Router	<u>IP_Routed</u>	<u>WANPPPPConnection</u>
		PPTP Relay	<u>PPTP_Relay</u>	<u>WANPPPPConnection</u>
		PPPoE Relay	<u>PPPoE_Relay</u>	<u>WANPPPPConnection</u>
		L2TP Relay	<u>L2TP_Relay</u>	<u>WANPPPPConnection</u>
		DHCP Spoofer	<u>DHCP_Spoofed</u>	<u>WANPPPPConnection</u>
	<u>PPPoE</u>	Router	<u>IP_Routed</u>	<u>WANPPPPConnection</u>

ISO/IEC 29341-24-2:2017(E)

Modem Type	<u>LinkType</u> ^a	Available Modem Capabilities	<u>PossibleConnectionTypes</u> ^a	Connection Service Type
		PPTP Relay	<u>PPTP_Relay</u>	<u>WANPPPConnection</u>
		L2TP Relay	<u>L2TP_Relay</u>	<u>WANPPPConnection</u>
		Bridge	<u>PPPoE_Bridged</u>	<u>WANPPPConnection</u>
		DHCP Spoofer	<u>DHCP_Spoofed</u>	<u>WANPPPConnection</u>
Cable	<u>Ethernet</u>	Router	<u>IP_Routed</u>	<u>WANIPConnection</u>
		Bridge	<u>IP_Bridged</u>	<u>WANIPConnection</u>
POTS	<u>PPP_Dialup</u>	Router	<u>IP_Routed</u>	<u>WANPPPConnection</u>
Ethernet-Attached (External)	<u>Ethernet</u>	Router	<u>IP_Routed</u>	<u>WANIPConnection</u>
		Bridge	<u>IP_Bridged</u>	<u>WANIPConnection</u>
		Router ^b	<u>IP_Routed</u>	<u>WANPPPConnection</u>

^a Refer to the [WAN*LinkConfig](#) service specifications for a more detailed description of each of the [LinkType](#) and [PossibleConnectionTypes](#) values, including abbreviation expansions.

^b NOTICE for implementers: PPP-based connected types, originating from the WAN interface of an IGD, are possible for an Ethernet-attached external modem, most likely over an Ethernet or IP link. For example, a PPPoE connection can originate on the WAN interface of the IGD, terminating at the ISP head-end, with the externally attached modem acting as a pass-through Ethernet bridge. However, modeling this (or other similar) connection type(s) might require additional variables and/or actions in the [WANPPPConnection](#) service not currently defined by the IGD working committee. If needed, these features should be implemented as vendor extensions.

