

INTERNATIONAL ELECTROTECHNICAL COMMISSION

IEC 62341-6-3 Edition 2.0 2017-11

ORGANIC LIGHT EMITTING DIODE (OLED) DISPLAYS –

Part 6-3: Measuring methods of image quality

CORRIGENDUM 1

4.1 Light measuring device

Replace, in the second paragraph, in item 1):

"... and not greater than 0,1 % for luminance values 10 cd/m² and below."

with:

"... and not greater than 10 % for luminance values 0,1 cd/m² and below."

Delete, in the second paragraph, item 5).

Table 6 – Temporal contrast sensitivity function

Replace Table 6 with the following new table:

Frequency (Hz)	Contrast sensitivity	Frequency (Hz)	Contrast sensitivity
1	38,00	39	10,21
2	68,21	40	9,10
3	96,87	41	8,10
4	121,89	42	7,20
5	142,28	43	6,40
6	157,50	44	5,68
7	167,46	45	5,03
8	172,37	46	4,46
9	172,76	47	3,95
10	169,30	48	3,49
11	162,79	49	3,09
12	154,06	50	2,73
13	143,86	51	2,41
14	132,90	52	2,13
15	121,74	53	1,88
16	110,82	54	1,66
17	100,43	55	1,46

Frequency (Hz)	Contrast sensitivity	Frequency (Hz)	Contrast sensitivity
18	90,78	56	1,29
19	81,96	57	1,14
20	73,97	58	1,00
21	66,80	59	0,89
22	60,38	60	0,78
23	54,62	61	0,69
24	49,45	62	0,61
25	44,79	63	0,54
26	40,57	64	0,47
27	36,74	65	0,42
28	33,25	66	0,37
29	30,06	67	0,32
30	27,16	68	0,29
31	24,50	69	0,25
32	22,07	70	0,22
33	19,85	71	0,20
34	17,83	72	0,17
35	16,00	73	0,15
36	14,33	74	0,14
37	12,82	75	0,12
38	11,45		

Figure 20 – Temporal contrast sensitivity function

Replace Figure 20 with the following new figure:

